# NAVAL POSTGRADUATE SCHOOL

## Monterey, California

# THESIS

AN INVESTIGIATION INTO THE CONTROL
LIMITATIONS OF A BANK TO TURN MISSILE
IN THE TERMINAL HOMING PHASE

by

Barton P. Anderson

September 1984

Thesis Advisor: M. D. Hewett

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

| REPORT DOCUMENTATION PAGE | | READ INSTRUCTIONS BEFORE COMPLETING FORM |
|---|---|---|
| 1. REPORT NUMBER | 2. GOVT ACCESSION NO. | 3. RECIPIENT'S CATALOG NUMBER |
| 4. TITLE (and Subtitle) An Investigation Into The Control Limitations of a Bank to Turn Missile in the Terminal Homing Phase | | 5. TYPE OF REPORT & PERIOD COVERED Master's Thesis September 1984 |
| | | 6. PERFORMING ORG. REPORT NUMBER |
| 7. AUTHOR(s) Barton Paul Anderson | | 8. CONTRACT OR GRANT NUMBER(s) |
| 9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Postgraduate School Monterey, California 93943 | | 10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS |
| 11. CONTROLLING OFFICE NAME AND ADDRESS Naval Postgraduate School Monterey, CAlifornia 93943 | | 12. REPORT DATE September 1984 |
| | | 13. NUMBER OF PAGES 205 |
| 14. MONITORING AGENCY NAME & ADDRESS(if different from Controlling Office) | | 15. SECURITY CLASS. (of this report) |
| | | 15a. DECLASSIFICATION/DOWNGRADING SCHEDULE |

16. DISTRIBUTION STATEMENT (of this Report)

Approved for public release, distribution unlimited

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)

18. SUPPLEMENTARY NOTES

19. KEY WORDS (Continue on reverse side if necessary and identify by block number)

Cruise Missile
Bank-to-turn homing
Proportional Navigation
Guidance and Control

20. ABSTRACT (Continue on reverse side if necessary and identify by block number)

The purpose of this thesis was to examine guidance and control deficiencies in a bank to turn (BTT) cruise missile with limited roll authority in the terminal homing phase of its mission. A six degree of freedom simulation of a typical BTT missile was translated into FORTRAN H from the Continuous System Modelling Program (CSMP) simulation language and run on the IBM System 370 computer. Tests were conducted with the revised

DD FORM 1 JAN 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE

S N 0102-LF-014-6601



UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

simulation program to examine the effects of electronic countermeasures (ECM) blinking and glint upon the missile's control system and accuracy against a simulated medium sized combatant vessel traveling at 20 knots perpendicular to the missile's track over the earth. In addition to the standard attack profile involving a popout attack, several other attack profiles were tested including skid-to-turn (STT) control laws and a ballistic trajectory. Miss distances varied from 3.7 feet without ECM or glint to 85 feet with ECM operating. Susceptibility of the missile to ECM blinking varied with the blinking frequency. The largest miss distances occurred with ECM frequencies below 0.2 Hz and near 6.0 Hz. Analysis of the data showed that errors at the low frequencies were primarily caused by the bank command loop of the autopilot. Those at the higher frequency were due to the roll rate command loop. Variation of the geometry of the missile's flight profile had no significant impact upon missile accuracy except that, without a popup maneuver, the roll rate channel demonstrated a marked decrease in effectiveness. Variation of the autopilot gain in the roll rate control loop changed the frequency at which degradation occurred but actually increased its effects. Skid to turn control laws were tested however the missile was unable to produce the necessary sideforce needed to track a passive target and produced undesireable coupling in the flight controls. An attempt to use the altitude command channel to fly a ballistic profile was unsuccessful due to instabilities created in the control system. It is recommended that a popup maneuver be included in the terminal guidance of a BTT cruise missile and that further tests be conducted to determine the extent to which autopilot midifications and gain adjustments can decrease the effectiveness of an ECM blinker against a BTT missile.

Approved for public release; distribution unlimited.

# An Investigation into the Control Limitations of a Bank to Turn Missile in the Terminal Homing Phase

by

Barton P. Anderson
Commander, United States Navy
B.S., Wheaton College, 1970

Submitted in partial fulfillment of the requirements for the degree of

MASTER OF SCIENCE IN AERONAUTICAL ENGINEERING

from the

NAVAL POSTGRADUATE SCHOOL
September 1984

# ABSTRACT

The purpose of this thesis was to examine guidance and control deficiencies in a bank to turn (BTT) cruise missile with limited roll authority in the terminal homing phase of its mission. A six degree of freedom simulation of a typical BTT missile was translated into FORTRAN H from the Continuous System Modelling Program (CSMP) simulation language and run on the IBM System 370 computer. Tests were conducted with the revised simulation program to examine the effects of electronic countermeasures (ECM) blinking and glint upon the missile's control system and accuracy against a simulated medium sized combatant vessel traveling at 20 knots perpendicular to the missile's track over the earth. In addition to the standard attack profile involving a popout attack, several other attack profiles were tested including skid-to-turn (STT) control laws and a ballistic trajectory. Miss distances varied from 3.7 feet without ECM or glint to 85 feet with ECM operating. Susceptibility of the missile to ECM blinking varied with the blinking frequency. The largest miss distances occurred with ECM frequencies below 0.2 HZ and near 6.0 Hz. Analysis of the data showed that errors at the low frequencies were primarily caused by the bank command loop of the autopilot. Those at the higher frequency were due to the roll rate command loop. Variation of the geometry of the missile's flight profile had no significant impact upon missile accuracy except that, without a popup maneuver, the roll rate channel demonstrated a marked decrease in effectiveness. Variation of the autopilot gain in the roll rate control loop changed the frequency at which degradation occurred but actually increased its effects. Skid to turn control laws were tested

however the missile was unable to produce the necessary sideforce needed to track a passive target and produced undesireable coupling in the flight controls. An attempt to use the altitude command channel to fly a ballistic profile was unsuccessful due to instabilities created in the control system. It is recommended that a popup maneuver be included in the terminal guidance of a BTT cruise missile and that further tests be conducted to determine the extent to which autopilot modifications and gain adjustments can decrease the effectiveness of an ECM blinker against a BTT missile.

# TABLE OF CONTENTS

# LIST OF TABLES

LIST OF FIGURES

## ACKNOWLEDGEMENT

The author wishes to acknowledge Dr. Marle D. Hewett, PhD, whose encouragement and advice contributed greatly to this project.

# I. INTRODUCTION

## A. BACKGROUND

Bank-To-Turn (BTT) control is utilized extensively on missiles which must cruise for long ranges within the atmosphere. These missiles utilize a primary lifting surface (wing) and smaller controlling surfaces as on a conventional airplane. This method has two primary advantages. First, the wing provides lift to support the missile's weight at a relatively high efficiency thereby permitting longer ranges for a given size engine and fuel load. Second, the lift vector can be positioned by banking the missile to provide large lateral accelerations resulting in excellent turn performance. Certain BTT cruise missile configurations, however, use differential tail for roll control as opposed to ailerons and suffer from poor roll rate and acceleration performance. It is the investigation into the control limitations of a BTT cruise missile configured this way in the terminal homing phase which is the subject of this thesis.

## B. STATEMENT OF THE PROBLEM

In order to provide compact storage of a BTT missile, the main wings are usually folded back and designed to snap into position as the missile emerges from its cannister at launch. Because of this feature, it is generally not feasible to install roll control devices at the extremities of the wings. Roll control is normally provided by differential actuation of the tail fins of the missile. Because of their short moment arm and small area and because the main wing has a relatively large degree of roll damping, BTT missiles are limited in their ability to roll rapidly.

Because of the need to bank the missile in order to align its lift vector in the desired direction it has been suggested that the requirement for rapid roll maneuvering in the terminal phase of flight would limit the accuracy of the missile. In addition, natural fluctuations in the position of the radar target, known as glint, and artificial fluctuations due to the presence of electronic countermeasures (ECM) might further degrade the performance of a BTT missile.

## C. MISSION SCENARIO

### 1. Control Configuration

The missile simulated in this thesis is a hypothetical bank to turn cruise missile with limited roll control authority. Its design incorporates characteristics typical of many similar designs. The missile is equipped with a standard rudder for yaw control and stabilators for both roll and pitch control. Inner loop closures for stabilization and command are included in the simulation. Command loop closures consist of normal acceleration, bank angle, and lateral acceleration. The lateral acceleration command system can be used as a turn coordinator in the bank-to-turn mode (normal) mode or as a lateral load factor (NY) command system in a skid-to-turn mode. Outer loop closures are provided for altitude and flight path angle. The autopilot control loop design is presented in detail in [Ref. 1].

### 2. Target

The target is assumed to be a surface combatant ship located initially 24,000 feet due North from the missile and moving East at a constant speed of 20 knots. It is assumed that the missile seeker tracks an aim point perfectly. The aim point is located nominally 10 feet above the ship's

waterline and amidships. This aim point continually shifts as a function of ECM blinking and a random glint simulation.

3. ECM Simulation

The ECM blinker simulation shifts the radar target seen by the missile's seeker forward and aft from the true target aim point by ±75 feet along the ships longitudinal axis at a specified frequency. The aim point is simultaneously shifted vertically ±10 feet at the same frequency.

4. Attack Profiles

The attack profile used as a baseline for this simulation began at 50 feet of altitude at a speed of Mach 0.75. The missile tracked toward the target using proportional navigation in azimuth and altitude hold at 50 feet. At a range of 18000 feet the missile rolled to 60 degrees of bank and turned away from the target to the right until the target line of sight was offset by 10 degrees. When the offset was reached, the missile climbed to an altitude of approximately 250 feet and then dove toward the target using proportional navigation in both azimuth and elevation. This mission profile is often referred to as a popout attack.

Variations of this mission included eliminating the 10 degree offset turn and/or the climb to altitude and substituting skid-to-turn control laws for some phase of the mission. A ballistic altitude profile was also attempted.

## D. EXISTING WORK

In order to examine the existence of such problems and to test several proposed solutions, a six degree of freedom simulation of a typical BTT cruise missile was produced by LCDR Kent Watterson and published in [Ref. 1]. This simulation was produced using the IBM Continuous System Modelling

Program (CSMP III) simulation language. A detailed description of this language and its constructions is presented in [Ref. 2] and [Ref. 3]. The simulation included dynamics, autopilot, guidance and mission profiles. It did not represent any specific missile but, rather, included characteristics typical of missiles configured in this way. In order to overcome limitations imposed upon the simulation program by the available computer installation, this CSMP program was rewritten in extended FORTRAN H. This allowed greater flexibility and full utilization of the DISSPLA graphics programming package available at NPS. A complete copy of the program listing is presented in Appendix D.

## E. SCOPE OF TESTS

The tests conducted with the revised simulation program were limited to examining the effects of ECM blinking and glint upon the missile's control system and accuracy against a simulated medium sized combatant vessel traveling at 20 knots perpendicular to the missile's track over the earth. Alternate attack profiles using modified flight geometry and, in some cases, skid-to-turn control laws were also tested. A listing of the different flight profiles examined is presented in table I.

For all flight tests of the missile, certain parameters were held constant. A list of these values is presented in table II.

TABLE I

Missile Attack Profile Test Configurations

| | OFFSET TURN | POP-UP | KROLLP | TURN |
|---|---|---|---|---|
| BASELINE | X | X | 0.5 | BTT |
| II | | X | 0.5 | BTT |
| III | | | 0.5 | BTT |
| IV | | X | 0.1 | BTT |
| V | | X | 0.5 | STT |
| VI | | X | 0.5 | * |

* 90 degree bank on ballistic terminal trajectory

TABLE II

Simulation Variables Held Constant

| Variable Name | Value |
|---|---|
| Radar Burn-Through Range | 500 ft |
| ECM Blinker Shifts: | |
| Longitudinal | ± 75 ft |
| Lateral | ± 00 ft |
| Vertical | ± 10 ft |
| Baseline guidance scheme: | |
| Offset | 10 deg |
| Popup Altitude | 100 ft |
| Popup Range | 18000 ft |
| Roll rate limit | 75 dps |

# II. PROGRAM DESCRIPTION

## A. INTEGRATION OF THE EQUATIONS OF MOTION

This simulation uses the linear, six degree of freedom equations of flight developed by Roskam in [Ref. 5:vol 1] and modified by Hewett in [Ref. 4]. The CSMP program developed by Watterson [Ref. 1] used a variable step Runge-Kutta integration method. The FORTRAN translation program uses a

INTEGRAL(YDOT DT) = Y + (YDOT)*DT (eqn 2.1)

simple Eulerian integration which is given by equation 2.1. The incremental time element, DT, is fixed at 0.01 seconds and the integration period lasts for less than 30 seconds.

## B. PROGRAM NOMENCLATURE

A detailed description of the nomenclature used throughout the simulation program is presented in Appendix C. The variable names used in the FORTRAN translation are, with few exceptions, the same as those used in the the CSMP simulation.

## C. AXIS SYSTEM

The simulation uses a right handed earth reference frame where the x-axis points North, the y-axis points East and the z-axis points down. However, altitude and vertical velocity are always given as positive upwards (i.e. ALTITUDE = -Z). For plotting the geographical track in the output routines, the axes are transformed so that the X,Y,and Z axes point East, North and upward, respectively.

## D. PROGRAM ARCHITECTURE

The FORTRAN simulation program consists of an executive program which calls seven major subroutines which are briefly described as follows.

### 1. Executive Program

The main calling program is short and handles only three tasks. It increments the TIME variable for each integration cycle. It calls the output data storage routine, PREPAR, at the specified output interval and it controls the execution of multiple flights within a single program run changing one or more key variables between the runs.

### 2. Subroutine INIT

This subroutine contains a small section of executable statements which resets variables to their initial value when more than one flight is flown during a program run. Included with this subroutine is the BLOCK DATA subroutine which must be used to initialize all variables in named common areas. The majority of the BLOCK DATA subprogram is taken up with arrays listed in table form which contain the aerodynamic coefficient data for the missile. Static coefficients which are functions of one variable are shown in figures A.2 through A.9 Static coefficients which are functions of two parameters are presented in figures A.10 through A.18 Dynamic coefficients are assumed to be constant and are not presented graphically.

### 3. Subroutine MISSN

This subroutine dictates the mission profile. It is divided into sections which activate in sequence as the mission progresses. Each section takes the flight dynamics data for the missile, compares it with the target

acquisition data (generated in subroutine TGTNAV) and outputs vertical and horizontal acceleration commands in the geographic earth reference frame. These in turn are translated into commanded bank angle and normal load factor for the missile according to equations 2.2 and 2.3. A diagram

PHIC = ARCTAN(AYC/AZC) (eqn 2.2)

NZC = AZC cos(PHI) + AYC sin(PHI) (eqn 2.3)

of these vectors is given in figure A.1. Different terminal attack profiles are implemented using variations of this subroutine, MISSN1 and MISSN2, which are presented in Appendices E and F.

4. Subroutine APILOT

This subroutine takes the commanded normal load factor and bank angle and applies them to the missile autopilot system. A detailed discription of the design of the missile's autopilct is presented in reference [Ref. 1]. The output of the control system is delivered in terms of conventional airplane elevator, aileron and rudder control positions. These are mixed to obtain the commanded missile fin positions. The control limits of ±15 degrees are applied to the fins and these controls are then unmixed to obtain the limited conventional control positions. The dynamics of the servc actuators that move the tail surfaces are modelled as a first order real pole. Although CSMP-III provides macros that perform the simulation of many types of transfer functions within the control system only the first order real pole transfer function was necessary for this program. It is modelled in the FORTRAN translation using subroutine REALPL, presented in the program listing in Appendix C.

5. Subroutine AERO

Subroutine AERO uses two table lookup routines to retrieve the aerodynamic coefficients from the data presented in figures A.2 through A.18 Linear interpolations are used to obtain values between given parameters. Error messages are printed when the input parameters are outside the bounds of the data in the lookup table and these are suppressed after about 5 successive integration cycles. AERO completes the buildup process, uses these data to compute the forces and moments on the aircraft and then integrates the equations of motion to update all of the aircraft's flight parameters and position information.

6. Subroutine TGTNAV

The TGTNAV subroutine navigates the target vessel on a course of East at a steady speel of 20 knots. It shifts the position of the radar target relative to its real position according to the ECM and GLINT parameters. The GLINT offset is produced by multiplying the GLINT shift in each axis by a random number between -1 and 1. The GLINT offset is calculated every output interval rather than 100 times per second. The ECM offset is switched according to the sign of a sine wave which runs at the ECM blinking frequency, FREQ. These offsets are then added to the actual target position to produce the radar target position. Line of sight angles and rates are calculated from this information with the assumption that the seeker has perfect pointing capability.

7. Subroutine PREPAR

At intervals specified by the output counter, this subroutine is called and stores up to 20 variables in a large array call PTS. The output interval used for all tests

was 0.20 sec. The PTS array is passed to the output routines when the simulation run is completed. This subroutine also converts output variables from radian to degree format and, in the final attack phase, calculates four error functions. These error functions are time averaged differences between commanded variables (e.g. BANK or ROLL RATE) and their actual counterparts. These are later used to analyse the performance of the control system under various conditions.

8. Subroutine OUTPUT

OUTPUT produces 3 forms of output information. The primary data output lists the value of MISDST (the distance at which the missile passed the target at its closest approach), the value of the error functions at the end of the mission, and the ranges of all the variables stored. These data are also printed to another file followed by the full contents of the PTS array in tabular form. This gives a numerical history of all the output variables from the start to the finish of the mission. (Normally, to save disk space, this file was routed to a dummy variable. It was needed only when detailed data histories of a portion of the mission were required.)

OUTPUT also calls the necessary DISSPLA routines to print graphs of the output variables. The independent variable in six graphs is TIME. In the seventh graph the positions of the missile and the target ship are plotted in three dimensional space for each output interval. Each of the graphs in this subroutine are controlled by the setting of 7 flags in the first column of the data statement at the beginning of the routine (0 to pass over and 1 to plot).

# III. BASELINE ATTACK CONFIGURATION

## A. AUTOPILOT ROLL RATE COMMAND LOOP ADJUSTMENT

Initial testing of the simulation was conducted on the CSMP version of the program. The frequency of the ECM blinker was varied from 0.2 Hz to a maximum of 2.0 Hz and the roll performance of the missile was graphed. Figure A.19 shows the commanded roll rate and actual roll rate plotted against time for the duration of a thirty second flight straight toward the target at a constant altitude of 50 feet. The target's radar position was blinked at a rate of 0.4 Hz and roll rate command was limited to 75 degrees per sec. In the figure, the command oscillations increased in magnitude as the target range decreased and, after 24 seconds, the autopilot commanded the maximum rate with every shift of the target's apparent position. While the commanded roll rate remained at 75 degrees per second, the actual roll rate never exceeded 35 degrees per second. Figure A.20, which plots the fin positions as a function of time, shows that the fin servos never used more than 3 degrees (of the maximum 15) of travel in either direction. To remedy this problem, the missile autopilot roll rate command loop gain (KROLRT in the program) was increased from 0.1 to 0.5. The value of this gain had been set by Watterson [Ref. 1] using root locus based upon the perturbation equations of motion [Ref. 4] in steady state level flight. Figures A.21 and A.22 show the results of a subsequent run with the revised guidance loop. Steady state error in roll rate was significantly reduced and the full range of available flight controls (±15 deg.) was used. This difference in the autopilot was incorporated into the baseline program and remained throughout all subsequent tests.

## B. BASELINE PROGRAM

In order to provide a baseline performance record against which to examine the effects of ECM and glint and/or alternate attack profiles on the accuracy of the missile and the performance of its control system, a standard, pop-out attack with an offset turn was selected and flown and is used as a standard for comparison. The parameters which apply to this baseline are listed in table II. Figures A.23 through A.28 are a complete record of the baseline program run without any ECM or glint offsets applied to the target. Figures A.29 through A.35 are a complete record of the baseline program run with the ECM blinker operating at 0.2 HZ and the glint feature operating. The complete tabular data output from this latter run is presented in Appendix B.

## IV. FREQUENCY SCAN TESTS

### A. ERROR FUNCTIONS

For testing the effects of glint and ECM at various blinking frequencies against the control system of the missile, a quantitative measure of the system's effectiveness was needed. Four error functions were developed for this purpose. The time weighted difference between the commanded value and the actual value of a variable was computed according to equation 4.1 This time weighted error was summed over all of the time intervals and divided by the

ERR = DT * ABS(COMMAND - VARIABLE) (eqn 4.1)

total time to produce the error function for the variable. The variables for which these functions were computed are

TABLE III

Error Function Variables

| VARIABLE | COMMAND VARIABLE |
|---|---|
| 1. BANK | BANK |
| 2. ROLL RATE | ROLRT |
| 3. AZIMUTH LOS RATE | 0.0 |
| 4. ELEVATION LOS RATE | 0.0 |

listed in Table III. In the terminal phase where proportional guidance is used in both the azimuth and elevation channels, the commanded azimuth and elevation angle rates are zero to produce a constant bearing intercept.

## B. ECM PHASING

At low frequency blinking rates, the phase of the ECM blinker at the start of the mission had a very large effect on the miss distance. To minimize the distortion of the data due to this effect, a phase variable was added to the ECM generator to change the phase of the blinker at the start of each run. Four runs were conducted at each frequency using values of 0.0, PI/2, PI, (3/2)PI for the phase variable. The data for each frequency were averaged to get mean values for the miss distance and each error function.

## C. BASELINE TEST RESULTS

### 1. ECM Frequency Scans

Four simulated flights were conducted at each frequency from 0.0 to 30 Hz. Glint was disabled for the course of these tests. The attack profile flown was the baseline popout attack mission. A graph of the mean value of the miss distance (MISDST) versus frequency is presented in figure A.36 The data show that maximum miss distance occurs in the very low frequency range of the the order of 0.2 Hz and again to a lesser degree in the vicinity of 6 Hz. Figures A.40 and A.44 are plots of the error function means against frequency for the autopilot command errors and the tracking errors respectively. These data show that the bank angle command loop is susceptible to ECM frequencies of the order of 0.2 Hz while the roll rate command loop is primarily responsible for the errors that occur at the higher frequencies in the range of 5 to 10 Hz. Figure A.44 also demonstrates that the time averaged tracking errors follow the same basic pattern.

Figures A.48 through A.53 demonstrate these effects in flight. Figures A.48 and A.51 show the bank angle and

roll rate performance of the baseline missile without ECM. Both variables track closely to their commanded values with the exception of a small, steady state error in the rate channel which is most evident at large commanded rates. Figures A.49 and A.50 show the effects of ECM at 0.4 and 6.0 Hz upon the bank channel. In figure A.49 significant errors exist in bank as the system cannot keep up with the large, sudden changes in commanded bank caused by the ECM shift of the target. The bracket in figure A.49 is drawn between two corresponding points to emphasize the large lag present in the channel. Roll rate tracks close to its commanded level at this frequency.

At 6.0 Hz, figures A.52 and A.53 show the opposite effect. In figure A.53 the bracket emphasizes the large lag that exists in the aircraft roll response to the rapid changes in rate command. The bank command loop at this frequency has effectively filtered out most of the high frequency input.

The results of the frequency scan tests showed that the baseline BTT cruise missile simulated by the program was more susceptible to ECM frequencies in the vicinity of 0.2 and 6.0 Hz due to the excitation of the bank and roll rate command loops respectively. If distances greater than 20 ft from the center of the target are considered likely misses, then the excitation of the roll rate command loop did not produce enough error to cause a likely miss. The best results, from the target's point of view, will be obtained with low blinking frequencies in the vicinity of 0.2 Hz.

### 2. Effects of Glint

In order to isolate the effects of glint, the baseline configuration was flown without ECM or glint and again with glint only. Figure A.33 shows a trace of the random glint

displacement applied to the target's position as a function of time. Figures A.23 through A.28, which trace the missile's load factor, bank angle, roll rate and flight controls without glint, may be compared with figures A.54 through A.57 which show the same traces for the mission with glint.

The miss distance recorded without glint and an ECM phase of 0 was 3.7 feet. The distance measured with glint was 9.4 feet. Although these distances are very small compared with the miss distances achieved with ECM, the degradation induced by glint was large (154 percent) compared to the best obtainable value. Ways of minimizing the effect of random perturbations in the target position due to radar glint will make a significant improvement in the missile's accuracy in the absence of ECM and should be developed.

Since the miss distances without ECM and glint were very small compared to those obtained with very slow blinking frequencies (0.05 to 0.2 Hz), further tests should be run concentrating on ECM in the very low frequency range. These tests should obtain a much larger sample of ECM phases in order to best define the shape of the miss distance curve below 0.2 Hz.

## D. ALTERNATE CONFIGURATION FREQUENCY SCAN RESULTS

### 1. Mission Profile

Similar frequency scan profiles were flown using the MISSN1 (Appendix E) subroutine to generate the guidance commands for configurations II, III and IV. These attack profiles committed the offset turn and proceeded straight toward the target using proportional navigation in azimuth from start to finish. The popup maneuver was commenced at 15000 feet from the target. Of ranges from 20,000 to 5,000

feet which were tested, 15,000 feet produced the most consistent hits with a 200 foot popup altitude command. All subsequent tests of these missile attack configurations used 15,000 ft. popup range and a 200 ft. altitude command when the maneuver was performed.

An algorithm was added to the baseline proportional guidance scheme for the terminal phase which ensured that the missile rolled to place the nearest of the positive or negative Z-axis vectors on the direction commanded by the guidance system. This ensured that the missile would command negative load factor rather than trying to roll the missile upside down as it reached the apex of its climb. Azimuthal accelerations commanded by the guidance were still achieved by banking the missile except for configuration V.

A complete set of mission profile graphs for configurations II, III, and IV against a target with glint and ECM blinking at 0.2 Hz are presented in figures A.58 through A.75

2. Frequency Scan Results

a. Miss Distances

Each configuration was flown against the target four times per test frequency. The tests covered a range of blinker frequencies from 0.05 through 30.0 Hz. The mean miss distances recorded are graphically presented as a function of frequency in figures A.37 through A.39 The results obtained were very similar to those obtained from the baseline configuration. There were two areas of higher than normal errors, one at low frequency below 0.2 Hz and another at a higher frequency near 6.0 Hz. Table IV compares the miss distances for each of the configurations.

The maximum values that occurred for all configurations appeared at the same frequencies with one

TABLE IV

Maximum Miss Distances

| CONFIGURATION | FREQ. RANGE (HZ) | LOCATION (HZ) | MAGNITUDE |
|---|---|---|---|
| BASELINE | 0.20 - 20.0 | ≤ 0.20<br>6.00 | ≥ 45<br>22 |
| II | 0.05 - 21.0 | ≤ 0.05<br>6.00 | ≥ 75<br>17 |
| III | 0.10 - 30.0 | ≤ 0.10<br>5.50 | ≥ 75<br>17 |
| IV | 0.10 - 30.0 | ≤ 0.10<br>N/A | ≥ 75<br>N/A |

exception: changing the roll rate gain from 0.5 to 0.1 eliminated the maximum at the higher frequency. In addition, the magnitude of the errors did not differ significantly. (The baseline shows a smaller magnitude because the data do not extend below 0.2 Hz. while the other configurations were tested down to 0.1 and 0.05 Hz). Changing the attack geometry of the missile did not significantly alter its susceptibility to ECM jamming within the scope of these tests. Altering the gain of the roll rate command channel in the missile autopilot significantly decreased its susceptibility to ECM blinking at higher frequencies. Further testing should be conducted to determine the extent to which autopilot modifications and gain adjustments can decrease the effectiveness of an ECM blinker against a bank to turn missile.

b. Autopilot Errors

Figures A.40 through A.43 graphically present the error functions for both the bank angle and roll rate command loops within the autopilot. These functions are representative of the ability of the missile to follow the

commands given it by the autopilot (the higher the function, the poorer the performance). As with the baseline configuration these figures demonstrate that the bank angle loop contributed most to the errors at low frequency and the roll rate loop contributed most at the higher frequency. Table V

**TABLE V**

**Autopilot Errors**

| ONFIGURATION | BANK ERROR | | RATE ERROR | |
|---|---|---|---|---|
| | FREQ. (HZ) | MAGNITUDE | FREQ. (HZ) | MAGNITUDE |
| BASELINE | 0.4 | 0.22 | 7.0 | 0.19 |
| II | 0.6 | 0.17 | 8.0 | 0.18 |
| III | 0.5 | 0.18 | 8.0 | 0.27 |
| IV | 0.6 | 0.21 | 2.0 | 0.37 |

is a summary of these graphs.

Magnitude of the bank error function and the frequency at which it occurred were not significantly altered in any one of the tested configurations. Changing the geometry of the attack had no effect on the frequency at which ECM was most effective against the roll rate control system, however the magnitude of the errors were increased by approximately 50 percent when the popup maneuver was eliminated (configuration III).

Decreasing the roll rate autopilot gain from 0.5 to 0.1 (configuration IV) moved the resonant frequency for the roll rate command system to a lower frequency but

increased the magnitude of the errors by more than 100 percent. This effect is reflected in the miss distance graphs (figures A.36 through A.39) in the disappearance of the distinct maximum at 6 HZ and a widening of the lower maximum (figure A.39). Altering the autopilot gain was effective at moving the resonant frequency to a different region but could not eliminate its effect.

c. Tracking System Errors

Errors in the tracking loops are charted in figures A.44 through A.47. These errors follow the trends of the autopilot and miss distance errors. At the lower frequencies, azimuth performance was dominant while at higher frequencies the elevation tracking loop experienced the largest degradation.

3. Skid To Turn Guidance Results

The MISSN1 subroutine was further modified to allow the lateral load factor command variable, NYC, to be set according to guidance commands rather than being kept at zero for turn coordination purposes. The commanded bank angle was set to zero in the terminal phase in order to examine the effectiveness of lateral G command. No changes to the basic dynamics of the autopilot were made. The missile was flown in this configuration against a passive target. Figures A.76 through A.81 present the full data set from this test. The missile splashed into the water 99 feet left and short of the target. Once the missile came within 5 seconds of impact, cross coupling between the rudder channel and normal load factor, roll rate and bank can be seen in the figures. Although the rudder commands were never saturated, neither could the lateral load factor control loop create enough sideforce to follow the ship's lateral drift to the right. The addition of ECM and/or glint would have

only worsened the performance of the missile in this configuration. No further tests of this configuration were conducted. The use of skid-to-turn control laws could not produce sufficient sideforce to adequately follow a passive crossing target and produced excessive coupling into the longitudinal and lateral flight controls of the missile.

### 4. Ballistic Trajectory

Because the majority of the apparent target shift with ECM blinking occurs in the horizontal plane, an attempt was made to place the missile on a ballistic trajectory and then roll the aircraft to 90 degrees angle of bank until impact using the primary load factor to follow the ECM target and lateral load factor to maintain the ballistic trajectory. In order to fly the ballistic trajectory, the altitude hold system was driven by a commanded altitude slaved to a parabolic trajectory derived from the missile's vertical speed and range to the target according to equation

$$ALT = HMDOT*RANGE/VH + (G/2)*(RANGE/VT)^2 + 10 \quad \text{(eqn 4.2)}$$

4.2. where HMDOT,VH and VT are the vertical, horizontal and total speeds of the missile. The controlling subroutine used for this mission was MISSN2 and is presented in Appendix F.

Figures A.82 through A.85 show that the addition of the dynamics of the altitude command loop made the missile's control system unstable. Oscillations to the limits occurred in normal load factor and in roll rate. Considerable cross coupling occurred between the lateral-directional and longitudinal dynamics of the missile. The attempt to fly a ballistic trajectory using the existing altitude control system was unsuccessful. In order to fly the attempted profile, a major redesign of the missile's autopilot would be necessary.

# V. CONCLUSIONS

The conclusions listed below were derived from analysis of the results of simulated flights conducted using the baseline popout attack profile configuration, three variations of the baseline attack, a skid-to-turn control configuration and a ballistic altitude trajectory.

## A. BASELINE CONFIGURATION TESTS

At low frequency blinking rates, the phase of the ECM blinker had a very large effect on the miss distance.

The best obtainable performance for the baseline mission without ECM or glint was a miss distance of 3.7 feet. The addition of GLINT produced a miss distance of 9.7 feet, a degradation of 154 percent.

The bank angle command loop of the missile autopilot in the baseline configuration was especially susceptible to ECM frequencies of the order of 0.2 Hz while the roll rate command loop was primarily affected at the higher frequencies in the range of 5 to 10 Hz. The time averaged tracking errors also followed the same basic pattern.

If distances greater than 20 ft from the center of the target are considered likely misses, then the excitation of the roll rate command loop did not produce enough error to cause a likely miss. The best results, from the target's point of view, will be obtained with low blinking frequencies in the vicinity of 0.2 Hz.

## B. ALTERNATE ATTACK PROFILE CONFIGURATIONS

In terms of the average miss distances measured, changing the flight geometry of the missile did not signifi-

cantly alter its susceptibility to ECM jamming within the scope of these tests.

Altering the gain of the roll rate command channel in the baseline missile autopilot significantly decreased its susceptibility to ECM blinking at higher frequencies.

Changing the geometry of the attack had no effect on the magnitude of the bank error function and the frequency at which its maximum occurred.

Changing the roll rate gain from 0.5 to 0.1 had no noticeable affect on the magnitude of the bank error function and the frequency at which its maximum occurred.

Changing the geometry of the attack had no effect on the frequency at which ECM was most effective against the roll rate control system, however the magnitude of the errors were increased by approximately 50 percent when the popup maneuver was eliminated (configuration III).

Decreasing the roll rate autopilot gain from 0.5 to 0.1 (configuration IV) moved the resonant frequency for the roll rate command system to a lower frequency but increased the magnitude of the errors by more than 100 percent. This effect was reflected in the miss distance data by the disappearance of the distinct maximum at 6 HZ and a widening of the lower maximum. Altering the autopilot gain was effective at moving the resonant frequency to a different region but could not eliminate its effect and, in this case enlarged it.

Errors in the azimuth and elevation tracking loops closely followed the trends of the autopilot and miss distance errors. At the lower frequencies, azimuth performance was dominant while at higher frequencies the elevation tracking loop experienced the largest degradation.

## C. SKID TO TURN CONTROL

The use of skid-to-turn control laws could not produce sufficient sideforce to adequately follow a passive crossing target and produced excessive coupling into the longitudinal and lateral flight controls of the missile.

## D. BALLISTIC ATTACK PROFILE

The attempt to fly a ballistic trajectory using the existing altitude control system was unsuccessful. In order to fly the attempted profile, a major redesign of the missile's autopilot would be necessary.

# VI. RECOMMENDATIONS

Ways of minimizing the effect of random perturbations in the target position due to radar glint will make a significant improvement in the missile's accuracy in the absence of ECM and should be developed.

Further testing should be conducted to determine the extent to which autopilot modifications and gain adjustments can decrease the effectiveness of an ECM blinker against a bank to turn missile.

Since the elimination of a popup increased roll rate errors by 50 percent, a popup profile is recommended for the terminal phase of a BTT cruise missile. Further testing should be conducted to determine the effects of different popup profiles on the susceptibility of the roll rate command system to ECM blinking.

Since the miss distances without ECM and glint were very small compared to those with very slow blinking frequencies (0.05 to 0.2 Hz), further tests should be run concentrating on ECM in the very low frequency range. These tests should obtain a much larger sample of ECM phases in order to best define the shape of the miss distance curve below 0.2 Hz.

# APPENDIX A

FIGURES




Figure A.1 Load Factor Commands.




Figure A.2 Data Array LFT1.




Figure A.3 Data Array LFT2.




Figure A.4 Data Array DRG1.




Figure A.5 Data Array DRG2.




Figure A.6    Data Array DRG3.




Figure A.7 Dara Array DRG4.




Figure A.8 Data Array PTCH1.




Figure A.9 Data Array PTCH2.




Figure A.10    Data Array SID1.




Figure A.11 Data Array SID2.




Figure A.12 Data Array SID3.




Figure A.13 Data Array DREC1.




Figure A.14 Data Array DREC2.




Figure A.15 Data Array DREC3.




Figure A.16 Data Array LTRL1.




Figure A.17 Data Array LTFL2.




Figure A.18 Data Array LTRL3.




Figure A.19 CSMP Data (Roll Rate) - KRØLLR = 0.1.




Figure A.20 CSMP Data (Controls) - KROLLP = 0.1.



Figure A.21 CSMP Data (Roll Rate) - KROLLR = 0.5.




Figure A.22   CSMP Data (Controls) - Krollr = 0.5.




Figure A.23 Baseline - no ECM or GLINT - Load Factor.




Figure A.24 Baseline - no ECM or GLINT - Roll Rate.




Figure A.25 Baseline - no ECM or GLINT - Bank.




Figure A.26 Baseline - no ECM or GLINT - Controls.




Figure A.27 Baseline - no ECM or GLINT - Altitude.




Figure A.28 Baseline - no ECM or GLINT - Geo Plot.




Figure A.29 Baseline with GLINT & ECM - Load Factor.




Figure A.30 Baseline with GLINT & ECM - Bank.




Figure A.31 Baseline with GLINT & ECM - Roll Rate.




Figure A.32   Baseline with GLINT & ECM - Controls.




Figure A.33 Baseline with GLINT & ECM - ECM & GLINT.




Figure A.34 Baseline with GLINT & ECM - Altitude.




Figure A.35   Baseline with GLINT & ECM - Geo Plot.




Figure A.36 Mean Miss Distances - Baseline.




Figure A.37 Mean Miss Distances - Configuration II.




Figure A.38 Mean Miss Distances - Configuration III.




Figure A.39 Mean Miss Distances - Configuration IV.


Figure A.40 Autopilot Errors - Baseline.




Figure A.41 Autopilot Errors - Configuration II.




Figure A.42 Autcpilot Errors - Configuration III.




Figure A.43 Autopilot Errors - Configuration IV.




Figure A.44 Tracking Errors - Baseline.




Figure A.45 Tracking Errors - Configuration II.




Figure A.46 Tracking Errors - Configuration III.




Figure A.47 Tracking Errors - Configuration IV.




Figure A.48 Baseline/ECM Freq = 0.0 Hz - Bank.




Figure A.49 Baseline/ECM Freq = 0.4 Hz - Bank.




Figure A.50 Baseline/ECM Freq = 6.0 Hz - Bank.




Figure A.51 Baseline/ECM Freq = 0.0 Hz - Roll Rate.




Figure A.52 Baseline/ECM Freq = 0.4 Hz - Roll Rate.




Figure A.53 Baseline/ECM Freq = 6.0 Hz - Roll Rate.




Figure A.54 Baseline with GLINT only - Load Factor.




Figure A.55 Baseline with GLINT only - Bank.




Figure A.56 Baseline with GLINT only - Roll Rate.




Figure A.57 Baseline with GLINT only - Controls.




Figure A.58 Conf. II Mission Set - Load Factor.




Figure A.59 Conf. II Mission Set - Bank.




Figure A.60    Conf. II Mission Set - Roll Rate.




Figure A.61 Conf. II Mission Set - Controls.




Figure A.62 Conf. II Mission Set - Altitude.




Figure A.63   Conf. II Mission Set - Geo Plot.




Figure A.64 Conf. III Mission Set - Load Factor.




Figure A.65 Conf. III Mission Set - Bank.




Figure A.66 Conf. III Mission Set - Roll Rate.




Figure A.67 Conf. III Mission Set - Controls.




Figure A.68 Conf. III Mission Set - Altitude.




Figure A.69   Conf. III Mission Set - Geo Plot.




Figure A.70 Conf. IV Mission Set - Load Factor.




Figure A.71 Conf. IV Mission Set - Bank.




Figure A.72   Conf. IV Mission Set - Roll Rate.




Figure A.73 Conf. IV Mission Set - Controls.




Figure A.74 Conf. IV Mission Set - Altitude.




Figure A.75 Conf. IV Mission Set - Geo Plot.




Figure A.76 Conf. V Mission Set - Load Factor.




Figure A.77 Conf. V Mission Set - Bank.




Figure A.78 Conf. V Mission Set - Roll Rate.




Figure A.79 Conf. V Mission Set - Controls.




Figure A.80 Conf. V Mission Set - Altitude.




Figure A.81 Conf. V Mission Set - Geo Plot.




Figure A.82 Conf. VI Mission Set - Load Factor.




Figure A.83 Conf. VI Mission Set - Bank.




Figure A.84 Conf. VI Mission Set - Roll Rate.




Figure A.85 Conf. VI Mission Set - Controls.

# APPENDIX B

## SIMULATION PROGRAM TABULAR DATA OUTPUT

```
*********************************************************************

                    CRUISE MISSILE TESTS
                    BASELINE MISSION SET
                  GLINT PLUS ECM AT 0.2 HZ
                          9-19-84

SIMULATICN TERMINATED DUE TO CPA
*** BLINKER FREQUENCY=      0.20
*** BLINKER PHASE    =      0.

   MISS     * ==================== ERROR FUNCTIONS ====================*
 DISTANCE   *     BANK     *    ROLLRATE   *    AZIMUTH    *   ELEVATION   *

  42.87372  *     0.20466  *     0.11202   *     0.03046   *     0.00866   *


              ******* RANGES FOR ALL SAVED VARIABLES *******

                              MINIMUM          MAXIMUM

        TIME......(SEC)        0.190000        29.061737
        NZC.........(G)        0.289882         4.000000
        NZ..........(G)        0.551692         3.750864
        BANKC.....(DEG)     -115.634293        92.840149
        BANK......(DEG)     -115.765106        84.187943
        R/RT CMD..(DPS)      -74.999985        74.999985
        RCLL RATE.(DPS)      -73.526184        73.167145
        ECM SHIFT..(FT)      -75.000000        75.000000
        GLINT SHIFT(FT)      -47.924805        47.070313
        STBLTR....(DEG)      -15.000000         7.934396
        AILRCN....(DEG)       -6.261881         0.000000
```

| | | |
|---|---|---|
| RUDDER....(DEG) | -3.446685 | 3.952714 |
| ALTITUDE...(FT) | 13.361130 | 250.106537 |
| XM...(FT NORTH) | 159.440155 | 23887.324200 |
| YM....(FT EAST) | -3.526452 | 1771.405030 |
| XT...(FT NORTH) | 24000.000000 | 24000.000000 |
| XM....(FT EAST) | 6.649995 | 1017.160640 |
| RANGE......(FT) | 116.888184 | 23840.589800 |
| PHASE MARKER | 0.000000 | 4.000000 |

CRUISE MISSILE TESTS
BASELINE MISSION SET
GLINT PLUS ECM AT 0.2 HZ
9-19-84

*** BLINKER FREQUENCY= 0.20

DATA SET NUMBER 1 OF 4

| TIME......(SEC) | NZC.........(G) | NZ..........(G) | BANKC.....(DEG) | BANK......(DEG) |
|---|---|---|---|---|
| * 0.190000 | * 0.996454 | * 0.984984 | * 6.838765 | * 5.825313 |
| * 0.380000 | * 1.002067 | * 0.939250 | * 6.808969 | * 6.542444 |
| * 0.570000 | * 1.012286 | * 0.935853 | * 6.645293 | * 6.510144 |
| * 0.759999 | * 1.022474 | * 0.946949 | * 6.546911 | * 6.396442 |
| * 0.949999 | * 1.030748 | * 0.962120 | * 6.503017 | * 6.327559 |
| * 1.139989 | * 1.036386 | * 0.977738 | * 6.458877 | * 6.279079 |
| * 1.329975 | * 1.039639 | * 0.991862 | * 6.589023 | * 6.328140 |
| * 1.519961 | * 1.040093 | * 1.004217 | * 6.606047 | * 6.386812 |
| * 1.709948 | * 1.038448 | * 1.014323 | * 6.744779 | * 6.470833 |
| * 1.899934 | * 1.034911 | * 1.021769 | * 6.918423 | * 6.623720 |
| * 2.089920 | * 1.029593 | * 1.027047 | * 7.007813 | * 6.747380 |
| * 2.279906 | * 1.023017 | * 1.030146 | * 7.091106 | * 6.834517 |
| * 2.469893 | * 1.015957 | * 1.030586 | * 7.323808 | * 7.001084 |
| * 2.659879 | * 1.008910 | * 1.028598 | * 7.696206 | * 7.294130 |
| * 2.849865 | * 1.002075 | * 1.024692 | * 8.092773 | * 7.688922 |
| * 3.039851 | * 0.995503 | * 1.020577 | * 8.427306 | * 8.050833 |
| * 3.229837 | * 0.989452 | * 1.015759 | * 8.742263 | * 8.377364 |
| * 3.419824 | * 0.983882 | * 1.010625 | * 8.969087 | * 8.645678 |
| * 3.609810 | * 0.979212 | * 1.005136 | * 9.224430 | * 8.892548 |
| * 3.799796 | * 0.975287 | * 0.999566 | * 9.405898 | * 9.108006 |
| * 3.989782 | * 0.972403 | * 0.994111 | * 9.605278 | * 9.302847 |
| * 4.179769 | * 0.970392 | * 0.988990 | * 9.752930 | * 9.474633 |
| * 4.369755 | * 0.969642 | * 0.984181 | * 9.988882 | * 9.674054 |

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| * | 4.559741 | * | 0.969938 | * | 0.979871 | * | 10.235960 | * | 9.915122 |
| * | 4.749727 | * | 0.970555 | * | 0.976926 | * | 10.297152 | * | 10.058768 |
| * | 4.939713 | * | 0.972024 | * | 0.974900 | * | 10.423241 | * | 10.161740 |
| * | 5.129700 | * | 0.973534 | * | 0.973648 | * | 10.384534 | * | 10.226965 |
| * | 5.319686 | * | 0.974787 | * | 0.973969 | * | 10.169158 | * | 10.063795 |
| * | 5.509672 | * | 0.976223 | * | 0.974415 | * | 9.974829 | * | 9.865085 |
| * | 5.699658 | * | 0.977961 | * | 0.974676 | * | 9.844348 | * | 9.706358 |
| * | 5.889645 | * | 0.980385 | * | 0.974635 | * | 9.898959 | * | 9.676970 |
| * | 6.079631 | * | 0.982658 | * | 0.975111 | * | 9.851148 | * | 9.668716 |
| * | 6.269617 | * | 0.985226 | * | 0.976146 | * | 9.896841 | * | 9.674454 |
| * | 6.459603 | * | 0.987471 | * | 0.977697 | * | 9.856885 | * | 9.669850 |
| * | 6.649590 | * | 0.989611 | * | 0.979646 | * | 9.846107 | * | 9.647703 |
| * | 6.839576 | * | 0.991370 | * | 0.981773 | * | 9.794549 | * | 9.613314 |
| * | 7.029562 | * | 0.993606 | * | 0.983401 | * | 9.991375 | * | 9.700686 |
| * | 7.219548 | * | 0.998174 | * | 0.949411 | * | 59.999954 | * | 11.834122 |
| * | 7.409534 | * | 1.097366 | * | 0.834173 | * | 59.999954 | * | 24.587097 |
| * | 7.599521 | * | 1.299035 | * | 0.803401 | * | 59.999954 | * | 37.007568 |
| * | 7.789507 | * | 1.677993 | * | 0.811473 | * | 59.999954 | * | 49.419754 |
| * | 7.979493 | * | 2.247486 | * | 0.916378 | * | 59.999954 | * | 58.482132 |
| * | 8.169479 | * | 2.473261 | * | 1.204178 | * | 59.999954 | * | 59.601837 |
| * | 8.359466 | * | 2.579926 | * | 1.523088 | * | 59.999954 | * | 59.680084 |
| * | 8.549452 | * | 2.618698 | * | 1.830282 | * | 59.999954 | * | 59.636536 |
| * | 8.739438 | * | 2.589437 | * | 2.115276 | * | 59.999954 | * | 59.560257 |
| * | 8.929424 | * | 2.495302 | * | 2.347334 | * | 59.999954 | * | 59.475677 |
| * | 9.119411 | * | 2.347077 | * | 2.504561 | * | 59.999954 | * | 59.397644 |
| * | 9.309397 | * | 2.161033 | * | 2.576699 | * | 59.999954 | * | 59.342728 |
| * | 9.499383 | * | 1.955719 | * | 2.563868 | * | 59.999954 | * | 59.316010 |
| * | 9.689369 | * | 1.749104 | * | 2.477899 | * | 59.999954 | * | 59.314651 |
| * | 9.879355 | * | 1.557662 | * | 2.332685 | * | 59.999954 | * | 59.346558 |
| * | 10.069342 | * | 1.394344 | * | 2.146254 | * | 59.999954 | * | 59.401413 |
| * | 10.259328 | * | 1.268426 | * | 1.938939 | * | 59.999954 | * | 59.469284 |
| * | 10.449314 | * | 1.184954 | * | 1.730132 | * | 59.999954 | * | 59.540421 |
| * | 10.639300 | * | 1.144872 | * | 1.536979 | * | 59.999954 | * | 59.606598 |
| * | 10.829287 | * | 0.850376 | * | 1.371496 | * | 0.000000 | * | 47.876846 |
| * | 11.019273 | * | 0.654307 | * | 1.266437 | * | 0.000000 | * | 34.769897 |
| * | 11.209259 | * | 0.533505 | * | 1.138158 | * | 0.000000 | * | 21.793655 |
| * | 11.399245 | * | 0.464801 | * | 1.010703 | * | 0.000000 | * | 8.865244 |
| * | 11.589231 | * | 0.440546 | * | 0.917152 | * | 0.000000 | * | 0.877188 |
| * | 11.779218 | * | 0.437432 | * | 0.851973 | * | 0.000000 | * | -0.043441 |

CRUISE MISSILE TESTS
BASELINE MISSION SET
GLINT PLUS ECM AT 0.2 HZ
9-19-84

*** BLINKER FREQUENCY= 0.20

DATA SET NUMBER 1 OF 4

| | TIME......(SEC) | | NZC.........(G) | | NZ..........(G) | | BANKC.....(DEG) | | BANK......(DEG) |
|---|---|---|---|---|---|---|---|---|---|
| * | 11.969204 | * | 0.450394 | * | 0.768242 | * | 0.000000 | * | -0.161884 |
| * | 12.159190 | * | 0.482046 | * | 0.685690 | * | 0.000000 | * | -0.162543 |
| * | 12.349176 | * | 0.531986 | * | 0.614517 | * | 0.000000 | * | -0.139814 |
| * | 12.539163 | * | 0.597679 | * | 0.569422 | * | 0.000000 | * | -0.120249 |
| * | 12.729149 | * | 0.674333 | * | 0.551692 | * | 0.000000 | * | -0.108467 |
| * | 12.919135 | * | 0.757205 | * | 0.557850 | * | 0.000000 | * | -0.104236 |
| * | 13.109121 | * | 0.841999 | * | 0.584029 | * | 0.000000 | * | -0.105790 |
| * | 13.299108 | * | 0.924948 | * | 0.626355 | * | 0.000000 | * | -0.111387 |
| * | 13.489094 | * | 1.002849 | * | 0.679794 | * | 0.000000 | * | -0.119782 |
| * | 13.679080 | * | 1.073686 | * | 0.738611 | * | 0.000000 | * | -0.132744 |
| * | 13.869066 | * | 1.135511 | * | 0.804878 | * | 0.000000 | * | -0.148209 |
| * | 14.059052 | * | 1.186506 | * | 0.874575 | * | 0.000000 | * | -0.164867 |
| * | 14.249039 | * | 1.225576 | * | 0.943938 | * | 0.000000 | * | -0.181834 |
| * | 14.439025 | * | 1.252302 | * | 1.009762 | * | 0.000000 | * | -0.198240 |
| * | 14.629011 | * | 1.266858 | * | 1.069501 | * | 0.000000 | * | -0.213442 |
| * | 14.818997 | * | 1.269832 | * | 1.123638 | * | 0.000000 | * | -0.226920 |
| * | 15.008984 | * | 1.261657 | * | 1.169641 | * | 0.000000 | * | -0.238204 |
| * | 15.198970 | * | 1.243847 | * | 1.203627 | * | 0.000000 | * | -0.246988 |
| * | 15.388956 | * | 1.218340 | * | 1.225422 | * | 0.000000 | * | -0.253153 |
| * | 15.578942 | * | 1.187195 | * | 1.235477 | * | 0.000000 | * | -0.256717 |
| * | 15.768929 | * | 1.152465 | * | 1.234756 | * | 0.000000 | * | -0.257825 |
| * | 15.958915 | * | 1.116103 | * | 1.224596 | * | 0.000000 | * | -0.256717 |
| * | 16.148834 | * | 1.079892 | * | 1.206601 | * | 0.000000 | * | -0.253706 |
| * | 16.338730 | * | 1.045380 | * | 1.182526 | * | 0.000000 | * | -0.249153 |
| * | 16.528625 | * | 1.013837 | * | 1.154176 | * | 0.000000 | * | -0.243445 |
| * | 16.718521 | * | 0.986244 | * | 1.123310 | * | 0.000000 | * | -0.236972 |
| * | 16.908417 | * | 0.963268 | * | 1.092164 | * | 0.000000 | * | -0.230110 |
| * | 17.098312 | * | 0.944965 | * | 1.063701 | * | 0.000000 | * | -0.223170 |
| * | 17.288208 | * | 0.931297 | * | 1.036421 | * | 0.000000 | * | -0.216391 |
| * | 17.478104 | * | 0.922266 | * | 1.011223 | * | 0.000000 | * | -0.210006 |
| * | 17.667999 | * | 0.917679 | * | 0.988825 | * | 0.000000 | * | -0.204210 |
| * | 17.857895 | * | 0.917206 | * | 0.969775 | * | 0.000000 | * | -0.199162 |
| * | 18.047791 | * | 0.920379 | * | 0.954433 | * | 0.000000 | * | -0.194973 |
| * | 18.237686 | * | 0.926643 | * | 0.942978 | * | 0.000000 | * | -0.191712 |
| * | 18.427582 | * | 0.935383 | * | 0.935418 | * | 0.000000 | * | -0.189403 |
| * | 18.617477 | * | 0.945946 | * | 0.931596 | * | 0.000000 | * | -0.188026 |
| * | 18.807373 | * | 0.957685 | * | 0.931231 | * | 0.000000 | * | -0.187529 |
| * | 18.997269 | * | 0.969978 | * | 0.933928 | * | 0.000000 | * | -0.187827 |
| * | 19.187164 | * | 0.982247 | * | 0.939216 | * | 0.000000 | * | -0.188814 |
| * | 19.377060 | * | 4.000000 | * | 0.956647 | * | -19.212936 | * | -11.716519 |

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| * | 19.566956 | * | 4.000000 | * | 1.336203 | * | -19.645432 | * | -18.829987 |
| * | 19.756851 | * | 4.000000 | * | 1.953647 | * | -20.514221 | * | -20.287003 |
| * | 19.946747 | * | 4.000000 | * | 2.603067 | * | -21.803818 | * | -21.606384 |
| * | 20.136642 | * | 4.000000 | * | 3.165137 | * | -23.917358 | * | -23.416321 |
| * | 20.326538 | * | 4.000000 | * | 3.547853 | * | -26.628387 | * | -25.876419 |
| * | 20.516434 | * | 3.993346 | * | 3.707689 | * | -29.875137 | * | -28.782227 |
| * | 20.706329 | * | 3.645613 | * | 3.750864 | * | -33.380920 | * | -32.118164 |
| * | 20.896225 | * | 3.328323 | * | 3.695785 | * | -37.201050 | * | -35.788803 |
| * | 21.086121 | * | 1.394300 | * | 3.743388 | * | -86.270721 | * | -41.193802 |
| * | 21.276016 | * | 1.548610 | * | 3.527078 | * | -91.988892 | * | -54.749466 |
| * | 21.465912 | * | 1.641810 | * | 3.080334 | * | -97.266113 | * | -67.457657 |
| * | 21.655807 | * | 1.692579 | * | 2.546545 | * | -102.053802 | * | -80.066727 |
| * | 21.845703 | * | 1.737501 | * | 2.077121 | * | -106.587250 | * | -92.754532 |
| * | 22.035599 | * | 1.724108 | * | 1.733549 | * | -109.825348 | * | -105.360977 |
| * | 22.225494 | * | 1.644519 | * | 1.687409 | * | -111.873642 | * | -110.729401 |
| * | 22.415390 | * | 1.576145 | * | 1.724775 | * | -113.156738 | * | -112.752167 |
| * | 22.605286 | * | 1.476245 | * | 1.736968 | * | -114.502014 | * | -113.975922 |
| * | 22.795181 | * | 1.340478 | * | 1.709265 | * | -115.634293 | * | -115.439880 |
| * | 22.985077 | * | 1.156681 | * | 1.647637 | * | -115.251144 | * | -115.765106 |
| * | 23.174973 | * | 1.009784 | * | 1.550969 | * | -114.067169 | * | -115.013672 |
| * | 23.364868 | * | 0.838435 | * | 1.428517 | * | -110.889008 | * | -112.811676 |
| * | 23.554764 | * | 0.704791 | * | 1.297051 | * | -106.212891 | * | -108.906342 |
| * | 23.744659 | * | 0.574909 | * | 1.162587 | * | -98.385605 | * | -102.649292 |
| * | 23.934555 | * | 0.480631 | * | 1.033371 | * | -87.793304 | * | -93.434158 |
| * | 24.124451 | * | 0.341435 | * | 0.913162 | * | -61.075912 | * | -81.214630 |

CRUISE MISSILE TESTS
BASELINE MISSION SET
GLINT PLUS ECM AT 0.2 HZ
9-19-84

*** BLINKER FREQUENCY= 0.20

DATA SET NUMBER 1 OF 4

| | TIME......(SEC) | | NZC..........(G) | | NZ...........(G) | | BANKC.....(DEG) | | BANK......(DEG) |
|---|---|---|---|---|---|---|---|---|---|
| * | 24.314346 | * | 0.312690 | * | 0.819130 | * | -41.207794 | * | -68.769150 |
| * | 24.504242 | * | 0.289882 | * | 0.748993 | * | -12.722169 | * | -56.286392 |
| * | 24.694138 | * | 0.323168 | * | 0.693249 | * | 7.391577 | * | -43.769882 |
| * | 24.884033 | * | 0.411515 | * | 0.642170 | * | 14.987059 | * | -31.229416 |
| * | 25.073929 | * | 0.560545 | * | 0.600143 | * | 13.566038 | * | -18.679733 |
| * | 25.263824 | * | 0.793154 | * | 0.574242 | * | 11.106000 | * | -6.130711 |

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| * | 25.453720 | * | 0.933357 | * | 0.581695 | * | 7.270296 | * | 5.453405 |
| * | 25.643616 | * | 1.042595 | * | 0.699352 | * | 5.325726 | * | 5.787602 |
| * | 25.833511 | * | 1.131395 | * | 0.796295 | * | 3.147260 | * | 3.985226 |
| * | 26.023407 | * | 1.231064 | * | 0.873536 | * | 2.354088 | * | 2.606244 |
| * | 26.213303 | * | 1.275287 | * | 0.949175 | * | -1.190448 | * | 0.250407 |
| * | 26.403198 | * | 1.373239 | * | 1.020734 | * | -1.089107 | * | -1.234868 |
| * | 26.593094 | * | 1.414298 | * | 1.093149 | * | -3.873116 | * | -2.835641 |
| * | 26.782990 | * | 1.498616 | * | 1.170446 | * | -3.584943 | * | -3.880977 |
| * | 26.972885 | * | 1.534853 | * | 1.246133 | * | -5.545876 | * | -4.924376 |
| * | 27.162781 | * | 1.728691 | * | 1.302967 | * | 1.781992 | * | -1.654127 |
| * | 27.352676 | * | 2.026227 | * | 1.329571 | * | 10.870007 | * | 6.405899 |
| * | 27.542572 | * | 1.853992 | * | 1.533800 | * | 14.335903 | * | 8.333620 |
| * | 27.732468 | * | 2.109669 | * | 1.368543 | * | 48.268494 | * | 19.893433 |
| * | 27.922363 | * | 3.284542 | * | 1.460158 | * | 64.898895 | * | 31.915710 |
| * | 28.112259 | * | 4.000000 | * | 1.654933 | * | 76.102646 | * | 43.756592 |
| * | 28.302155 | * | 4.000000 | * | 2.019216 | * | 85.941116 | * | 55.290161 |
| * | 28.492050 | * | 4.000000 | * | 2.458335 | * | 92.840149 | * | 66.378754 |
| * | 28.681946 | * | 4.000000 | * | 2.864714 | * | 84.516556 | * | 77.037064 |
| * | 28.871841 | * | 4.000000 | * | 3.297837 | * | 87.914276 | * | 84.187943 |
| * | 29.061737 | * | 4.000000 | * | 3.747063 | * | 78.001495 | * | 81.152344 |

CRUISE MISSILE TESTS
BASELINE MISSION SET
GLINT PLUS ECM AT 0.2 HZ
9-19-84

*** BLINKER FREQUENCY= 0.20

DATA SET NUMBER 2 OF 4

| | TIME......(SEC) | | R/RT CMD..(DPS) | | ROLL RATE.(DPS) | | ECM SHIFT..(FT) | | GLINT SHIFT(FT) |
|---|---|---|---|---|---|---|---|---|---|
| * | 0.190000 | * | 12.067198 | * | 9.865781 | * | -75.000000 | * | 19.921875 |
| * | 0.380000 | * | 2.970557 | * | 0.744763 | * | -75.000000 | * | 47.070313 |
| * | 0.570000 | * | 1.389124 | * | -0.660753 | * | -75.000000 | * | -43.310547 |
| * | 0.759999 | * | 1.571068 | * | -0.488012 | * | -75.000000 | * | -25.952148 |
| * | 0.949999 | * | 1.868235 | * | -0.235456 | * | -75.000000 | * | -19.886780 |
| * | 1.139989 | * | 1.916773 | * | -0.222514 | * | -75.000000 | * | -47.924805 |
| * | 1.329975 | * | 2.881227 | * | 0.608558 | * | -75.000000 | * | 45.671082 |
| * | 1.519961 | * | 2.381867 | * | 0.131129 | * | -75.000000 | * | -43.750000 |
| * | 1.709948 | * | 3.031082 | * | 0.685417 | * | -75.000000 | * | 19.897461 |
| * | 1.899934 | * | 3.278272 | * | 0.890394 | * | -75.000000 | * | 32.394409 |
| * | 2.089920 | * | 2.867801 | * | 0.508729 | * | -75.000000 | * | -27.539063 |

| | | | | |
|---|---|---|---|---|
| 2.279906 | 2.820111 | 0.457421 | -75.000000 | -42.993164 |
| 2.469893 | 3.609996 | 1.165082 | -75.000000 | 37.622070 |
| 2.659879 | 4.559071 | 2.016505 | 75.000000 | -5.271912 |
| 2.849865 | 4.583967 | 2.048492 | 75.000000 | 2.807617 |
| 3.039851 | 4.257809 | 1.761084 | 75.000000 | -9.204102 |
| 3.229837 | 4.120385 | 1.648042 | 75.000000 | -0.720215 |
| 3.419824 | 3.626225 | 1.217953 | 75.000000 | -33.416748 |
| 3.609810 | 3.728097 | 1.322030 | 75.000000 | -5.682373 |
| 3.799796 | 3.323970 | 0.973187 | 75.000000 | -33.227539 |
| 3.989782 | 3.378778 | 1.033268 | 75.000000 | -14.042664 |
| 4.179769 | 3.092050 | 0.787648 | 75.000000 | -31.372070 |
| 4.369755 | 3.529077 | 1.189073 | 75.000000 | 22.955322 |
| 4.559741 | 3.603025 | 1.265257 | 75.000000 | 43.412781 |
| 4.749727 | 2.618767 | 0.387185 | 75.000000 | -34.065247 |
| 4.939713 | 2.893435 | 0.636503 | 75.000000 | 2.099609 |
| 5.129700 | 1.653059 | -0.484199 | -75.000000 | 31.295776 |
| 5.319686 | 1.026196 | -1.037718 | -75.000000 | -12.695313 |
| 5.509672 | 1.077647 | -0.988593 | -75.000000 | -28.857422 |
| 5.699658 | 1.415164 | -0.684597 | -75.000000 | -24.087524 |
| 5.889645 | 2.419119 | 0.215088 | -75.000000 | 42.173767 |
| 6.079631 | 1.948160 | -0.209821 | -75.000000 | -10.717773 |
| 6.269617 | 2.423877 | 0.211000 | -75.000000 | 21.826172 |
| 6.459603 | 2.002267 | -0.169043 | -75.000000 | -22.363281 |
| 6.649590 | 2.136669 | -0.053513 | -75.000000 | -19.886780 |
| 6.839576 | 1.931415 | -0.240801 | -75.000000 | -47.924805 |
| 7.029562 | 3.238107 | 0.927199 | -75.000000 | 45.671082 |
| 7.219548 | 74.999985 | 73.167145 | -75.000000 | -43.750000 |
| 7.409534 | 74.999985 | 65.331711 | -75.000000 | 19.897461 |
| 7.599521 | 74.999985 | 65.214294 | 75.000000 | 32.394409 |
| 7.789507 | 74.999985 | 65.097687 | 75.000000 | -27.539063 |
| 7.979493 | 18.041362 | 13.599403 | 75.000000 | -42.993164 |
| 8.169479 | 4.459596 | 1.007195 | 75.000000 | 37.622070 |
| 8.359466 | 3.449299 | -0.345169 | 75.000000 | -5.271912 |
| 8.549452 | 3.887762 | -0.645887 | 75.000000 | 2.807617 |
| 8.739438 | 4.701549 | -0.759738 | 75.000000 | -9.204102 |
| 8.929424 | 5.614478 | -0.785816 | 75.000000 | -0.720215 |
| 9.119411 | 6.464853 | -0.724356 | 75.000000 | -33.416748 |
| 9.309397 | 7.075636 | -0.545664 | 75.000000 | -5.682373 |
| 9.499383 | 7.377189 | -0.398665 | 75.000000 | -33.227539 |
| 9.689369 | 7.410828 | -0.180096 | 75.000000 | -14.042664 |
| 9.879355 | 7.082125 | 0.013767 | 75.000000 | -31.372070 |
| 10.069342 | 6.500261 | 0.155098 | -75.000000 | 22.955322 |
| 10.259328 | 5.771453 | 0.234564 | -75.000000 | 43.412781 |
| 10.449314 | 5.002514 | 0.256450 | -75.000000 | -34.065247 |
| 10.639300 | 4.281966 | 0.208768 | -75.000000 | 2.099609 |
| 10.829287 | -74.999985 | -69.740738 | -75.000000 | 31.295776 |
| 11.019273 | -74.999985 | -68.475403 | -75.000000 | -12.695313 |
| 11.209259 | -74.999985 | -68.066742 | -75.000000 | -28.857422 |

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| * | 11.399245 | * | -74.999985 | * | -67.783478 | * | -75.000000 | * | -24.087524 |
| * | 11.589231 | * | -10.854013 | * | -11.366899 | * | -75.000000 | * | 42.173767 |
| * | 11.779218 | * | 0.309608 | * | -1.175964 | * | -75.000000 | * | -10.717773 |

CRUISE MISSILE TESTS
BASELINE MISSION SET
GLINT PLUS ECM AT 0.2 HZ
9-19-84

*** BLINKER FREQUENCY= 0.20

DATA SET NUMBER 2 OF 4

| | TIME......(SEC) | | R/RT CMD..(DPS) | | ROLL RATE.(DPS) | | ECM SHIFT..(FT) | | GLINT SHIFT(FT) |
|---|---|---|---|---|---|---|---|---|---|
| * | 11.969204 | * | 1.725770 | * | -0.077368 | * | -75.000000 | * | 21.826172 |
| * | 12.159190 | * | 1.766047 | * | 0.153380 | * | -75.000000 | * | -22.363281 |
| * | 12.349176 | * | 1.522860 | * | 0.138551 | * | -75.000000 | * | -19.886780 |
| * | 12.539163 | * | 1.307849 | * | 0.090493 | * | 75.000000 | * | -47.924805 |
| * | 12.729149 | * | 1.175968 | * | 0.044148 | * | 75.000000 | * | 45.671082 |
| * | 12.919135 | * | 1.126412 | * | 0.008935 | * | 75.000000 | * | -43.750000 |
| * | 13.109121 | * | 1.140409 | * | -0.015377 | * | 75.000000 | * | 19.897461 |
| * | 13.299108 | * | 1.198962 | * | -0.031489 | * | 75.000000 | * | 32.394409 |
| * | 13.489094 | * | 1.287829 | * | -0.049077 | * | 75.000000 | * | -27.539063 |
| * | 13.679080 | * | 1.425424 | * | -0.068103 | * | 75.000000 | * | -42.993164 |
| * | 13.869066 | * | 1.591445 | * | -0.075865 | * | 75.000000 | * | 37.622070 |
| * | 14.059052 | * | 1.771146 | * | -0.078154 | * | 75.000000 | * | -5.271912 |
| * | 14.249039 | * | 1.954254 | * | -0.075742 | * | 75.000000 | * | 2.807617 |
| * | 14.439025 | * | 2.131940 | * | -0.069467 | * | 75.000000 | * | -9.204102 |
| * | 14.629011 | * | 2.296958 | * | -0.060213 | * | 75.000000 | * | -0.720215 |
| * | 14.818997 | * | 2.443621 | * | -0.048663 | * | 75.000000 | * | -33.416748 |
| * | 15.008984 | * | 2.566842 | * | -0.035191 | * | -75.000000 | * | -5.682373 |
| * | 15.198970 | * | 2.663178 | * | -0.021065 | * | -75.000000 | * | -33.227539 |
| * | 15.388956 | * | 2.731251 | * | -0.007072 | * | -75.000000 | * | -14.042664 |
| * | 15.578942 | * | 2.771195 | * | 0.006111 | * | -75.000000 | * | -31.372070 |
| * | 15.768929 | * | 2.784501 | * | 0.017965 | * | -75.000000 | * | 22.955322 |
| * | 15.958915 | * | 2.773720 | * | 0.028139 | * | -75.000000 | * | 43.412781 |
| * | 16.148834 | * | 2.742187 | * | 0.036394 | * | -75.000000 | * | -34.065247 |
| * | 16.338730 | * | 2.693789 | * | 0.042629 | * | -75.000000 | * | 2.099609 |
| * | 16.528625 | * | 2.632695 | * | 0.046833 | * | -75.000000 | * | 51.295776 |
| * | 16.718521 | * | 2.563117 | * | 0.049088 | * | -75.000000 | * | -12.695313 |
| * | 16.908417 | * | 2.489133 | * | 0.049557 | * | -75.000000 | * | -28.857422 |
| * | 17.098312 | * | 2.414161 | * | 0.048846 | * | -75.000000 | * | -24.087524 |

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| * | 17.288208 | * | 2.340792 | * | 0.046959 | * | -75.000000 | * | 42.173767 |
| * | 17.478104 | * | 2.271552 | * | 0.044037 | * | -75.000000 | * | -10.717773 |
| * | 17.667999 | * | 2.208578 | * | 0.040282 | * | 75.000000 | * | 21.626172 |
| * | 17.857895 | * | 2.153597 | * | 0.035907 | * | 75.000000 | * | -22.363281 |
| * | 18.047791 | * | 2.107845 | * | 0.031138 | * | 75.000000 | * | -19.886780 |
| * | 18.237686 | * | 2.072089 | * | 0.026206 | * | 75.000000 | * | -47.924805 |
| * | 18.427582 | * | 2.046605 | * | 0.021321 | * | 75.000000 | * | 45.671082 |
| * | 18.617477 | * | 2.031221 | * | 0.016687 | * | 75.000000 | * | -43.750000 |
| * | 18.807373 | * | 2.025372 | * | 0.012457 | * | 75.000000 | * | 19.897461 |
| * | 18.997269 | * | 2.028170 | * | 0.008771 | * | 75.000000 | * | 32.394409 |
| * | 19.187164 | * | 2.038470 | * | 0.005710 | * | 75.000000 | * | -27.539063 |
| * | 19.377060 | * | -74.999985 | * | -68.719757 | * | 75.000000 | * | -42.993164 |
| * | 19.566956 | * | -10.174731 | * | -11.349103 | * | 75.000000 | * | 37.622070 |
| * | 19.756851 | * | -3.140329 | * | -5.873646 | * | 75.000000 | * | -5.271912 |
| * | 19.946747 | * | -2.969819 | * | -7.032695 | * | 75.000000 | * | 2.807617 |
| * | 20.136642 | * | -6.683754 | * | -10.891152 | * | -75.000000 | * | -9.204102 |
| * | 20.326538 | * | -9.487894 | * | -11.762302 | * | -75.000000 | * | -0.720215 |
| * | 20.516434 | * | -13.608355 | * | -15.634974 | * | -75.000000 | * | -33.416748 |
| * | 20.706329 | * | -15.620285 | * | -17.100998 | * | -75.000000 | * | -5.682373 |
| * | 20.896225 | * | -17.409729 | * | -18.505905 | * | -75.000000 | * | -33.227539 |
| * | 21.086121 | * | -74.999985 | * | -73.526184 | * | -75.000000 | * | -14.042664 |
| * | 21.276016 | * | -74.999985 | * | -68.097229 | * | -75.000000 | * | -31.372070 |
| * | 21.465912 | * | -74.999985 | * | -64.827148 | * | -75.000000 | * | 22.955322 |
| * | 21.655807 | * | -74.999985 | * | -65.806488 | * | -75.000000 | * | 43.412781 |
| * | 21.845703 | * | -74.999985 | * | -66.102875 | * | -75.000000 | * | -34.065247 |
| * | 22.035599 | * | -54.749130 | * | -55.254349 | * | -75.000000 | * | 2.099609 |
| * | 22.225494 | * | -13.985446 | * | -14.129050 | * | -75.000000 | * | 31.295776 |
| * | 22.415390 | * | -5.177193 | * | -7.009793 | * | -75.000000 | * | -12.695313 |
| * | 22.605286 | * | -6.651922 | * | -8.923970 | * | 75.000000 | * | -28.857422 |
| * | 22.795181 | * | -2.722851 | * | -5.446668 | * | 75.000000 | * | -24.087524 |
| * | 22.985077 | * | 5.737814 | * | 2.087615 | * | 75.000000 | * | 42.173767 |
| * | 23.174973 | * | 10.913829 | * | 6.743303 | * | 75.000000 | * | -10.717773 |
| * | 23.364868 | * | 22.559418 | * | 17.168839 | * | 75.000000 | * | 21.826172 |
| * | 23.554764 | * | 31.783112 | * | 25.545227 | * | 75.000000 | * | -22.363281 |
| * | 23.744659 | * | 50.506699 | * | 42.293365 | * | 75.000000 | * | -19.886780 |
| * | 23.934555 | * | 66.983032 | * | 57.138718 | * | 75.000000 | * | -47.924805 |
| * | 24.124451 | * | 74.999985 | * | 65.371765 | * | 75.000000 | * | 45.671082 |

CRUISE MISSILE TESTS
BASELINE MISSION SET
GLINT PLUS ECM AT 0.2 HZ
9-19-84

*** BLINKER FREQUENCY= 0.20

DATA SET NUMBER 2 OF 4

| TIME......(SEC) | R/RT CMD..(DPS) | ROLL RATE.(DPS) | ECM SHIFT..(FT) | GLINT SHIFT(FT) |
|---|---|---|---|---|
| * 24.314346 | * 74.999985 | * 65.562851 | * 75.000000 | * -43.750000 |
| * 24.504242 | * 74.999985 | * 65.786819 | * 75.000000 | * 19.897461 |
| * 24.694138 | * 74.999985 | * 65.964462 | * 75.000000 | * 32.394409 |
| * 24.884033 | * 74.999985 | * 66.059204 | * 75.000000 | * -27.539063 |
| * 25.073929 | * 74.999985 | * 66.085938 | * -75.000000 | * -42.993164 |
| * 25.263824 | * 74.999985 | * 66.059158 | * -75.000000 | * 37.622070 |
| * 25.453720 | * 22.935425 | * 22.956116 | * -75.000000 | * -5.271912 |
| * 25.643616 | * -5.669250 | * -6.440586 | * -75.000000 | * 2.807617 |
| * 25.833511 | * -10.200819 | * -10.561381 | * -75.000000 | * -9.204102 |
| * 26.023407 | * -3.224416 | * -4.461498 | * -75.000000 | * -0.720215 |
| * 26.213303 | * -17.424454 | * -17.331482 | * -75.000000 | * -33.416748 |
| * 26.403198 | * 1.460428 | * -0.733393 | * -75.000000 | * -5.682373 |
| * 26.593094 | * -12.643291 | * -13.444024 | * -75.000000 | * -33.227539 |
| * 26.782990 | * 3.221104 | * 0.505559 | * -75.000000 | * -14.042664 |
| * 26.972885 | * -7.714266 | * -9.377487 | * -75.000000 | * -31.372070 |
| * 27.162781 | * 40.710358 | * 33.784058 | * -75.000000 | * 22.955322 |
| * 27.352676 | * 53.080215 | * 44.799210 | * -75.000000 | * 43.412781 |
| * 27.542572 | * 66.124893 | * 25.035751 | * 75.000000 | * -34.065247 |
| * 27.732468 | * 74.999985 | * 63.833176 | * 75.000000 | * 2.099609 |
| * 27.922363 | * 74.999985 | * 62.675156 | * 75.000000 | * 31.295776 |
| * 28.112259 | * 74.999985 | * 61.318130 | * 75.000000 | * -12.695313 |
| * 28.302155 | * 74.999985 | * 58.976959 | * 75.000000 | * -28.857422 |
| * 28.492050 | * 74.999985 | * 56.138641 | * 75.000000 | * -24.087524 |
| * 28.681946 | * 74.999985 | * 54.246460 | * 0.000000 | * 42.173767 |
| * 28.871841 | * 43.046890 | * 24.959106 | * 0.000000 | * -10.717773 |
| * 29.061737 | * -38.403168 | * -41.171707 | * 0.000000 | * 21.826172 |

CRUISE MISSILE TESTS
BASELINE MISSION SET
GLINT PLUS ECM AT 0.2 HZ
9-19-84

*** BLINKER FREQUENCY= 0.20

DATA SET NUMBER 3 OF 4

TIME......(SEC) STBLTR....(DEG) AILRCN....(DEG) RUDDER....(DEG) ALTITUDE...(FT)

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| * | 0.190000 | * | -1.179925 | * | -1.272073 | * | -0.320945 | * | 50.047150 |
| * | 0.380000 | * | -1.038112 | * | -1.095920 | * | -0.182107 | * | 50.089844 |
| * | 0.570000 | * | -1.017799 | * | -1.048470 | * | -0.056974 | * | 50.075516 |
| * | 0.759999 | * | -1.034143 | * | -1.054128 | * | -0.009282 | * | 49.959283 |
| * | 0.949999 | * | -1.055637 | * | -1.077138 | * | -0.005256 | * | 49.873306 |
| * | 1.139989 | * | -1.071321 | * | -1.104088 | * | -0.014276 | * | 49.714828 |
| * | 1.329975 | * | -1.142786 | * | -1.129882 | * | -0.022971 | * | 49.541748 |
| * | 1.519961 | * | -1.122277 | * | -1.152071 | * | -0.024183 | * | 49.370300 |
| * | 1.709948 | * | -1.177706 | * | -1.170511 | * | -0.022619 | * | 49.214798 |
| * | 1.899934 | * | -1.195317 | * | -1.184159 | * | -0.018078 | * | 49.086792 |
| * | 2.089920 | * | -1.177351 | * | -1.193243 | * | -0.011021 | * | 48.994980 |
| * | 2.279906 | * | -1.182572 | * | -1.198361 | * | -0.006142 | * | 48.945496 |
| * | 2.469893 | * | -1.228275 | * | -1.199309 | * | -0.003228 | * | 48.941635 |
| * | 2.659879 | * | -1.275705 | * | -1.195999 | * | 0.003239 | * | 48.983841 |
| * | 2.849865 | * | -1.264773 | * | -1.189154 | * | 0.016585 | * | 49.069839 |
| * | 3.039851 | * | -1.243804 | * | -1.180487 | * | 0.032663 | * | 49.195465 |
| * | 3.229837 | * | -1.233457 | * | -1.171021 | * | 0.044216 | * | 49.355621 |
| * | 3.419824 | * | -1.199722 | * | -1.160979 | * | 0.050357 | * | 49.544617 |
| * | 3.609810 | * | -1.202726 | * | -1.150723 | * | 0.051594 | * | 49.756378 |
| * | 3.799796 | * | -1.171800 | * | -1.140256 | * | 0.051657 | * | 49.984329 |
| * | 3.989782 | * | -1.172373 | * | -1.130201 | * | 0.051135 | * | 50.221985 |
| * | 4.179769 | * | -1.149561 | * | -1.120715 | * | 0.051165 | * | 50.462906 |
| * | 4.369755 | * | -1.171543 | * | -1.112206 | * | 0.051478 | * | 50.701035 |
| * | 4.559741 | * | -1.166974 | * | -1.104602 | * | 0.054328 | * | 50.930740 |
| * | 4.749727 | * | -1.108326 | * | -1.098680 | * | 0.058848 | * | 51.147034 |
| * | 4.939713 | * | -1.130142 | * | -1.095016 | * | 0.058735 | * | 51.346466 |
| * | 5.129700 | * | -1.045614 | * | -1.092589 | * | 0.050655 | * | 51.526535 |
| * | 5.319686 | * | -1.032086 | * | -1.092353 | * | 0.051271 | * | 51.686035 |
| * | 5.509672 | * | -1.037953 | * | -1.093357 | * | 0.038513 | * | 51.825134 |
| * | 5.699658 | * | -1.055715 | * | -1.094423 | * | 0.026263 | * | 51.944427 |
| * | 5.889645 | * | -1.110085 | * | -1.095340 | * | 0.020173 | * | 52.044235 |
| * | 6.079631 | * | -1.076871 | * | -1.096312 | * | 0.023103 | * | 52.124771 |
| * | 6.269617 | * | -1.110800 | * | -1.098415 | * | 0.027839 | * | 52.186601 |
| * | 6.459603 | * | -1.084154 | * | -1.101169 | * | 0.032079 | * | 52.231140 |
| * | 6.649590 | * | -1.097795 | * | -1.104772 | * | 0.033428 | * | 52.260086 |
| * | 6.839576 | * | -1.086693 | * | -1.108665 | * | 0.032640 | * | 52.275726 |
| * | 7.029562 | * | -1.164207 | * | -1.112531 | * | 0.031169 | * | 52.280350 |
| * | 7.219548 | * | -11.369934 | * | -1.448772 | * | -0.003855 | * | 52.270688 |
| * | 7.409534 | * | -4.771715 | * | -1.065162 | * | 0.260663 | * | 52.196152 |
| * | 7.599521 | * | -4.885085 | * | -0.908555 | * | 0.724280 | * | 51.901566 |
| * | 7.789507 | * | -4.941984 | * | -0.930544 | * | 1.104971 | * | 51.305740 |
| * | 7.979493 | * | -1.221276 | * | -1.154338 | * | 1.380678 | * | 50.330307 |
| * | 8.169479 | * | -1.607866 | * | -1.647376 | * | 1.497520 | * | 48.969589 |
| * | 8.359466 | * | -1.866967 | * | -2.157928 | * | 1.178964 | * | 47.333832 |
| * | 8.549452 | * | -2.228454 | * | -2.533860 | * | 0.752841 | * | 45.598022 |
| * | 8.739438 | * | -2.690789 | * | -2.830583 | * | 0.417827 | * | 43.956161 |
| * | 8.929424 | * | -3.164660 | * | -3.067161 | * | 0.230265 | * | 42.599152 |

```
*    9.119411   *   -3.569754   *   -3.222716   *    0.192114   *   41.688568
*    9.309397   *   -3.802303   *   -3.288725   *    0.248152   *   41.337570
*    9.499383   *   -3.889286   *   -3.262568   *    0.364863   *   41.600983
*    9.689369   *   -3.815103   *   -3.148677   *    0.489636   *   42.473740
*    9.879355   *   -3.563250   *   -2.976035   *    0.613086   *   43.898743
*   10.069342   *   -3.206109   *   -2.761302   *    0.718114   *   45.777054
*   10.259328   *   -2.801994   *   -2.526126   *    0.790657   *   47.981018
*   10.449314   *   -2.403330   *   -2.292121   *    0.826747   *   50.369049
*   10.639300   *   -2.053359   *   -2.077678   *    0.831036   *   52.799927
*   10.829287   *    2.769983   *   -2.031552   *    0.837751   *   55.198746
*   11.019273   *    3.203503   *   -1.638245   *    0.107612   *   57.602005
*   11.209259   *    3.445362   *   -1.337570   *   -0.511320   *   60.093918
*   11.399245   *    3.590609   *   -1.067041   *   -0.863214   *   62.670746
*   11.589231   *   -0.761881   *   -0.860477   *   -1.133111   *   65.250519
*   11.779218   *   -0.806800   *   -0.768132   *   -1.088782   *   67.735687
```

CRUISE MISSILE TESTS
BASELINE MISSION SET
GLINT PLUS ECM AT 0.2 HZ
9-19-84

```
*** BLINKER FREQUENCY=      0.20
                                              DATA SET NUMBER  3  OF  4

TIME......(SEC) STBLTR....(DEG) AILRON....(DEG) RUDDER....(DEG) ALTITUDE...(FT)

*   11.969204   *   -0.915540   *   -0.655329   *   -0.792145   *   70.043457
*   12.159190   *   -0.818488   *   -0.529124   *   -0.461040   *   72.077484
*   12.349176   *   -0.699540   *   -0.417514   *   -0.218913   *   73.742950
*   12.539163   *   -0.612691   *   -0.339986   *   -0.095439   *   74.960114
*   12.729149   *   -0.566952   *   -0.309909   *   -0.054526   *   75.678207
*   12.919135   *   -0.557567   *   -0.324278   *   -0.055930   *   75.877914
*   13.109121   *   -0.575181   *   -0.376057   *   -0.073167   *   75.567383
*   13.299108   *   -0.611483   *   -0.457703   *   -0.093069   *   74.777695
*   13.489094   *   -0.661711   *   -0.561647   *   -0.110690   *   73.558517
*   13.679080   *   -0.739960   *   -0.676090   *   -0.125492   *   71.971649
*   13.869066   *   -0.826459   *   -0.799570   *   -0.138116   *   70.086105
*   14.059052   *   -0.917423   *   -0.928560   *   -0.148669   *   67.978912
*   14.249039   *   -1.008072   *   -1.056622   *   -0.156873   *   65.730789
*   14.439025   *   -1.094344   *   -1.177841   *   -0.162444   *   63.421967
*   14.629011   *   -1.172998   *   -1.287473   *   -0.165273   *   61.128418
*   14.818997   *   -1.241513   *   -1.381730   *   -0.165445   *   58.919159
```

| | | | | |
|---|---|---|---|---|
| 15.008984 | -1.297470 | -1.456547 | -0.163082 | 56.856552 |
| 15.198970 | -1.339688 | -1.511010 | -0.158429 | 54.993240 |
| 15.388956 | -1.367822 | -1.545155 | -0.151980 | 53.368027 |
| 15.578942 | -1.382230 | -1.559812 | -0.144324 | 52.005524 |
| 15.768929 | -1.383876 | -1.556629 | -0.136056 | 50.916870 |
| 15.958915 | -1.374182 | -1.537891 | -0.127722 | 50.100784 |
| 16.148834 | -1.354918 | -1.506315 | -0.119780 | 49.544998 |
| 16.338730 | -1.328072 | -1.464860 | -0.112589 | 49.228348 |
| 16.528625 | -1.295725 | -1.416553 | -0.106404 | 49.122620 |
| 16.718521 | -1.259953 | -1.364342 | -0.101381 | 49.194794 |
| 16.908417 | -1.222731 | -1.310954 | -0.097588 | 49.409073 |
| 17.098312 | -1.185530 | -1.257968 | -0.094979 | 49.729767 |
| 17.288208 | -1.149609 | -1.207210 | -0.093391 | 50.123581 |
| 17.478104 | -1.116189 | -1.160531 | -0.092715 | 50.559036 |
| 17.667999 | -1.086252 | -1.119246 | -0.092859 | 51.007065 |
| 17.857895 | -1.060576 | -1.084332 | -0.093730 | 51.441833 |
| 18.047791 | -1.039686 | -1.056404 | -0.095221 | 51.841492 |
| 18.237686 | -1.023868 | -1.035758 | -0.097213 | 52.188431 |
| 18.427582 | -1.013171 | -1.022363 | -0.099579 | 52.469574 |
| 18.617477 | -1.007424 | -1.015905 | -0.102191 | 52.676392 |
| 18.807373 | -1.006281 | -1.015826 | -0.104924 | 52.804611 |
| 18.997269 | -1.009237 | -1.021379 | -0.107659 | 52.853958 |
| 19.187164 | -1.015683 | -1.031667 | -0.110293 | 52.827713 |
| 19.377060 | 3.324049 | -1.988774 | -0.060459 | 52.717728 |
| 19.566956 | -1.054458 | -2.290795 | -0.521140 | 52.555893 |
| 19.756851 | -1.316113 | -2.873454 | -1.046701 | 52.734253 |
| 19.946747 | -1.960548 | -3.514855 | -1.334141 | 53.880951 |
| 20.136642 | -2.005396 | -4.166123 | -1.468184 | 56.644333 |
| 20.326538 | -1.250170 | -4.715120 | -1.425174 | 61.550415 |
| 20.516434 | -0.977447 | -5.256442 | -1.052974 | 68.895752 |
| 20.706329 | -0.714183 | -5.551373 | -1.111055 | 78.748398 |
| 20.896225 | -0.536378 | -5.656308 | -1.373256 | 91.015167 |
| 21.086121 | 7.934396 | -6.261881 | -1.550011 | 105.502518 |
| 21.276016 | 3.334913 | -4.589189 | -2.184981 | 121.881042 |
| 21.465912 | 5.091518 | -3.823456 | -2.715747 | 139.391983 |
| 21.655807 | 4.683903 | -3.211911 | -3.098340 | 157.130630 |
| 21.845703 | 4.476401 | -2.668601 | -3.310959 | 174.301590 |
| 22.035599 | -0.707323 | -2.269772 | -3.287128 | 190.300354 |
| 22.225494 | -0.402787 | -2.197576 | -3.446685 | 204.730820 |
| 22.415390 | -1.018952 | -2.253961 | -2.931566 | 217.343460 |
| 22.605286 | -0.957839 | -2.276559 | -2.294298 | 227.984009 |
| 22.795181 | -1.466182 | -2.234136 | -1.783365 | 236.559372 |
| 22.985077 | -1.966421 | -2.157530 | -1.464703 | 243.024078 |
| 23.174973 | -2.224481 | -2.042295 | -1.215720 | 247.387039 |
| 23.364868 | -2.933079 | -1.874610 | -0.999400 | 249.710815 |
| 23.554764 | -3.376541 | -1.656700 | -0.763346 | 250.106537 |
| 23.744659 | -4.530933 | -1.430122 | -0.548162 | 248.725403 |
| 23.934555 | -5.335417 | -1.202142 | -0.331894 | 245.756470 |

| | | | | |
|---|---|---|---|---|
| 24.124451 | -4.849390 | -0.962144 | -0.114661 | 241.418747 |

CRUISE MISSILE TESTS
BASELINE MISSION SET
GLINT PLUS ECM AT 0.2 HZ
9-19-84

*** BLINKER FREQUENCY= 0.20

DATA SET NUMBER 3 OF 4

| TIME......(SEC) | STBLTR....(DEG) | AILRON....(DEG) | RUDDER....(DEG) | ALTITUDE...(FT) |
|---|---|---|---|---|
| 24.314346 | -4.733329 | -0.741563 | 0.101332 | 235.931198 |
| 24.504242 | -4.620466 | -0.578142 | 0.231385 | 229.489410 |
| 24.694138 | -4.527917 | -0.465651 | 0.289164 | 222.255127 |
| 24.884033 | -4.474320 | -0.393226 | 0.322519 | 214.351547 |
| 25.073929 | -4.457426 | -0.346899 | 0.364436 | 205.859680 |
| 25.263824 | -4.467105 | -0.351945 | 0.428672 | 196.827133 |
| 25.453720 | 4.274610 | -0.385897 | 0.500631 | 187.284653 |
| 25.643616 | -0.232819 | -0.548033 | 0.558074 | 177.287750 |
| 25.833511 | -0.198692 | -0.756084 | 0.343086 | 166.953583 |
| 26.023407 | -0.690840 | -0.927217 | 0.039595 | 156.390366 |
| 26.213303 | 0.102798 | -1.071691 | -0.150439 | 145.687653 |
| 26.403198 | -1.248897 | -1.217293 | -0.305899 | 134.929001 |
| 26.593094 | -0.333312 | -1.352807 | -0.341328 | 124.194458 |
| 26.782990 | -1.492764 | -1.492980 | -0.385366 | 113.564758 |
| 26.972885 | -0.769291 | -1.620697 | -0.369920 | 103.123795 |
| 27.162781 | -3.682539 | -1.775579 | -0.400695 | 92.954956 |
| 27.352676 | -4.034352 | -1.926140 | -0.148369 | 83.127731 |
| 27.542572 | -15.000000 | 0.000000 | 0.402904 | 73.705917 |
| 27.732468 | -5.632820 | -2.184797 | 0.416052 | 64.775589 |
| 27.922363 | -6.096888 | -2.257270 | 0.805972 | 56.263779 |
| 28.112259 | -6.717966 | -2.657307 | 1.135191 | 48.184021 |
| 28.302155 | -7.838568 | -2.994135 | 1.294632 | 40.573837 |
| 28.492050 | -9.240601 | -3.403696 | 1.414780 | 33.465179 |
| 28.681946 | -10.259377 | -3.842335 | 1.650109 | 26.756851 |
| 28.871841 | -8.908066 | -4.308064 | 2.381865 | 20.155396 |
| 29.061737 | -1.385618 | -5.175614 | 3.952714 | 13.361130 |

GLINT PLUS ECM AT 0.2 HZ
9-19-84

*** BLINKER FREQUENCY= 0.20

DATA SET NUMBER 4 OF 4

| | TIME......(SEC) | | XM...(FT NORTH) | | YM....(FT EAST) | | XT...(FT NORTH) | | XM....(FT EAST) |
|---|---|---|---|---|---|---|---|---|---|
| * | 0.190000 | * | 159.440155 | * | -0.009810 | * | 24000.000000 | * | 6.649995 |
| * | 0.380000 | * | 318.873291 | * | -0.049694 | * | 24000.000000 | * | 13.299989 |
| * | 0.570000 | * | 478.301758 | * | -0.113570 | * | 24000.000000 | * | 19.949982 |
| * | 0.759999 | * | 637.728271 | * | -0.201762 | * | 24000.000000 | * | 26.599976 |
| * | 0.949999 | * | 797.151611 | * | -0.313580 | * | 24000.000000 | * | 33.249969 |
| * | 1.139989 | * | 956.573486 | * | -0.448021 | * | 24000.000000 | * | 39.899597 |
| * | 1.329975 | * | 1115.991460 | * | -0.603947 | * | 24000.000000 | * | 46.549118 |
| * | 1.519961 | * | 1275.407710 | * | -0.779674 | * | 24000.000000 | * | 53.198639 |
| * | 1.709948 | * | 1434.820310 | * | -0.973391 | * | 24000.000000 | * | 59.848160 |
| * | 1.899934 | * | 1594.228760 | * | -1.182685 | * | 24000.000000 | * | 66.497681 |
| * | 2.089920 | * | 1753.632810 | * | -1.404678 | * | 24000.000000 | * | 73.147202 |
| * | 2.279906 | * | 1913.032470 | * | -1.636795 | * | 24000.000000 | * | 79.796707 |
| * | 2.469893 | * | 2072.426510 | * | -1.876554 | * | 24000.000000 | * | 86.446228 |
| * | 2.659879 | * | 2231.814940 | * | -2.120413 | * | 24000.000000 | * | 93.095749 |
| * | 2.849865 | * | 2391.197750 | * | -2.362842 | * | 24000.000000 | * | 99.745270 |
| * | 3.039851 | * | 2550.574710 | * | -2.597082 | * | 24000.000000 | * | 106.394791 |
| * | 3.229837 | * | 2709.944090 | * | -2.816305 | * | 24000.000000 | * | 113.044296 |
| * | 3.419824 | * | 2869.307860 | * | -3.014300 | * | 24000.000000 | * | 119.693817 |
| * | 3.609810 | * | 3028.665530 | * | -3.185804 | * | 24000.000000 | * | 126.343338 |
| * | 3.799796 | * | 3188.016360 | * | -3.326302 | * | 24000.000000 | * | 132.992859 |
| * | 3.989782 | * | 3347.361330 | * | -3.432030 | * | 24000.000000 | * | 139.642380 |
| * | 4.179769 | * | 3506.700200 | * | -3.499740 | * | 24000.000000 | * | 146.291885 |
| * | 4.369755 | * | 3666.032710 | * | -3.526452 | * | 24000.000000 | * | 152.941406 |
| * | 4.559741 | * | 3825.359620 | * | -3.508787 | * | 24000.000000 | * | 159.590927 |
| * | 4.749727 | * | 3984.681400 | * | -3.443329 | * | 24000.000000 | * | 166.240448 |
| * | 4.939713 | * | 4143.984370 | * | -3.327466 | * | 24000.000000 | * | 172.889969 |
| * | 5.129700 | * | 4303.257810 | * | -3.159139 | * | 24000.000000 | * | 179.539490 |
| * | 5.319686 | * | 4462.531250 | * | -2.938205 | * | 24000.000000 | * | 186.188995 |
| * | 5.509672 | * | 4621.804690 | * | -2.666635 | * | 24000.000000 | * | 192.838516 |
| * | 5.699658 | * | 4781.078120 | * | -2.347534 | * | 24000.000000 | * | 199.488037 |
| * | 5.889645 | * | 4940.351560 | * | -1.983534 | * | 24000.000000 | * | 206.137558 |
| * | 6.079631 | * | 5099.625000 | * | -1.575940 | * | 24000.000000 | * | 212.787079 |
| * | 6.269617 | * | 5258.898440 | * | -1.125271 | * | 24000.000000 | * | 219.436584 |
| * | 6.459603 | * | 5418.171870 | * | -0.631455 | * | 24000.000000 | * | 226.086105 |
| * | 6.649590 | * | 5577.445310 | * | -0.094406 | * | 24000.000000 | * | 232.735626 |

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| * | 6.839576 | * | 5736.703120 | * | 0.485856 | * | 24000.000000 | * | 239.385147 |
| * | 7.029562 | * | 5895.902340 | * | 1.109634 | * | 24000.000000 | * | 246.034668 |
| * | 7.219548 | * | 6055.101560 | * | 1.785213 | * | 24000.000000 | * | 252.684174 |
| * | 7.409534 | * | 6214.300780 | * | 2.594645 | * | 24000.000000 | * | 259.333496 |
| * | 7.599521 | * | 6373.500000 | * | 3.660096 | * | 24000.000000 | * | 265.983154 |
| * | 7.789507 | * | 6532.699220 | * | 5.144712 | * | 24000.000000 | * | 272.632568 |
| * | 7.979493 | * | 6691.898440 | * | 7.223592 | * | 24000.000000 | * | 279.282227 |
| * | 8.169479 | * | 6851.023440 | * | 10.115357 | * | 24000.000000 | * | 285.931641 |
| * | 8.359466 | * | 7010.148440 | * | 14.135207 | * | 24000.000000 | * | 292.581055 |
| * | 8.549452 | * | 7169.210940 | * | 19.605545 | * | 24000.000000 | * | 299.230713 |
| * | 8.739438 | * | 7328.160160 | * | 26.823135 | * | 24000.000000 | * | 305.880127 |
| * | 8.929424 | * | 7486.953120 | * | 36.051483 | * | 24000.000000 | * | 312.529785 |
| * | 9.119411 | * | 7645.527340 | * | 47.497543 | * | 24000.000000 | * | 319.179199 |
| * | 9.309397 | * | 7803.820310 | * | 61.294495 | * | 24000.000000 | * | 325.828857 |
| * | 9.499383 | * | 7961.785160 | * | 77.494766 | * | 24000.000000 | * | 332.478271 |
| * | 9.689369 | * | 8119.371090 | * | 96.073334 | * | 24000.000000 | * | 339.127686 |
| * | 9.879355 | * | 8276.554690 | * | 116.938950 | * | 24000.000000 | * | 345.777344 |
| * | 10.069342 | * | 8433.335940 | * | 139.948761 | * | 24000.000000 | * | 352.426758 |
| * | 10.259328 | * | 8589.730470 | * | 164.924744 | * | 24000.000000 | * | 359.076416 |
| * | 10.449314 | * | 8745.746090 | * | 191.672058 | * | 24000.000000 | * | 365.725830 |
| * | 10.639300 | * | 8901.429690 | * | 219.996429 | * | 24000.000000 | * | 372.375488 |
| * | 10.829287 | * | 9056.800780 | * | 249.667542 | * | 24000.000000 | * | 379.024902 |
| * | 11.019273 | * | 9211.929690 | * | 280.360840 | * | 24000.000000 | * | 385.674316 |
| * | 11.209259 | * | 9366.890620 | * | 311.764160 | * | 24000.000000 | * | 392.323975 |
| * | 11.399245 | * | 9521.742190 | * | 343.555176 | * | 24000.000000 | * | 398.973389 |
| * | 11.589231 | * | 9676.562500 | * | 375.463623 | * | 24000.000000 | * | 405.623047 |
| * | 11.779218 | * | 9831.382810 | * | 407.341797 | * | 24000.000000 | * | 412.272461 |

CRUISE MISSILE TESTS
BASELINE MISSION SET
GLINT PLUS ECM AT 0.2 HZ
9-19-84

*** BLINKER FRECUENCY= 0.20

CATA SET NUMBER 4 OF 4

| | TIME......(SEC) | | XM...(FT NORTH) | | YM....(FT EAST) | | XT...(FT NORTH) | | XM....(FT EAST) |
|---|---|---|---|---|---|---|---|---|---|
| * | 11.969204 | * | 9986.203120 | * | 439.127930 | * | 24000.000000 | * | 418.922119 |
| * | 12.159190 | * | 10141.023400 | * | 470.795654 | * | 24000.000000 | * | 425.571533 |
| * | 12.349176 | * | 10295.843700 | * | 502.336670 | * | 24000.000000 | * | 432.220947 |
| * | 12.539163 | * | 10450.683600 | * | 533.751709 | * | 24000.000000 | * | 438.870605 |

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| * | 12.729149 | * | 10605.578100 | * | 565.044678 | * | 24000.000000 | * | 445.520020 |
| * | 12.919135 | * | 10760.472700 | * | 596.219727 | * | 24000.000000 | * | 452.169678 |
| * | 13.109121 | * | 10915.398400 | * | 627.277344 | * | 24000.000000 | * | 458.819092 |
| * | 13.299108 | * | 11070.367200 | * | 658.218750 | * | 24000.000000 | * | 465.468750 |
| * | 13.489094 | * | 11225.335900 | * | 689.041992 | * | 24000.000000 | * | 472.118164 |
| * | 13.679080 | * | 11380.375000 | * | 719.744141 | * | 24000.000000 | * | 478.767578 |
| * | 13.869066 | * | 11535.418000 | * | 750.322754 | * | 24000.000000 | * | 485.417236 |
| * | 14.059052 | * | 11690.523400 | * | 780.773926 | * | 24000.000000 | * | 492.066650 |
| * | 14.249039 | * | 11845.640600 | * | 811.093506 | * | 24000.000000 | * | 498.716309 |
| * | 14.439025 | * | 12000.828100 | * | 841.276611 | * | 24000.000000 | * | 505.365723 |
| * | 14.629011 | * | 12156.027300 | * | 871.318848 | * | 24000.000000 | * | 512.015381 |
| * | 14.818997 | * | 12311.293000 | * | 901.215088 | * | 24000.000000 | * | 518.664795 |
| * | 15.008984 | * | 12466.574200 | * | 930.961670 | * | 24000.000000 | * | 525.314209 |
| * | 15.198970 | * | 12621.914100 | * | 960.554443 | * | 24000.000000 | * | 531.963867 |
| * | 15.388956 | * | 12777.261700 | * | 989.990479 | * | 24000.000000 | * | 538.613281 |
| * | 15.578942 | * | 12932.675800 | * | 1019.267580 | * | 24000.000000 | * | 545.262939 |
| * | 15.768929 | * | 13088.089800 | * | 1048.383790 | * | 24000.000000 | * | 551.912354 |
| * | 15.958915 | * | 13243.550800 | * | 1077.338620 | * | 24000.000000 | * | 558.562012 |
| * | 16.148834 | * | 13399.039100 | * | 1106.131350 | * | 24000.000000 | * | 565.208984 |
| * | 16.338730 | * | 13554.527300 | * | 1134.763180 | * | 24000.000000 | * | 571.855469 |
| * | 16.528625 | * | 13710.054700 | * | 1163.234620 | * | 24000.000000 | * | 578.501709 |
| * | 16.718521 | * | 13865.617200 | * | 1191.547360 | * | 24000.000000 | * | 585.148193 |
| * | 16.908417 | * | 14021.179700 | * | 1219.703370 | * | 24000.000000 | * | 591.794434 |
| * | 17.098312 | * | 14176.742200 | * | 1247.704100 | * | 24000.000000 | * | 598.440918 |
| * | 17.288208 | * | 14332.351600 | * | 1275.552250 | * | 24000.000000 | * | 605.087158 |
| * | 17.478104 | * | 14487.988300 | * | 1303.249510 | * | 24000.000000 | * | 611.733398 |
| * | 17.667999 | * | 14643.625000 | * | 1330.797610 | * | 24000.000000 | * | 618.379883 |
| * | 17.857895 | * | 14799.261700 | * | 1358.198240 | * | 24000.000000 | * | 625.026123 |
| * | 18.047791 | * | 14954.949200 | * | 1385.453370 | * | 24000.000000 | * | 631.672607 |
| * | 18.237686 | * | 15110.660200 | * | 1412.564210 | * | 24000.000000 | * | 638.318848 |
| * | 18.427582 | * | 15266.371100 | * | 1439.531740 | * | 24000.000000 | * | 644.965332 |
| * | 18.617477 | * | 15422.082000 | * | 1466.356450 | * | 24000.000000 | * | 651.611572 |
| * | 18.807373 | * | 15577.867200 | * | 1493.039310 | * | 24000.000000 | * | 658.258057 |
| * | 18.997269 | * | 15733.652300 | * | 1519.580080 | * | 24000.000000 | * | 664.904297 |
| * | 19.187164 | * | 15889.437500 | * | 1545.979250 | * | 24000.000000 | * | 671.550537 |
| * | 19.377060 | * | 16045.246100 | * | 1572.180910 | * | 24000.000000 | * | 678.197021 |
| * | 19.566956 | * | 16201.109400 | * | 1598.057130 | * | 24000.000000 | * | 684.843262 |
| * | 19.756851 | * | 16357.054700 | * | 1623.358890 | * | 24000.000000 | * | 691.489746 |
| * | 19.946747 | * | 16513.078100 | * | 1647.744380 | * | 24000.000000 | * | 698.135986 |
| * | 20.136642 | * | 16669.160200 | * | 1670.831050 | * | 24000.000000 | * | 704.782471 |
| * | 20.326538 | * | 16825.242200 | * | 1692.221190 | * | 24000.000000 | * | 711.428711 |
| * | 20.516434 | * | 16981.269500 | * | 1711.564210 | * | 24000.000000 | * | 718.074951 |
| * | 20.706329 | * | 17137.136700 | * | 1728.602290 | * | 24000.000000 | * | 724.721436 |
| * | 20.896225 | * | 17292.789100 | * | 1743.127440 | * | 24000.000000 | * | 731.367676 |
| * | 21.086121 | * | 17448.156200 | * | 1754.952150 | * | 24000.000000 | * | 738.014160 |
| * | 21.276016 | * | 17603.203100 | * | 1763.747310 | * | 24000.000000 | * | 744.660400 |
| * | 21.465912 | * | 17757.972700 | * | 1769.209720 | * | 24000.000000 | * | 751.306885 |
| * | 21.655807 | * | 17912.515600 | * | 1771.405030 | * | 24000.000000 | * | 757.953125 |

| | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| * | 21.845703 | * | 18066.910200 | * | 1770.707280 | * | 24000.000000 | * 764.599609 |
| * | 22.035599 | * | 18221.203100 | * | 1767.581790 | * | 24000.000000 | * 771.245850 |
| * | 22.225494 | * | 18375.429700 | * | 1762.431400 | * | 24000.000000 | * 777.892090 |
| * | 22.415390 | * | 18529.609400 | * | 1755.413820 | * | 24000.000000 | * 784.538574 |
| * | 22.605286 | * | 18683.722700 | * | 1746.558110 | * | 24000.000000 | * 791.184814 |
| * | 22.795181 | * | 18837.746100 | * | 1735.896970 | * | 24000.000000 | * 797.831299 |
| * | 22.985077 | * | 18991.644500 | * | 1723.493900 | * | 24000.000000 | * 804.477539 |
| * | 23.174973 | * | 19145.402300 | * | 1709.431880 | * | 24000.000000 | * 811.124023 |
| * | 23.364868 | * | 19299.007800 | * | 1693.809570 | * | 24000.000000 | * 817.770264 |
| * | 23.554764 | * | 19452.437500 | * | 1676.730710 | * | 24000.000000 | * 824.416504 |
| * | 23.744659 | * | 19605.695300 | * | 1658.295170 | * | 24000.000000 | * 831.062988 |
| * | 23.934555 | * | 19758.785200 | * | 1638.600340 | * | 24000.000000 | * 837.709229 |
| * | 24.124451 | * | 19911.699200 | * | 1617.746830 | * | 24000.000000 | * 844.355713 |

CRUISE MISSILE TESTS
BASELINE MISSION SET
GLINT PLUS ECM AT 0.2 HZ
9-19-84

*** BLINKER FREQUENCY= 0.20

DATA SET NUMBER 4 OF 4

| | TIME......(SEC) | | XM...(FT NORTH) | | YM....(FT EAST) | | XT...(FT NORTH) | XM....(FT EAST) |
|---|---|---|---|---|---|---|---|---|
| * | 24.314346 | * | 20064.460900 | * | 1595.848880 | * | 24000.000000 | * 851.001953 |
| * | 24.504242 | * | 20217.089800 | * | 1573.031490 | * | 24000.000000 | * 857.648437 |
| * | 24.694138 | * | 20369.617200 | * | 1549.432370 | * | 24000.000000 | * 864.294678 |
| * | 24.884033 | * | 20522.062500 | * | 1525.198730 | * | 24000.000000 | * 870.941162 |
| * | 25.073929 | * | 20674.441400 | * | 1500.484370 | * | 24000.000000 | * 877.587402 |
| * | 25.263824 | * | 20826.812500 | * | 1475.440190 | * | 24000.000000 | * 884.233643 |
| * | 25.453720 | * | 20979.183600 | * | 1450.201660 | * | 24000.000000 | * 890.880127 |
| * | 25.643616 | * | 21131.578100 | * | 1424.848630 | * | 24000.000000 | * 897.526367 |
| * | 25.833511 | * | 21284.023400 | * | 1399.423830 | * | 24000.000000 | * 904.172852 |
| * | 26.023407 | * | 21436.527300 | * | 1373.927490 | * | 24000.000000 | * 910.819092 |
| * | 26.213303 | * | 21589.078100 | * | 1348.337400 | * | 24000.000000 | * 917.465576 |
| * | 26.403198 | * | 21741.671900 | * | 1322.615970 | * | 24000.000000 | * 924.111816 |
| * | 26.593094 | * | 21894.339800 | * | 1296.726810 | * | 24000.000000 | * 930.758057 |
| * | 26.782990 | * | 22047.039100 | * | 1270.628660 | * | 24000.000000 | * 937.404541 |
| * | 26.972885 | * | 22199.781200 | * | 1244.285160 | * | 24000.000000 | * 944.050781 |
| * | 27.162781 | * | 22352.566400 | * | 1217.680910 | * | 24000.000000 | * 950.697266 |
| * | 27.352676 | * | 22505.390600 | * | 1190.884520 | * | 24000.000000 | * 957.343506 |
| * | 27.542572 | * | 22658.285200 | * | 1164.029050 | * | 24000.000000 | * 963.989990 |

| | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| * | 27.732468 | *22811.261700 | * | 1137.282230 | *24000.000000 | * | 970.636230 |
| * | 27.922363 | *22964.343700 | * | 1110.862550 | *24000.000000 | * | 977.282715 |
| * | 28.112259 | *23117.585900 | * | 1085.108890 | *24000.000000 | * | 983.928955 |
| * | 28.302155 | *23271.027300 | * | 1060.469970 | *24000.000000 | * | 990.575195 |
| * | 28.492050 | *23424.718700 | * | 1037.558840 | *24000.000000 | * | 997.221680 |
| * | 28.681946 | *23578.683600 | * | 1017.097900 | *24000.000000 | * | 1003.867920 |
| * | 28.871841 | *23732.902300 | * | 999.782715 | *24000.000000 | * | 1010.514400 |
| * | 29.061737 | *23887.324200 | * | 986.245850 | *24000.000000 | * | 1017.160640 |

APPENDIX C

TASM SIMULATION PROGRAM NOMENCLATURE

```
*****************************************************************************

CONTROL

  TIME                  TIME IN SECONDS
  DT                    INTEGRATION INTERVAL
  OPDT                  OUTPUT INTERVAL
  NPTS                  NUMBER OF OUTPUT SETS SAVED
  CPA                   FLAG SET TO INDICATE TERMINATION & REASON
  PTS                   ARRAY CONTAINING ALL SAVED DATA
  NFAZE                 SETS THE PHASE APPLIED TO ECM BLINKER
  PCFRNG                SETS THE RANGE AT WHICH CLIMB IS COMMENCED

MISSILE DYNAMICS

  U,V,W                 BODY AXIS LINEAR VELOCITIES (FT/SEC)
  UDOT,VDOT,WDOT        BODY AXIS LINEAR ACCELERATIONS
  P,Q,R                 BODY AXIS ANGULAR VELOCITIES (RAD/SEC)
  ROLLRT,PTCHRT,YAWRT                       "              (DEG/SEC)
  PDOT,QDOT,RDOT        BODY AXIS ANGULAR ACCELERATIONS
  X,Y,Z                 BODY AXIS AERODYNAMIC FORCES (LBS)
  L,D                   LIFT, DRAG AERODYNAMIC FORCES (LBS)
  LA,MA,NA              BODY AXIS AERODYNAMIC MOMENTS (FT-LBS)
  PHI,THETA,SY          EULER ANGLES (RAD)
  BANK,PITCH,HEADNG          "       (DEG)
  PHIDOT,THETAD,SYDOT        "       RATE OF CHANGE OF
  ALFA,BETA             ANGLE OF ATTACK, SIDESLIP (RAD)
  ACA,SIDESL                 "               "     (DEG)
  ALFADT,BETADT         RATE OF CHANGE OF ALFA,BETA
  GAMMA                 FLIGHT PATH ANGLE (RAD)
  FLTPTH                     "             (DEG)
  NY,NZ                 LATERAL ACCELERATION, LOAD FACTOR (G'S)
  XM,YM,ALTUDE          EARTH COORDINATES OF MISSILE (FT)
                        (XM-NORTH,YM-EAST)
  XMDOT,YMDOT,HMDOT     RATES OF CHANGE OF XM, YM, ALTITUDE
  VT                    TOTAL MISSILE VELOCITY (FT/SEC)
  CHORD,SPAN            MEAN AERODYNAMIC CHORD, SPAN (FT)
  CHORD2, SPAN2         HALF CHORD, HALF SPAN
```

```
  WT,M,G              GROSS WEIGHT, MASS, ACCEL DUE TO GRAVITY
  T,S                 THRUST, WING AREA
  RHC                 AIR DENSITY
  QS                  DYNAMIC PRESSURE X WING AREA
  C--                 AERODYNAMIC COEFFICIENTS
  DC---               INCREMENTS IN     "
  IXX,IYY,IZZ,IXZ     MOMENTS AND PRODUCTS OF INERTIA
  IA - IK             FUNCTIONS OF      "
  ELE,AIL,RUD         STANDARD CONTROL DEFLECTIONS (DEG)
  STBLTR,AILRON,RUDDER         CONTROL DEFLECTIONS WITH LIMITS
                               APPLIED (DEG)
  RSTAB1,LSTAB1       TASM UNLIMITED CONTROL DEFLECTIONS (DEG)
  RSTAB,LSTAB         TASM LIMITED CONTROL DEFLECTIONS (DEG)
  ---1                INITIAL CONDITION

AUTOPILOT

  K---                AUTOPILOT GAINS
  CGARM-              ACCELEROMETER LOCATION WRT CG
  E---                COMPARATOR ERRORS
  ---LIM              LIMITED VALUES
  ---SERI             SERVO INPUTS
  ---SERO             SERVO OUTPUTS
  ---C                COMMANDED VALUES
  ---F,---FF,---FFF   FILTERED SENSOR VARIABLE
  FNCOF-,FDCOF-       NOTCH FILTER COEFFICIENTS

GUIDANCE

  AZC,AYC             COMMANDED VERTICAL AND HORIZONTAL
                      ACCELERATIONS IN EARTH AXES (G'S)
  XT,YT,HT            EARTH COORDINATES OF TARGET (FT)
  XR,YR,HR            POSITION OF THE TARGET WRT MISSILE IN
                      EARTH COORDINATES (FT)
  XRECM,YRECM,HRECM   POSITION OF RADAR TARGET (XR,YR,HR WITH ECM
                      AND GLINT ADDED WRT MISSILE (FT)
  XDOTR,YDOTR,HDOTR   RATES OF CHANGE OF XRECM,YRECM,HRECM (FT/S)
                      (RELATIVE VELOCITY OF TGT WRT MISSILE)
  XECM,YECM,HECM      INCR. IN TARGET RADAR POSITION DUE TO ECM
  XGLNT,YGLNT,HGLNT   INCR. IN TARGET RADAR POSITION DUE TO GLINT
  RANGE               RANGE TO TARGET (FT)
  RNGECM,RGECMT       RANGE TO RADAR TARGET (TGT WITH ECM+GLINT)
  TSPEED              TARGET SPEED (FT/SEC)
  SYT,THETAT          HEADING, ELEV. TO TARGET FROM MISSILE (RAD)
  HEADT,ELEVT         HEADING, ELEV. TO TARGET FROM MISSILE (DEG)
  VTANAZ,VTANEL       COMPONENT OF RELATIVE VEL. PERPENDICULAR
                      TO LOS IN AZIMUTH AND ELEVATION (FT/SEC)
  TRAKAZ,TRAKEL       COMPONENT OF MISSILE VELOCITY VECTOR IN
```

| | |
|---|---|
| | AZIMUTH AND ELEVATION (FT/SEC) |
| SIGAZ,SIGEL | EARTH AZIMUTH, ELEVATION LOS ANGLES (RAD) |
| DSIGAZ,DSIGEL | EARTH AZIMUTH, ELEVATION LOS ANGLES (DEG) |
| SIGDAZ,SIGDEL | RATES OF CHANGE OF EARTH REFERENCED LOS (RAD/SEC) |
| DSGDAZ,DSGDEL | SAME AS ABOVE (DEG/SEC) |
| SIGDAF,SIGDEF | FILTERED SIGDAT,SIGDET (RAD/SEC) |
| DSGDAF,DSGDEF | FILTERED DSGDAT,DSGDET (DEG/SEC) |
| LAMDAZ,LAMDEL | PROPORTIONAL NAVIGATION CONSTANTS |
| FREQ | FREQUENCY OF ECM BLINKING |
| SHIFTY,SHIFTH | DISTANCE OF ECM BLINKER FROM TARGET AIM POINT (FT) |
| BRNTHR | BURN-THROUGH RANGE |
| KNFAZ,KNFEL | AZIMUTH AND ELEVATION NAVIGATION FILTER CONSTANTS |

```
C
C
C
C                      APPENDIX D
C
C                 MAIN PROGRAM LISTING
C                         FOR
C          TACTICAL CRUISE MISSILE SIMULATION
C
C                         ***
C                    TRANSLATED BY
C            CDR BARTON P. ANDERSON, USN
                          ***
C                NAVY POSTGRADUATE SCHOOL
C       DEPARTMENT OF AERONAUTICAL ENGINEERING
C                 MONTEREY, CA 93943
C                         ***
C            TRANSLATED FROM CSMP PROGRAM BY
C                  DR. MARLE HEWETT
C              LCDR KENT WATTERSON, USN
C
C                                                            9-10-84
C *******************************************************************
C     PROGRAM TCMC
C *******************************************************************
C     CONTROLS THE OVERALL EXECUTION OF THE SIMULATION. CALLS THE
C     NECESSARY SUBROUTINES, DETERMINES WHEN THE DATA MUST BE STORED
C     FOR OUTPUT AND WHEN THE RUN HAS COMPLETED DUE TO CPA OR FINTIM.
C     ***************************************************************
C
      IMPLICIT REAL(A-Z)
      INTEGER PH1,PH2,PH3,PH4,I,J,K,N,NPTS,CPA,NOUT,PCOUNT,NFAZE
C
C
C     ******************************************
C     COMMON BLOCK /A/: MISCELLANEOUS CONSTANTS
C     ******************************************
C
      COMMON /A/ TIME  ,FINTIM,DT    ,CPDT ,NOUT ,NPTS ,CPA   ,PCOUNT,
     *           G     ,T     ,RHO   ,PI   ,PII  ,MASS ,WT    ,S     ,
     *           IXX   ,IYY   ,IZZ   ,IXZ  ,IA   ,IB   ,IC    ,CS    ,
     *           ID    ,IE    ,IF    ,IG   ,IH   ,II   ,IJ    ,IK    ,
     *           CHORD2,CHORD ,SPAN2 ,SPAN ,NFAZE
C
C
C     ******************************************
C     COMMON BLOCK /H/: ECM/GLINT PARAMETERS
C     ******************************************
```

```
C
      COMMON /H/ FREQ          ,SHIFTY       ,SHIFTH       ,BRNTHR       ,
     *           XECM          ,YECM         ,HECM         ,XGLNT        ,
     *           YGLNT         ,HGLNT        ,XTECM        ,YTECM        ,
     *           HTECM
C
C     *******************************************
C     COMMON BLOCK /F/: GUIDANCE PARAMETERS
C     *******************************************
C
      COMMON /F/ PH1           ,PH2          ,PH3          ,PH4          ,
     *           OFFSET        ,ALTATT       ,SGDZPU       ,MISDST       ,
     *           LAMDAZ        ,LAMDEL       ,KNFAZ        ,KNFEL        ,
     *           NZC           , PHIC        ,GAMMAC       ,PCLIM        ,
     *           PC            ,QC           ,RC           ,RANGE        ,
     *           SIGAZ         ,SIGEL        ,SIGDAF       ,SIGDEF       ,
     *           SYT           ,THETAT       ,XT           ,YT           ,
     *           HT            ,NYC          ,POPRNG
C
C
C     *******************************************
C     COMMON BLOCK /I/: OUTPUT ARRAY
C     *******************************************
C
      COMMON /I/ PTS(300,20)
C
C*********************************************************************
C
C *** INITIALIZE ALL VARIABLES
C
C     PLOTTING SURFACE
C
C
      CALL TEK618
      CALL COMPRS
      CALL SWISSM
C
C
    1 CALL INIT
C
C *** BEGIN DYNAMIC SIMULATION ***************************************
C
C
   10 IF(CPA.GE.1.0) GO TO 100
            TIME=TIME+DT
            IF(TIME.GE.FINTIM) CPA=2.0
            PCOUNT =   PCOUNT+1
C
C
C *** FROM MISSION PROFILE/GUIDANCE, GENERATE NZC,PHIC
```

```
C
            CALL MISSN1
C
C
C *** GENERATE CONTROL MCVEMENTS: STBLTR, AILRON, RUDDER
C
            CALL APILOT
C
C
C *** GENERATE MISSILE MOTION AND POSITION
C
            CALL AERO
C
C
C *** GENERATE APPARENT RADAR TARGET POSITION & MOTION
C
            CALL TGTNAV
C
C
C *** STORE REQUIRED PLOT DATA IN THE PTS ARRAY.
C
            IF(PCOUNT.LT.NOUT)GO TO 50
                 CALL PREPAR
                 PCOUNT = 0.0
   50       CONTINUE
C
            GO TO 10
C
  100 CONTINUE
C
C *** END DYNAMIC SIMULATION ******************************************
C
C
C
C *** INVOKE DISSPLA AND TABULAR OUTPUT ROUTINES
C
      CALL CUTPUT(NPTS,CPA)
C
C ************ TESTPATCH TO BYPASS ITERATIONS (KTEST = 1)
      KTEST = 0
      IF(KTEST.EQ.1) GO TO 150
C ************ ENDTEST
C
C *** ITERATE THE PHASE VARIABLE IN THE ECM PACKAGE
C
      NFAZE  = NFAZE + 1
      IF(NFAZE.LE.4) GO TO 1
      NFAZE = 1
C
```

```
C *** ITERATE THE BLINKER FREQUENCY
C
      FREQ = FREQ +5.0
C
      IF(FREQ.LE.30.0)  GO TO 1
 150  CALL DONEPL
C
      STOP
      END
C
C                                                                 9-07-84
C***********************************************************************
      SUBROUTINE INIT
C***********************************************************************
C     BLOCK DATA
C**********************
C     CONTAINS DATA STATEMENTS AND ASSIGNMENT STATEMENTS FOR
C     VARIABLES NOT INITIALIZED IN THE BLOCK DATA SUBPROGRAM BELOW.
C     ALSO REINITIALIZES INITIAL CONDITIONS FOR MORE THAN ONE RUN.
C     *****************************************************************
C
      IMPLICIT REAL(A-Z)
      INTEGER PH1,PH2,PH3,PH4,I,J,K,N,NPTS,CPA,NOUT,PCOUNT,NFAZE
C
C
      COMMON /A/ TIME   ,FINTIM,DT    ,CPDT  ,NOUT  ,NPTS  ,CPA   ,PCOUNT,
     *           G      ,T     ,RHO   ,PI    ,PII   ,MASS  ,WT    ,S     ,
     *           IXX    ,IYY   ,IZZ   ,IXZ   ,IA    ,IB    ,IC    ,QS    ,
     *           ID     ,IE    ,IF    ,IG    ,IH    ,II    ,IJ    ,IK    ,
     *           CHORD2,CHORD ,SPAN2,SPAN  ,NFAZE
C
      COMMON /C/ KPTCHR        ,KROLLR        ,KYAWRT        ,KBANK        ,
     *           KGAMMA        ,KALT          ,CGARML        ,CGARMN       ,
     *           KRTLIM        ,PLIM          ,KNY           ,KNZ          ,
     *           AILRON        ,STBLTR        ,RUDDER        ,
     *           BSERO         ,NZSERO        ,NYSERO
C
      COMMON /D/ ALFA          ,BETA          ,VT            ,HMDOT        ,
     *           U             ,V             ,W             ,
     *           PHI           ,GAMMA         ,THETA         ,SY           ,
     *           CD            ,CY            ,CL            ,CR           ,
     *           CM            ,CN            ,P             ,Q            ,
     *           R             ,ALFADT        ,BETADT        ,PDOT         ,
     *           QDOT          ,RDOT          ,NZ            ,ALTUDE       ,
     *           XM            ,YM            ,XMDOT         ,YMDOT
C
      COMMON /E/ XM1           ,YM1           ,ALTUD1        ,U1           ,
     *           PITCH1        ,BANK1         ,HEDNG1        ,SIDES1       ,
```

```
     *              ADA1          ,PTCHR1       ,ROLLR1       ,YAWR1        ,
     *              XT1           ,YT1          ,HT1          ,TSPEED
C
      COMMON /F/ PH1           ,PH2          ,PH3          ,PH4          ,
     *              OFFSET        ,ALTATT       ,SGDZPU       ,MISDST       ,
     *              LAMDAZ        ,LAMDEL       ,KNFAZ        ,KNFEL        ,
     *              NZC           , PHIC        ,GAMMAC       ,PCLIM        ,
     *              PC            ,QC           ,RC           ,RANGE        ,
     *              SIGAZ         ,SIGEL        ,SIGDAF       ,SIGDEF       ,
     *              SYT           ,THETAT       ,XT           ,YT           ,
     *              HT            ,NYC          ,POPRNG
C
      COMMON /H/ FREQ          ,SHIFTY       ,SHIFTH       ,BRNTHR       ,
     *              XECM          ,YECM         ,HECM         ,XGLNT        ,
     *              YGLNT         ,HGLNT        ,XTECM        ,YTECM        ,
     *              HTECM
C
      COMMON /I/ PTS(300,20)
C
C
C EXECUTABLE STMTS ***************************************************
C
C *** COMPUTED CONSTANTS
C
      PII= 180.0/PI
      IA = IXX*IZZ-IXZ**2
      IB = IZZ/IA
      IC = IXZ/IA
      ID = IXZ*(IYY-IXX-IZZ)/IA
      IE = (IZZ**2-IYY*IZZ+IXZ**2)/IA
      IF = 1/IYY
      IG = (IXX-IZZ)/IYY
      IH = IXZ/IYY
      II = IXX/IA
      IJ = (IXX*IYY-IXX**2-IXZ**2)/IA
      IK = (IXX+IZZ-IYY)*IXZ/IA
C
      PLIM    = RRTLIM/PII
C
C ********************************************************************
C     PARAMETERS TO BE INITIALIZED FOR EACH RUN FOLLOW.
C     ****************************************************************
C
      TIME = 0.0
      CPA  = 0
      PCOUNT     = 0
      NOUT = INT(OPDT/DT)
      IF(AMOD(OPDT,DT).GE.0.5) NOUT=NOUT+1
```

```
C
      NPTS = C
      DO 100 I=1,300
         DC 50 J=1,20
            PTS(I,J)   = 0.0
 50      CCNTINLE
10C   CONTINLE
C
      U  =  L1
      W  =  L1*TAN(AOA1/PII)
      V  =  SCRT(U1**2+W**2)*TAN(SIDES1/PII)
      VT = SCRT(U**2+V**2+W**2)
      QS = 12.0*RHO*(VT**2)/2.0
C
      P  =  RCLLR1/PII
      Q  =  PTCHR1/PII
      R  =  YAWR1/PII
C
      PDCT    = 0.0
      QDCT    = 0.0
      RDOT    = 0.0
C
      THETA   = PITCH1/PII
      PHI     = BANK1/PII
      SY      = HEDNG1/PII
      GAMMA   = 0.0
      NZ      = 1.0
C
C
      XM    = XM1
      YM    = YM1
      ALTUDE     = ALTUD1
C
      AOA   = ACA1
      ALFA    = ACA1/PII
      ALFADT     = 0.0
C
      SICESL     = SIDES1
      BETA    = SIDES1/PII
      BETADT     = 0.0
C
      XT    = XT1
      YT    = YT1
      HT    = HT1
      RANGE  = SQRT((XT-XM)**2+(YT-YM)**2+(HT-ALTUCE)**2)
C
      PH1   = 0
      PH2   = C
```

```
      PH3    = 0
      PH4    = 0
C
C *** INITIAL CONTROL POSITIONS
C
      ELE1    = -1.0
      AIL1    =  0.0
      RUD1    =  0.0
C
      NZSERO = -ELE1/PII
      BSERO  = -AIL1/PII
      NYSERO = -RUD1/PII
C
C *** INITIAL ACCELERATIONS & COMMANDED RATES
C
      NZ      = 1.0
      NY      = 0.0
C
      PC    = 0.0
      QC    = -ELE1/PII
      RC    = 0.0
C
C *** PARAMETERS TO BE CHANGED FROM BASELINE VALUES
C
C
      FINTIM = 30.0
      KRCLLR = 0.5
      ALTATT = 0.0
      BRNTHR= 500
C
      SIGDAF = TSPEED/XT1
      SIGDEF = (HT1-ALTUC1)*U1/XT1**2
C
      RETURN
      END
C
C
C
C
C                                                                    9-07-84
C ****************************************************************************
C     BLOCK DATA SUBPROGRAM TO INITIALIZE COMMON BLOCKS OF MEMORY.
C ****************************************************************************
      BLOCK DATA
C     **********
C
      IMPLICIT REAL(A-Z)
      INTEGER PH1,PH2,PH3,PH4,NPTS,CPA,NULT,PCOUNT,TITLE,PLTN,LEG,XN,
```

```
     *         YN,NFAZE
C
      COMMON /A/ TIME   ,FINTIM,DT    ,OPDT  ,NCUT  ,NPTS  ,CPA   ,PCOUNT,
     *           G      ,T     ,RHO   ,PI    ,PII   ,MASS  ,WT    ,S     ,
     *           IXX    ,IYY   ,IZZ   ,IXZ   ,IA    ,IB    ,IC    ,QS    ,
     *           ID     ,IE    ,IF    ,IG    ,IH    ,II    ,IJ    ,IK    ,
     *           CHORD2,CHORD  ,SPAN2 ,SPAN  ,NFAZE
C
      COMMON /B/ LFT1(2,36)   ,LFT2(2,36)   ,DRG1(2,36)   ,DRG2(2,36)   ,
     *           DRG3(2,36)   ,DRG4(2,36)   ,PTCH1(2,36)  ,PTCH2(2,36)  ,
     *           SID1(6,10)   ,SID2(6,10)   ,SID3(6,10)   ,DREC1(6,10)  ,
     *           DREC2(6,10)  ,DREC3(6,10)  ,LTRL1(6,10)  ,LTRL2(6,10)  ,
     *           LTRL3(6,10)  ,CLADT        ,CDADT        ,CMADT        ,
     *           CLQ          ,CDQ          ,CMQ          ,CRBDT        ,
     *           CYR          ,CNBDT        ,CRR          ,CYP          ,
     *           CNR          ,CRP          ,CYBDT        ,CNP
C
      COMMON /C/ KPTCHR       ,KROLLR       ,KYAWRT       ,KBANK        ,
     *           KGAMMA       ,KALT         ,CGARML       ,CGARMN       ,
     *           RRTLIM       ,PLIM         ,KNY          ,KNZ          ,
     *           AILRON       ,STBLTR       ,RUDDER       ,
     *           BSERO        ,NZSERO       ,NYSERO
C
      COMMON /D/ ALFA         ,BETA         ,VT           ,HMDOT        ,
     *           U            ,V            ,W            ,
     *           PHI          ,GAMMA        ,THETA        ,SY           ,
     *           CD           ,CY           ,CL           ,CR           ,
     *           CM           ,CN           ,P            ,Q            ,
     *           R            ,ALFADT       ,BETADT       ,PDOT         ,
     *           QDOT         ,RDOT         ,NZ           ,ALTUDE       ,
     *           XM           ,YM           ,XMDOT        ,YMDOT
C
      COMMON /E/ XM1          ,YM1          ,ALTUD1       ,U1           ,
     *           PITCH1       ,BANK1        ,HEDNG1       ,SIDES1       ,
     *           AOA1         ,PTCHR1       ,ROLLR1       ,YAWR1        ,
     *           XT1          ,YT1          ,HT1          ,TSPEED
C
      COMMON /F/ PH1          ,PH2          ,PH3          ,PH4          ,
     *           OFFSET       ,ALTATT       ,SGDZPU       ,MISDST       ,
     *           LAMDAZ       ,LAMDEL       ,KNFAZ        ,KNFEL        ,
     *           NZC          , PHIC        ,GAMMAC       ,PCLIM        ,
     *           PC           ,QC           ,RC           ,RANGE        ,
     *           SIGAZ        ,SIGEL        ,SIGDAF       ,SIGDEF       ,
     *           SYT          ,THETAT       ,XT           ,YT           ,
     *           HT           ,NYC          ,POPRNG
C
      COMMON /H/ FREQ         ,SHIFTY       ,SHIFTH       ,BRNTHR       ,
     *           XECM         ,YECM         ,HECM         ,XGLNT        ,
```

```
     *           YGLNT       ,HGLNT      ,XTECM      ,YTECM      ,
     *           HTECM
C
C
C       ******************************************
C       COMMON BLOCK /I/: OUTPUT ARRAY
C       ******************************************
C
        COMMON /I/ PTS(300,20),PLTN(6,7),XN(6,7),YN(6,7),TITLE(8,4),
     *           LEG(4,20)
C
C
C
C*** INITIALIZE THE DATA
C
C       ******************************************
C       COMMON BLOCK /A/: MISCELLANEOUS CONSTANTS
C       ******************************************
C
C
        DATA      TIME  ,FINTIM ,DT      ,OPDT     ,CPA
     *          /0.0   ,30.0   ,0.01    ,0.20     ,0        /
C
        DATA      G     ,T      ,RHO     ,PI       ,WT       ,MASS
     *          /32.17 ,242.3  ,.002377 ,3.141593 ,2200.    ,68.38   /
C
        DATA      IXX   ,IYY    ,IZZ     ,IXZ      ,S
     *          /27.8  ,1507.0 ,1512.0  ,11.7     ,12.0     /
C
        DATA      CHORD2,CHORD  ,SPAN2   ,SPAN     ,NFAZE
     *          /0.707 ,1.414  ,4.2425  ,8.485    ,1         /
C
C
C
C       ******************************************
C       COMMON BLOCK /B/: AERODYNAMIC COEFFICIENT TABLES
C       ******************************************
C
C
C ** STATIC AERODYNAMIC COEFFICIENTS
C
C   * 1.  LIFT COEFFICIENT DATA
C
C         A.  CLBAS VS. AOA (BASIC LIFT COEFFICIENT AS A FUNCTION
C             OF ANGLE OF ATTACK)  .
C
        DATA LFT1/ -12.0,-0.32,  -11.0,-0.39,  -10.0,-0.46,  -9.0,-0.57,
     *              -8.0,-0.70,   -7.0,-0.69,  - 6.0,-0.65,  -5.0,-0.58,
```

```
     *              -4.0,-0.50,   -3.0,-0.42,   -2.0,-0.30,   -1.0,-0.18,
     *               0.0,-0.08,    1.0, 0.04,    2.0, 0.15,    3.0, 0.25,
     *               4.0, 0.36,    5.0, 0.47,    6.0, 0.58,    7.0, 0.69,
     *               8.0, 0.80,    9.0, 0.87,   10.0, 0.78,   11.0, 0.70,
     *              12.0, 0.64,   22*9999.0/
C
C
C          B.  DCLSTE VS. STBLTR (INCREMENT IN LIFT COEFFICIENT
C              DUE TO SYMMETRIC STABILATOR DEFLECTION)
C
      DATA LFT2/ -15.0,-.100,  -14.0,-.097,  -13.0,-.094,  -12.0,-.090,
     *           -11.0,-.084,  -10.0,-.078,   -9.0,-.071,   -8.0,-.065,
     *            -7.0,-.056,   -6.0,-.048,   -5.0,-.040,   -4.0,-.032,
     *            -3.0,-.024,   -2.0,-.016,   -1.0,-.008,    0.0, .000,
     *             1.0, .008,    2.0, .016,    3.0, .024,    4.0, .033,
     *             5.0, .041,    6.0, .049,    7.0, .057,    8.0, .065,
     *             9.0, .073,   10.0, .080,   11.0, .086,   12.0, .092,
     *            13.0, .096,   14.0, .098,   15.0, .100,   10*9999./
C
C
C   *  2.  DRAG COEFFICIENT DATA
C
C          A.  CDBAS VS. CLBAS (BASIC DRAG COEFFICIENT AS A FUNCTION
C              OF BASIC LIFT COEFFICIENT)
C
      DATA DRG1/   -.9, .080,     -.8, .061,     -.7, .050,     -.6, .042,
     *             -.5, .035,     -.4, .031,     -.3, .026,     -.2, .023,
     *             -.1, .022,     0.0, .022,     0.1, .023,     0.2, .024,
     *             0.3, .026,     0.4, .031,     0.5, .036,     0.6, .042,
     *             0.7, .049,     0.8, .057,     0.9, .068,     1.0, .080,
     *             32*9999./
C
C
C          B.  CCDSTE VS. STBLTR (INCREMENT IN DRAG COEFFICIENT
C              DUE TO SYMMETRIC STABILATOR DEFLECTION)
C
      DATA DRG2/ -15., .0106,  -14., .0091,  -13., .0077,  -12., .0065,
     *           -10., .0044,   -9., .0036,   -8., .0028,   -7., .0022,
     *            -6., .0016,   -5., .0011,   -4., .0007,   -3., .0003,
     *            -2., .0001,   -1., 0.   ,    0., 0.   ,    1., .0001,
     *             2., .0004,    3., .0007,    4., .0011,    5., .0016,
     *             6., .0023,    7., .0030,    8., .0039,    9., .0049,
     *            10., .0060,   11., .0073,   12., .0089,   13., .0106,
     *            14., .0126,   15., .0146,   12*9999.  /
C
C          C.  DCDSTA VS. AILRON (INCREMENT IN DRAG COEFFICIENT
C              DUE TO ASYMMETRIC STABILATCR DEFLECTION)
C
```

```
      DATA DRG3/ -15., .0120,  -14., .0102,  -13., .0085,  -12., .0071,
     *           -10., .0048,   -9., .0038,   -8., .0030,   -7., .0023,
     *            -6., .0016,   -5., .0011,   -4., .0007,   -3., .0003,
     *            -2., .0001,   -1., .0000,    0., .0000,    1., .0000,
     *             2., .0001,    3., .0003,    4., .0007,    5., .0011,
     *             6., .0017,    7., .0023,    8., .0030,    9., .0038,
     *            10., .0048,   11., .0059,   12., .0071,   13., .0085,
     *            14., .0100,   15., .0120,   12*9999.  /
C
C        D.  DCDSTR VS. RUDDER (INCREMENT IN DRAG COEFFICIENT
C            DUE TO RUDDER DEFLECTION)
C
      DATA DRG4/ -15., .0059,  -14., .0054,  -13., .0048,  -12., .0043,
     *           -10., .0032,   -9., .0027,   -8., .0022,   -7., .0017,
     *            -6., .0013,   -5., .0009,   -4., .0006,   -3., .0003,
     *            -2., .0002,   -1., .0001,    0., .0000,    1., .0001,
     *             2., .0001,    4., .0006,    5., .0009,    6., .0013,
     *             7., .0017,    8., .0022,    9., .0027,   10., .0032,
     *            11., .0037,   12., .0043,   13., .0048,   14., .0054,
     *            15., .0059,   14*9999.  /
C
C
C  *  3.   PITCHING MOMENT COEFFICIENT DATA
C
C        A.  CMBAS VS. ACA (BASIC PITCHING MOMENT COEFFICIENT
C            AS A FUNCTION OF ANGLE OF ATTACK)
C
      DATA PTCH1/ -10., 1.13,    -8., 0.80,    -6., 0.50,    -4., 0.31,
     *             -2., 0.16,     0., 0.08,     2.,-0.03,     4.,-0.13,
     *              6.,-0.22,     8.,-0.32,    10.,-0.46,    12.,-0.62,
     *            48*9999. /
C
C        B.  DCMSTE VS. STBLTR (INCREMENT IN PITCHING MOMENT
C            COEFFICIENT DUE TO SYMMETRIC STABILATOR DEFLECTION)
C
      DATA PTCH2/ -15., .90,    -14., .88,    -12., .78,    -10., .68,
     *             -8., .56,     -6., .42,     -4., .27,     -2., .12,
     *              0., .00,      2.,-.10,      4.,-.20,      6.,-.32,
     *              8.,-.45,     10.,-.58,     12.,-.69,     14.,-.78,
     *             15.,-.80,    38*9999./
C
C
C  *  4.   SIDESLIP COEFFICIENT DATA
C
C        A.  CYBAS VS. SIDESL AND AOA (BASIC SIDE FORCE COEFFICIENT
C            AS A FUNCTION OF SIDESLIP AND ANGLE OF ATTACK. THE IN-
C            DEPENDENT VARIABLE IS SIDESLIP, THE PARAMETER IS ANGLE
C            OF ATTACK).
```

```
C
      DATA SIC1/   0.0,    -8.0   ,  -6.0   ,   4.0   ,   8.0   ,    9999.,
     *            -8.0,     0.148,    0.149,    0.140,    0.137,     9999.,
     *            -6.0,     0.111,    0.110,    0.100,    0.077,     9999.,
     *            -4.0,     0.073,    0.072,    0.063,    0.060,     9999.,
     *            -2.0,     0.034,    0.034,    0.025,    0.022,     9999.,
     *             0.0,    -0.002,   -0.003,   -0.013,   -0.020,     9999.,
     *             2.0,    -0.040,   -0.042,   -0.050,   -0.060,     9999.,
     *             4.0,    -0.077,   -0.078,   -0.089,   -0.096,     9999.,
     *             6.0,    -0.114,   -0.116,   -0.127,   -0.129,     9999.,
     *             8.0,    -0.151,   -0.153,   -0.162,   -0.162,     9999./
C
C
C         B.  CRBAS VS. SIDESL AND ACA (BASIC ROLL COEFFICIENT AS A
C             FUNCTION OF SIDESLIP AND PARAMETER ANGLE OF ATTACK)
C
      DATA SIC2/   0.0,    -8.0   ,   2.0   ,   6.0   ,  10.0   ,    9999.,
     *            -8.0,    .0048  ,  .0046  ,  .0040  ,  .0044  ,    9999.,
     *            -6.0,    .0038  ,  .0036  ,  .0028  ,  .0030  ,    9999.,
     *            -4.0,    .0026  ,  .0022  ,  .0015  ,  .0020  ,    9999.,
     *            -2.0,    .0014  ,  .0010  ,  .0004  ,  .0008  ,    9999.,
     *             0.0,    .0004  , -.0004  , -.0006  , -.0002  ,    9999.,
     *             2.0,   -.0005  , -.0014  , -.0020  , -.0014  ,    9999.,
     *             4.0,   -.0016  , -.0026  , -.0032  , -.0025  ,    9999.,
     *             6.0,   -.0030  , -.0038  , -.0042  , -.0036  ,    9999.,
     *             8.0,   -.0044  , -.0052  , -.0057  , -.0048  ,    9999./
C
C
C         C.  CNBAS VS. SIDESL AND ACA (BASIC YAW COEFFICIENT AS A
C             FUNCTION OF SIDESLIP AND PARAMETER ANGLE OF ATTACK)
C
      DATA SIC3/   0.0,    -8.0   ,   0.0   ,   6.0   ,   8.0   ,    9999.,
     *            -8.0,    -.034  , -.037   , -.042   , -.042   ,    9999.,
     *            -6.0,    -.025  , -.028   , -.033   , -.033   ,    9999.,
     *            -4.0,    -.016  , -.019   , -.022   , -.023   ,    9999.,
     *            -2.0,    -.007  , -.009   , -.012   , -.014   ,    9999.,
     *             0.0,     .001  , -.001   , -.004   , -.004   ,    9999.,
     *             2.0,     .010  ,  .009   ,  .007   ,  .007   ,    9999.,
     *             4.0,     .019  ,  .018   ,  .016   ,  .016   ,    9999.,
     *             6.0,     .028  ,  .026   ,  .024   ,  .024   ,    9999.,
     *             8.0,     .036  ,  .034   ,  .032   ,  .032   ,    9999./
C
C
C  *  5.  DIRECTIONAL CONTROL COEFFICIENT DATA
C
C         A.  CCYSTR VS. RUDDER AND ACA (INCREMENT IN SIDE FORCE
C             COEFFICIENT DUE TO RUDDER DEFLECTION AND PARAMETER
C             ANGLE OF ATTACK)
```

```
C
      DATA DREC1/  0.0,   -8.0  ,  2.0   ,  6.0   ,  8.0   ,    9999.,
     *         -15.0,  -.090  , -.097  , -.095  ,-.102   ,    9999.,
     *         -10.0,  -.060  , -.062  , -.062  ,-.069   ,    9999.,
     *          -5.0,  -.032  , -.036  , -.037  ,-.042   ,    9999.,
     *           0.0,   .004  , -.002  , -.003  ,-.003   ,    9999.,
     *           5.0,   .040  ,  .042  ,  .038  , .004   ,    9999.,
     *          10.0,   .070  ,  .066  ,  .062  , .066   ,    9999.,
     *          15.0,   .100  ,  .098  ,  .092  , .096   ,    9999.,
     * 12*9999./
C
C
C     B.  DCNSTR VS. RUDDER AND AOA (INCREMENT IN YAWING MOMENT
C         COEFFICIENT DUE TO RUDDER DEFLECTION AND PARAMETER
C         ANGLE OF ATTACK)
C
      DATA DREC2/  0.0,   -8.0  ,  2.0   ,  6.0   ,  8.0   ,    9999.,
     *         -15.0,   .070  ,  .068  ,  .062  , .065   ,    9999.,
     *         -10.0,   .050  ,  .049  ,  .048  , .048   ,    9999.,
     *          -5.0,   .026  ,  .024  ,  .022  , .018   ,    9999.,
     *           0.0,   .000  ,  .000  ,  .000  , .000   ,    9999.,
     *           5.0,  -.022  , -.020  , -.018  ,-.014   ,    9999.,
     *          10.0,  -.052  , -.048  , -.047  ,-.046   ,    9999.,
     *          15.0,  -.080  , -.079  , -.074  ,-.075   ,    9999.,
     * 12*9999./
C
C
C     C.  DCRSTR VS. RUDDER AND AOA (INCREMENT IN ROLLING MOMENT
C         COEFFICIENT DUE TO RUDDER DEFLECTION AND PARAMETER
C         ANGLE OF ATTACK)
C
      DATA DREC3/  0.0,   -8.0  ,  2.0   ,  4.0   ,  6.0   ,  8.0   ,
     *         -15.0,  -.0050 , -.0038 , -.0032 ,-.0022  ,-.0002  ,
     *         -10.0,  -.0034 , -.0029 , -.0026 ,-.0020  ,-.0004  ,
     *          -5.0,  -.0018 , -.0018 , -.0018 ,-.0014  ,-.0008  ,
     *           0.0,   .0004 ,  .0000 , -.0003 ,-.0008  ,-.0013  ,
     *           5.0,   .0024 ,  .0012 ,  .0004 ,-.0005  ,-.0014  ,
     *          10.0,   .0048 ,  .0028 ,  .0016 , .0000  ,-.0016  ,
     *          15.0,   .0070 ,  .0053 ,  .0040 ,-.0012  ,-.0025  ,
     * 12*9999./
C
C
C *  6.  LATERAL CONTROL COEFFICIENT DATA
C
C     A.  DCYSTA VS. AILRON AND AOA (INCREMENT IN SIDE FORCE
C         COEFFICIENT DUE TO ASYMETRIC STABILATOR DEFLECTION AND
C         PARAMETER ANGLE OF ATTACK)
C
```

```
      DATA LTRL1/  0.0,   -8.0  ,  -1.0  ,   4.0  , 10.0   ,    9999.,
     *          -15.0,   .015  ,  .019  ,  .017  , .006   ,    9999.,
     *          -10.0,   .013  ,  .014  ,  .010  ,-.002   ,    9999.,
     *           -5.0,   .010  ,  .009  ,  .002  ,-.010   ,    9999.,
     *            0.0,   .007  ,  .002  , -.007  ,-.018   ,    9999.,
     *            5.0,   .002  , -.003  , -.014  ,-.026   ,    9999.,
     *           10.0,  -.005  , -.009  , -.020  ,-.033   ,    9999.,
     *           15.0,  -.010  , -.014  , -.025  ,-.042   ,    9999.,
     * 12*9999./
C
C
C        B.  DCNSTA VS. AILRON AND AOA (INCREMENT IN YAWING MOMENT
C            COEFFICIENT DUE TO ASYMETRIC STABILATOR DEFLECTION AND
C            PARAMETER ANGLE OF ATTACK)
C
      DATA LTRL2/  0.0,   -8.0  ,  -4.0  ,   0.0  ,  4.0   ,  8.0   ,
     *          -15.0,   .0075 ,  .0050 ,  .00   ,-.0075  ,-.0120  ,
     *          -10.0,   .0040 ,  .0030 ,  .00   ,-.0050  ,-.0085  ,
     *           -5.0,   .0015 ,  .0020 ,  .00   ,-.0025  ,-.0060  ,
     *            0.0,  -.0020 , -.0010 ,  .00   ,-.0008  ,-.0020  ,
     *            5.0,  -.0070 , -.0030 ,  .00   , .0025  , .0050  ,
     *           10.0,  -.0120 , -.0045 ,  .00   , .0040  , .0120  ,
     *           15.0,  -.0175 , -.0070 ,  .00   , .0070  , .0175  ,
     * 12*9999./
C
C        C.  DCRSTA VS. AILRON AND AOA (INCREMENT IN ROLLING MOMENT
C            COEFFICIENT DUE TO ASYMETRIC STABILATOR DEFLECTION AND
C            PARAMETER ANGLE OF ATTACK)
C
      DATA LTRL3/  0.0,   -8.0  ,  -4.0  ,   0.0  ,  4.0   ,  8.0   ,
     *          -15.0,   .0087 ,  .0096 ,  .0100 , .0092  , .0084  ,
     *          -10.0,   .0060 ,  .0066 ,  .0068 , .0064  , .0058  ,
     *           -5.0,   .0030 ,  .0033 ,  .0034 , .0036  , .0030  ,
     *            0.0,   .0004 ,  .0004 ,  .0004 , .0000  , .0000  ,
     *            5.0,  -.0012 , -.0024 , -.0030 ,-.0030  ,-.0020  ,
     *           10.0,  -.0030 , -.0058 , -.0072 ,-.0046  ,-.0047  ,
     *           15.0,  -.0050 , -.0080 , -.0092 ,-.0088  ,-.0067  ,
     * 12*9999./
C
C
C
C ** 2. DYNAMIC STABILITY DERIVATIVES
C
      DATA  CLADT      ,CDADT         ,CMADT
     *     /2.00       ,0.10          ,-10.0  /,
     *      CLQ        ,CDQ           ,CMQ
     *     /5.0        ,0.1           ,-15.0  /,
     *      CRBDT      ,CYR           ,CNBDT
```

```
     *      /0.0          ,0.4          ,0.15    /,
     *       CRR          ,CYP          ,CNR
     *      /0.2          ,-0.1         ,-0.2    /,
     *       CRP          ,CYBDT        ,CNP
     *      /-C.4         ,-0.1         ,-0.01   /
C
C
C
C       ****************************************
C       COMMON BLOCK /C/: CONTROL SYSTEM PARAMETERS
C       ****************************************
C
C  *** CONTROL SYSTEM PARAMETERS
C
        DATA        KPTCHR        ,KROLLR      ,KYAWRT      ,KBANK
     *             /0.28          ,0.10        ,0.40        ,10.8    /,
     *              KGAMMA        ,KALT        ,CGARML      ,CGARMN
     *             /1.0           ,0.3         ,0.0         ,0.0     /,
     *              RRTLIM        ,KNY         ,KNZ
     *             /75.0          ,0.35        ,0.05/
C
C
C       ****************************************
C       COMMON BLOCK /E/: INITIAL CONDITIONS
C       ****************************************
C
C
C  *** MISSILE INITIAL CONDITIONS
C
        DATA        XM1           ,YM1         ,ALTUD1      ,U1
     *             /0.0           ,0.0         ,50.0        ,838.1/
C
        DATA        PITCH1        ,BANK1       ,HEDNG1      ,SIDES1
     *             /3.00          ,0.0         ,0.0         ,0.0     /
C
        DATA        AOA1          ,PTCHR1      ,ROLLR1      ,YAWR1
     *             /3.00          ,0.0         ,0.0         ,0.0     /
C
C
C  *** TARGET INITIAL CONDITIONS
C
        DATA        XT1          ,YT1          ,HT1         ,TSPEED
     *             /24000.0      ,0.0          ,10.0        ,35.0    /
C
C
C
C       ****************************************
C       COMMON BLOCK /F/: GUIDANCE PARAMETERS
```

```
C        ****************************************************
C
C
C *** PROPORTIONAL NAVIGATION & NAV FILTER CONSTANTS (AZIMUTH & ELEV.)
C
      DATA          LAMDAZ          ,LAMDEL         ,KNFAZ          ,KNFEL
     *              /3.15           ,3.85           ,0.8            ,0.50 /
C
C
C *** MISSION PHASE FLAGS & DECISION PARAMETERS
C
      DATA          PH1             ,PH2            ,PH3            ,PH4
     *              /0              ,0              ,0              ,0     /
C
      DATA          OFFSET          ,ALTATT         ,SGDZPU         ,MISDST
     *              /10.0           ,200.0          ,1.12           ,0.0   /
C
C
C
C        ****************************************************
C        COMMON BLOCK /H/: ECM/GLINT PARAMETERS
C        ****************************************************
C
      DATA          FREQ            ,SHIFTY         ,SHIFTH         ,BRNTHR
     *              /0.00           ,-75.0          ,10.0           ,250.0 /
C
      END
C
C                                                                   9-07-84
C **************************************************************************
      SUBROUTINE MISSN
C **************************************************************************
C     MAKES MISSION PHASE DECISIONS AND INVOKES THE DIFFERENT MODES
C     OF GUIDANCE AS REQUIRED. DELIVERS NZC AND PHIC TO THE AUTOPILOT
C     CONTROL LOOPS. NYC IS ASSUMED TO ALWAYS BE ZERO EXCEPT DURING
C     ATTACK. NZC IS LIMITED TO +4.0 AND -2.0 G'S.
C     **********************************************************************
C
      IMPLICIT REAL(A-Z)
      INTEGER PH1,PH2,PH3,PH4,I,J,K,N,NPTS,CPA,NCLT,PCOUNT,NFAZE
C
C
C        ****************************************************
C        COMMON BLOCK /A/: MISCELLANEOUS CONSTANTS
C        ****************************************************
C
      COMMON /A/ TIME   ,FINTIM,DT    ,CPDT  ,NCLT  ,NPTS ,CPA   ,PCOUNT,
     *           G      ,T      ,RHO  ,PI    ,PII   ,MASS ,WT    ,S     ,
```

```
     *          IXX    ,IYY    ,IZZ   ,IXZ   ,IA    ,IB    ,IC    ,QS    ,
     *          ID     ,IE     ,IF    ,IG    ,IH    ,II    ,IJ    ,IK    ,
     *          CHORD2,CHORD  ,SPAN2,SPAN  ,NFAZE
C
C
C     *********************************************
C     COMMON BLOCK /C/: CONTROL SYSTEM PARAMETERS
C     *********************************************
C
      COMMON /C/ KPTCHR         ,KROLLR         ,KYAWRT         ,KBANK         ,
     *           KGAMMA         ,KALT           ,CGARML         ,CGARMN        ,
     *           RRTLIM         ,PLIM           ,KNY            ,KNZ           ,
     *           AILRON         ,STBLTR         ,RUDDER         ,
     *           BSERO          ,NZSERO         ,NYSERO
C
C     *********************************************
C     COMMON BLOCK /D/: MISSILE FLIGHT DYNAMICS PARAMETERS
C     *********************************************
C
      COMMON /D/ ALFA           ,BETA           ,VT             ,HMDOT         ,
     *           U              ,V              ,W              ,
     *           PHI            ,GAMMA          ,THETA          ,SY            ,
     *           CD             ,CY             ,CL             ,CR            ,
     *           CM             ,CN             ,P              ,Q             ,
     *           R              ,ALFADT         ,BETADT         ,PDOT          ,
     *           QDOT           ,RDOT           ,NZ             ,ALTUDE        ,
     *           XM             ,YM             ,XMDOT          ,YMDOT
C
C     *********************************************
C     COMMON BLOCK /F/: GUIDANCE PARAMETERS
C     *********************************************
C
      COMMON /F/ PH1            ,PH2            ,PH3            ,PH4           ,
     *           OFFSET         ,ALTATT         ,SGDZPU         ,MISDST        ,
     *           LAMDAZ         ,LAMDEL         ,KNFAZ          ,KNFEL         ,
     *           NZC            , PHIC          ,GAMMAC         ,PCLIM         ,
     *           PC             ,QC             ,RC             ,RANGE         ,
     *           SIGAZ          ,SIGEL          ,SIGDAF         ,SIGDEF        ,
     *           SYT            ,THETAT         ,XT             ,YT            ,
     *           FT             ,NYC            ,PUPRNG
C
C     *********************************************
C     COMMON BLOCK /G/: OUTPUT PARAMETERS
C     *********************************************
C
      COMMON /G/ AOA            ,SIDESL         ,BANK           ,FLTPHC        ,
     *           BANKC          ,PITCH          ,ROLLRT         ,ROLRTC        ,
     *           PTCHRT         ,YAWRT          ,HEADNG         ,FLTPTH        ,
```

```
     *             HEADT         ,ELEVT        ,DSIGAZ       ,DSIGEL       ;
     *             DSGDAZ        ,DSGDEL       ,ERFBK        ,ERFRR        ;
     *             ERFAZ         ,ERFEL
C
C
C*****************************************************************************
C
C      MISSION PHASE LOGIC AND GUIDANCE COMMANDS
C
     1 IF(PH4.EQ.1) GO TO 40
       IF(PH3.EQ.1) GO TO 30
       IF(PH2.EQ.1) GO TO 20
       IF(PH1.EQ.1) GO TO 10
C
C  *** INGRESS FROM INITIAL CONDITION TO OFFSET MANEUVER
C
          IF(RANGE.LT.18000.0) GO TO 9
C
C            ALTITUDE HOLD
C
C
C
             ALTC   = 50.0
             ALTUDF = ALTUDE
             GAMMAC = KALT*(ALTC-ALTUDF)/VT
             GAMMAF = GAMMA
             AZC    = COS(GAMMAF)+KGAMMA*VT*(GAMMAC-GAMMAF)/G
C
C            PROPORTIONAL NAVIGATION IN AZIMUTH
C
             AYC    = LAMDAZ*VT*SIGDAF/G
             PHIC   = ATAN2(AYC,AZC)
             NZC    = AZC*COS(PHI)+AYC*SIN(PHI)
             GO TO 100
     9       PH1    = 1
C
C  *** OFFSET TURN (60 DEG BANK) TO OFFSET HEADING
C
    10    ABSDSZ = ABS(DSIGAZ)
          IF(ABSDSZ.GT.OFFSET) GO TO 19
C
C            ALTITUDE HOLD
C
             ALTC   = 50.0
             ALTUDF = ALTUDE
             GAMMAC = KALT*(ALTC-ALTUDF)/VT
             GAMMAF = GAMMA
             AZC    = COS(GAMMAF)+KGAMMA*VT*(GAMMAC-GAMMAF)/G
C
```

```
C               BANK ANGLE HOLD (60 DEG)
C
                AYC    = 0.0
                PHIC   = 60.0/PII
                NZC    = AZC/COS(PHI)
                GO TO 100
   19           PH2    = 1
C
C  ***       COURSE HOLD ON OFFSET HEADING TO POPUP
C
   20        ABDSDZ = ABS(DSGDAZ)
             IF(ABDSDZ.GT.SGDZPU) GO TO 29
C
C               ALTITUDE HOLD
C
                ALTC   = 50.0
                ALTUDF = ALTUDE
                GAMMAC = KALT*(ALTC-ALTUDF)/VT
                GAMMAF = GAMMA
                AZC    = COS(GAMMAF)+KGAMMA*VT*(GAMMAC-GAMMAF)/G
C
C               BANK ANGLE HOLD (0 DEG)
C
                AYC    = 0.0
                PHIC   = 0.0
                NZC    = AZC/COS(PHI)
                GO TO 100
   29           PH3    = 1
C
C  ***       PULLUP TO ATTACK ALTITUDE
C            PROPORTIONAL NAVIGATION IN AZIMUTH
C
   30        IF(ALTUDE.GT.ALTATT) GO TO 39
C
C               VERTICAL FLIGHT PATH ANGLE HOLD (8.5 DEG)
C
                ALTC   = 0.0
                GAMMAC = 8.5/PII
                GAMMAF = GAMMA
                AZC    = COS(GAMMAF)+KGAMMA*VT*(GAMMAC-GAMMAF)/G
C
C               PROPORTIONAL NAVIGATION IN AZIMUTH
C
                AYC    = LAMDAZ*VT*SIGDAF/G
                NZC    = AZC*COS(PHI)+AYC*SIN(PHI)
                PHIC   = ATAN2(AYC,AZC)
                GO TO 100
   39           PH4    = 1
```

```
C
C ***    ATTACK
C        PROPORTIONAL NAVIGATION IN AZIMUTH AND ELEVATION
C
   40          ALTC   = 0.0
               GAMMAC = 0.0
               GAMMAF = GAMMA
               AYC    = LAMDAZ*VT*SIGDAF/G
               AZC    = LAMDEL*VT*SIGDEF/G+COS(GAMMAF)
               NZC    = AZC*COS(PHI)+AYC*SIN(PHI)
               NYC    = 0.0
C
C              BANK ANGLE COMMAND ROUTINE INSURES ROLL
C              IN SHORTEST DIRECTION
C
               PHIC   = ATAN2(AYC,AZC)
               DELPHI = PHIC-PHI
               DPHIAB = ABS(DELPHI)
               IF(DPHIAB.LT.PI) GO TO 100
               IF(PHIC.GE.0.0) GO TO 90
               PHIC   = PHIC+2.0*PI
               GO TO 100
   90          PHIC   = PHIC-2.0*PI
  100 CONTINUE
C *****************************************************************
C
C *** NZ COMMAND LIMITED TO -2 & +4 G'S
C
      NZC  = LIMIT(-2.0,4.0,NZC)
C
      RETURN
      END
C
C                                                           9-07-84
C *****************************************************************
      SUBROUTINE APILOT
C *****************************************************************
C     LIMIT, REALPL
C   ***************************************************************
C     MODELS THE INNER LOOP AUTOPILOT AND CONTROL MIXER. CALCULATES
C     REQUIRED ELEVATOR, AILERON & RUDDER REQUIRED, MIXES THESE TO GET
C     THE FIN STABILATOR COMMANDS, APPLIES THE FIN LIMITS OF +-15 DEG.
C     AND ADJUSTS THE THREE CONTROL OUTPUTS TO ACCOUNT FOR THE LIMITS.
C     *************************************************************
C
      IMPLICIT REAL(A-Z)
      INTEGER PH1,PH2,PH3,PH4,I,J,K,N,NPTS,CPA,NOUT,PCOUNT,NFAZE
C
```

```
C
C     ****************************************************
C     COMMON BLOCK /A/: MISCELLANEOUS CONSTANTS
C     ****************************************************
C
      COMMON /A/ TIME  ,FINTIM,DT    ,GPDT ,NCUT ,NPTS ,CPA  ,PCOUNT,
     *          G     ,T     ,RHO   ,PI   ,PII  ,MASS ,WT   ,S     ,
     *          IXX   ,IYY   ,IZZ   ,IXZ  ,IA   ,IB   ,IC   ,QS    ,
     *          ID    ,IE    ,IF    ,IG   ,IH   ,II   ,IJ   ,IK    ,
     *          CHORD2,CHORD ,SPAN2 ,SPAN ,NFAZE
C
C
C     ****************************************************
C     COMMON BLOCK /C/: CONTROL SYSTEM PARAMETERS
C     ****************************************************
C
      COMMON /C/ KPTCHR      ,KRCLLR      ,KYAWRT      ,KBANK      ,
     *          KGAMMA      ,KALT        ,CGARML      ,CGARMN     ,
     *          RRTLIM      ,PLIM        ,KNY         ,KNZ        ,
     *          AILRON      ,STBLTR      ,RUDDER      ,
     *          BSERO       ,NZSERO      ,NYSERO
C
C
C     ****************************************************
C     COMMON BLOCK /D/: MISSILE FLIGHT DYNAMICS PARAMETERS
C     ****************************************************
C
      COMMON /C/ ALFA        ,BETA        ,VT          ,HMDOT      ,
     *          U           ,V           ,W           ,
     *          PHI         ,GAMMA       ,THETA       ,SY         ,
     *          CD          ,CY          ,CL          ,CR         ,
     *          CM          ,CN          ,P           ,Q          ,
     *          R           ,ALFADT      ,BETADT      ,PDOT       ,
     *          QDOT        ,RDOT        ,NZ          ,ALTUDE     ,
     *          XM          ,YM          ,XMDCT       ,YMDCT
C
C
C     ****************************************************
C     COMMON BLOCK /F/: GUIDANCE PARAMETERS
C     ****************************************************
C
      COMMON /F/ PH1         ,PH2         ,PH3         ,PH4        ,
     *          OFFSET      ,ALTATT      ,SGDZPU      ,MISDST     ,
     *          LAMDAZ      ,LAMDEL      ,KNFAZ       ,KNFEL      ,
     *          NZC         , PHIC       ,GAMMAC      ,PCLIM      ,
     *          PC          ,QC          ,RC          ,RANGE      ,
     *          SIGAZ       ,SIGEL       ,SIGDAF      ,SIGDEF     ,
     *          SYT         ,THETAT      ,XT          ,YT         ,
```

```
     *              FT                ,NYC              ,POPRNG
C
C EXECUTABLE STMTS *************************************************************
C
C       INNER LOOP AUTOPILOT
C
C          NORMAL ACCELERATION COMMAND SYSTEM
C
           NZCLIM = LIMIT(-2.0,4.0,NZC)
           NZZ    = NZ+CGARMN*QDOT/G
           ENZ    = NZCLIM-NZZ
           ENZKNZ = ENZ*KNZ
           QC     = QC  + ENZKNZ*DT
           NZSERI = QC-KPTCHR*Q
           NZSERO = REALPL(NZSERO,0.025,NZSERI,DT)
C
           ELE    = -PII*NZSERO
C
C
C          BANK ANGLE  COMMAND  SYSTEM
C
           EPHI   = PHIC-PHI
           PC     = KBANK*EPHI
           PCLIM  = LIMIT(-PLIM,PLIM,PC)
           EP     = PCLIM-P
           BSERI  = EP*KROLLR
           BSERO  = REALPL(BSERO,0.025,BSERI,DT)
C
           AIL    = -PII*BSERO
C
C
C          TURN COORDINATOR
C
           IF(PH4.EQ.1) GO TO 30
               NYC     = 0.0
   30      CONTINUE
           NYY    = NY+CGARML*RDOT/G
           ENY    = NYC-NYY
           RC     = RC+ENY*KNY*DT
           NYSERI = RC-KYAWRT*R
           NYSERO = REALPL(NYSERO,0.025,NYSERI,DT)
C
           RUD    = -PII*NYSERO
C       CONTROLS MIXER AND LIMITS
C
        LSTAB1 = ELE-AIL
        RSTAB1 = ELE+AIL
        LSTAB  = LIMIT(-15.0,15.0,LSTAB1)
```

```
      RSTAB   = LIMIT(-15.0,15.0,RSTAB1)
C
      STBLTR  = (RSTAB+LSTAB)/2.0
      AILRON  = (RSTAB-LSTAB)/2.0
      RUDDER  = LIMIT(-15.0,15.0,RUD)
C
C
      RETURN
      END
C
C                                                                   8-01-84
C ***************************************************************************
      FUNCTION LIMIT(LOW,HI,CONTRL)
C ***************************************************************************
C     MODELS THE PHYSICAL LIMITS IMPOSED UPON THE CONTROLS AND OTHER
C     PARAMETERS.
C     ************************************************************************
C
      IMPLICIT REAL(A-Z)
C     **************************************************************************
C
      IF (CONTRL.GT.LOW) GO TO  50
           LIMIT = LOW
           RETURN
   50 IF (CONTRL.LT.HI ) GO TO 100
           LIMIT = HI
           RETURN
  100 CONTINUE
           LIMIT = CONTRL
           RETURN
      END
C
C                                                                   8-04-84
C ***************************************************************************
      FUNCTION REALPL(PV,T,INPUT,DT)
C ***************************************************************************
C     MODELS A FIRST ORDER LAG (Y/X = 1/TS+1).
C     ************************************************************************
C
      IMPLICIT REAL(A-Z)
C
      PVDOT   = (1/T)*(INPUT-PV)
      REALPL  = PV + PVDOT*DT
      RETURN
      END
C                                                                   9-07-84
C ***************************************************************************
      SUBROUTINE AERO
```

```
C ********************************************************************
C     TABLE1,TABLE2,SUPRES
C   *******************************************************************
C     USES TABLE LOOKUP ROUTINES (TABLE1,2) TC CONSTRUCT THE AERO-
C     DYNAMIC COEFFICIENTS FCR THE MISSILE GIVEN THE CONTROL
C     INPUTS, ANGLE OF ATTACK, SIDESLIP AND ANGULAR RATES P,Q,R,ADT,BDT.
C     THEN CALCULATES MOMENTS, FORCES, RATES, ANGLES AND POSITIONS OF
C     THE MISSILE IN SPACE. ALL VARIABLES RETURNEC ARE RETURNED WITHIN
C     THE COMMON BLOCKS. CUT-OF-RANGE WARNINGS ARE SUPPRESSED AFTER
C     20 CONSECUTIVE CALLS CUT OF RANGE.
C     *****************************************************************
C
      IMPLICIT REAL(A-Z)
      INTEGER PH1,PH2,PH3,PH4,I,J,K,N,NPTS,CPA,NOLT,PCOUNT,NFAZE
C
C
C     ******************************************
C     COMMON BLOCK /A/: MISCELLANEOUS CONSTANTS
C     ******************************************
C
      COMMON /A/ TIME   ,FINTIM,DT    ,OPDT  ,NOLT  ,NPTS ,CPA   ,PCOUNT,
     *           G      ,T     ,RHO   ,PI    ,PII   ,MASS ,WT    ,S     ,
     *           IXX    ,IYY   ,IZZ   ,IXZ   ,IA    ,IB   ,IC    ,CS    ,
     *           ID     ,IE    ,IF    ,IG    ,IH    ,II   ,IJ    ,IK    ,
     *           CHORD2,CHORC ,SPAN2 ,SPAN  ,NFAZE
C
C
C     ******************************************
C     COMMON BLOCK /B/: AERODYNAMIC COEFFICIENT TABLES
C     ******************************************
C
      COMMON /B/ LFT1(2,36)   ,LFT2(2,36)  ,DRG1(2,36)  ,DRG2(2,36)  ,
     *           DRG3(2,36)   ,DRG4(2,36)  ,PTCH1(2,36),PTCH2(2,36),
     *           SID1(6,10)   ,SID2(6,10)  ,SID3(6,10)  ,DREC1(6,10),
     *           DREC2(6,10)  ,DREC3(6,10),LTRL1(6,10),LTRL2(6,10),
     *           LTRL3(6,10)  ,CLADT       ,CDADT       ,CMADT       ,
     *           CLQ          ,CDQ         ,CMQ         ,CRBDT       ,
     *           CYR          ,CNBDT       ,CRR         ,CYP         ,
     *           CNR          ,CRP         ,CYBDT       ,CNP
C
C
C     ******************************************
C     COMMON BLOCK /C/: CCNTROL SYSTEM PARAMETERS
C     ******************************************
C
      COMMON /C/ KPTCHR       ,KROLLR      ,KYAWRT      ,KBANK       ,
     *           KGAMMA       ,KALT        ,CGARML      ,CGARMN      ,
     *           RRTLIM       ,PLIM        ,KNY         ,KNZ         ,
```

```
     *          AILRON       ,STBLTR      ,RUDCER      ,
     *          BSERO        ,NZSERO      ,NYSERO
C
C
C     ****************************************
C     COMMON BLOCK /D/: MISSILE FLIGHT DYNAMICS PARAMETERS
C     ****************************************
C
      COMMON /C/ ALFA        ,BETA        ,VT          ,HMDOT       ,
     *          U            ,V           ,W           ,
     *          PHI          ,GAMMA       ,THETA       ,SY          ,
     *          CD           ,CY          ,CL          ,CR          ,
     *          CM           ,CN          ,P           ,Q           ,
     *          R            ,ALFADT      ,BETADT      ,PDOT        ,
     *          QDOT         ,RDOT        ,NZ          ,ALTUDE      ,
     *          XM           ,YM          ,XMDCT       ,YMDCT
C
C
C     ***********************************************************
      SIDESL = PII*BETA
      AOA = FII*ALFA
C
      CLBAS  = TABLE1(LFT1,AOA)
      DCLSTE = TABLE1(LFT2,STBLTR)
      CDBAS  = TABLE1(DRG1,CLBAS)
      DCDSTE = TABLE1(DRG2,STBLTR)
      DCDSTA = TABLE1(DRG3,AILRON)
      DCDSTR = TABLE1(DRG4,RUDDER)
      CMBAS  = TABLE1(PTCH1,AOA)
      DCMSTE = TABLE1(PTCH2,STBLTR)
      CYBAS  = TABLE2(SID1,AOA,SIDESL)
      CRBAS  = TABLE2(SID2,AOA,SIDESL)
      CNBAS  = TABLE2(SID3,AOA,SIDESL)
      DCYSTR = TABLE2(DREC1,AOA,RUDDER)
      DCNSTR = TABLE2(DREC2,AOA,RUDDER)
      DCRSTR = TABLE2(DREC3,AOA,RUDDER)
      DCYSTA = TABLE2(LTRL1,AOA,AILRON)
      DCNSTA = TABLE2(LTRL2,AOA,AILRON)
      DCRSTA = TABLE2(LTRL3,AOA,AILRON)
C
C     AERODYNAMIC COEFFICIENTS
C
      CL  = CLBAS+DCLSTE+CHORD2*(CLADT*ALFADT+CLQ*Q)/VT
      CD  = CDBAS+DCDSTE+DCDSTA+DCDSTR+CHORD2*(CDADT*ALFADT+CDQ*Q)/VT
      CY  = CYBAS+DCYSTR+DCYSTA+SPAN2*(CYR*R+CYP*P+CYBDT*BETADT)/VT
      CM  = CMBAS+DCMSTE+CHORD2*(CMADT*ALFADT+CMQ*Q)/VT
      CN  = CNBAS+DCNSTR+DCNSTA+SPAN2*(CNBDT*BETADT+CNR*R+CNP*P)/VT
      CR  = CRBAS+DCRSTA+DCRSTR+SPAN2*(CRBDT*BETADT+CRR*R+CRP*P)/VT
```

```
C
C
C
C     AERODYNAMIC FORCES AND MOMENTS
C
      L  = CL*QS
      D  = CD*QS
      LA = SPAN*CR*QS
      MA = CHORD*CM*QS
      NA = SPAN*CN*QS
      X  = L*SIN(ALFA)-D*COS(ALFA)
      Y  = CY*QS
      Z  = -L*COS(ALFA)-D*SIN(ALFA)
C
C     NORMAL & LATERAL ACCELERATIONS
C
      NZ = -Z/(MASS*G)
      NY = Y/(MASS*G)
C
C *** COMMENCE INTEGRATION OF EQUATIONS OF MOTION
C
C     EULER ANGLES
C
      PHIDOT  = P+TAN(THETA)*(Q*SIN(PHI)+R*COS(PHI))
      THETAD  = Q*COS(PHI)-R*SIN(PHI)
      SYDOT   = (Q*SIN(PHI)+R*COS(PHI))/COS(THETA)
      PHI     = PHI + PHIDOT*DT
      THETA   = THETA + THETAD*DT
      SY      = SY + SYDOT*DT
C
C     LINEAR ACCELERATIONS AND VELOCITIES
C
      UDOT = -G*SIN(THETA)+V*R-W*Q+X/MASS+T/MASS
      VDOT = G*SIN(PHI)*COS(THETA)-U*R+W*P+Y/MASS
      WDOT = G*COS(PHI)*COS(THETA)+U*Q-V*P+Z/MASS
      U = U + UDOT*DT
      V = V + VDOT*DT
      W = W + WDOT*DT
      VT = SQRT(U**2+V**2+W**2)
      VTDOT = SQRT(UDOT**2+VDOT**2+WDOT**2)
C
C     ANGULAR ACCELERATIONS AND VELOCITIES
C
      PDOT = IB*LA+IC*NA-ID*P*Q-IE*R*Q
      QDOT = IF*MA-IG*P*R-IH*(P**2-R**2)
      RDOT = IC*LA+II*NA-IJ*P*Q-IK*R*Q
      P = P + PDOT*DT
      Q = Q + QDOT*DT
```

```
      R = R + RDOT*DT
C
C     ANGLES OF ATTACK, SIDESLIP, AND FLIGHT PATH
C
      ALFADT = (ATAN(W/U)-ALFA)/DT
      BETADT = (ASIN(V/VT)-BETA)/DT
      ALFA   = ATAN(W/U)
      BETA   = ASIN(V/VT)
      GAMMA  = ASIN(HMDOT/VT)
C
C     MISSILE POSITION IN INERTIAL SPACE
C
      XMDOT  = U*COS(SY)*COS(THETA)+V*(COS(SY)*SIN(THETA)*SIN(PHI)
     *         -SIN(SY)*COS(PHI))+W*(COS(SY)*SIN(THETA)*COS(PHI)+
     *         SIN(SY)*SIN(PHI))
      YMDOT  = U*SIN(SY)*COS(THETA)+V*(SIN(SY)*SIN(THETA)*SIN(PHI)
     *         +COS(SY)*COS(PHI))+W*(SIN(SY)*SIN(THETA)*COS(PHI)-
     *         COS(SY)*SIN(PHI))
      HMDOT  = U*SIN(THETA)-V*COS(THETA)*SIN(PHI)-W*COS(THETA)*COS(PHI)
      HORDOT= SQRT(XMDOT**2+YMDOT**2)
      XM  = XM  + XMDOT*DT
      YM  = YM  + YMDOT*DT
      ALTUDE = ALTUDE + HMDOT*DT
C
C
      RETURN
      END
C
C                                                                  9-07-84
C     ***********************************************************************
      FUNCTION   TABLE1 (ARRAY,IP)
C     ***********************************************************************
C     TABLE LOOKUP WITH LINEAR INTERPOLATION FOR A FUNCTION
C     OF ONE VARIABLE, Y=F(X). MAXIMUM NUMBER OF POINTS IS
C     LIMITED TO 30 BY THE DIMENSION STATEMENT. NOTE: THE
C     FIRST ARRAY ENTRY (ARRAY(1,1)) CANNOT BE 9999.0 AND ALL
C     UNUSED ARRAY ELEMENTS MUST BE EXACTLY 9999. THE INDEPENDENT
C     VARIABLE DATA IS STORED IN ROW 1, THE DEPENDENT IN ROW 2.
C     WARNINGS ARE SUPPRESSED AFTER 20 CONSECUTIVE CALLS (ABOUT 5 DT'S)
C     ***********************************************************************
C
      REAL ARRAY(2,30),IP,C,TABLE1
      INTEGER  I,J,K,N,SUPRES
      DATA J,K,N /3*0/
C
      K  = K+1
      IF(.NOT.IP.LT.ARRAY(1,1)) GO TO 10
          TABLE1=ARRAY(2,1)
```

```
C           IF(SUPRES(J,K,N).EQ.1)  WRITE(6,101) IP,TABLE1
            RETURN
C       END IF
C
C
   10 DO 90 I=1,30
            IF(.NOT.ARRAY(1,I).EQ.9999.0) GO TO 20
               TABLE1=ARRAY(2,I-1)
C              IF(SUPRES(J,K,N).EQ.1)  WRITE(6,102) IP,TABLE1
               RETURN
   20       IF(.NOT.IP.GT.ARRAY(1,I)) GO TO 30
               GO TO 90
   30       IF(.NOT.IP.EQ.ARRAY(1,I)) GO TO 40
               TABLE1 = ARRAY(2,I)
               RETURN
   40       IF(.NOT.IP.LT.ARRAY(1,I)) GO TO 90
               C= (IP-ARRAY(1,I-1))/(ARRAY(1,I)-ARRAY(1,I-1))
               TABLE1= ARRAY(2,I-1) +C*(ARRAY(2,I)-ARRAY(2,I-1))

               RETURN
C           END IF
   90 CONTINUE
C     WRITE(6,103)
      RETURN
C
C     FORMAT STATEMENTS FOR SUBROUTINE TABLE1****************************
C
 101  FORMAT('0','SUBROUTINE TABLE1: INPUT BELOW INDEPENDENT VARIABLE DA
     *TA.'/'             INPUT (IP)                  = ',F10.2,
     *    /'             USED LOWEST DATA AVAILABLE  = ',F10.2)
 102  FORMAT('0','SUBROUTINE TABLE1: INPUT ABOVE INDEPENDENT VARIABLE DA
     *TA.'/'             INPUT (IP)                  = ',F10.2,
     *    /'             USED HIGHEST DATA AVAILABLE = ',F10.2)
 103  FORMAT('0','SUBROUTINE TABLE1: ERROR. SUBROUTINE DID NOT END')
      END
C
C                                                              9-07-84
C     ******************************************************************
      FUNCTION TABLE2 (A,IP,IV)
C     ******************************************************************
C     TABLE LOOKUP WITH LINEAR INTERPOLATION FOR A FUNCTION
C     OF TWO VARIABLES, Z=F(X,Y). MAXIMUM NUMBER OF INPUT PARAMETERS IS
C     LIMITED TO 5, INDEPENDENT VARIABLE DATA POINTS TO 9 BY THE
C     DIMENSION OF THE ARRAY. A(1,1) IS NOT USED. THE PARAMETER VALUES
C     ARE STORED IN COL 1, INDEP. VAR. VALUES IN ROW 1. THE COEFFICIENT
C     DATA ARE STORED IN THE GRID CREATED BY ROW AND COL 1.
C     TABLE2 WARNINGS ARE SUPPRESSED AFTER 5 CONSECUTIVE OCCURRENCES.
C     ******************************************************************
```

```
C
      REAL A(6,10),IP,IV,CP,CV,LFT,RGT,TABLE2
      INTEGER  I,LI,UI,J,K,N,SUPRES
      DATA J,K,N /3*0/
C
C
      K   = K+1
      IF(.NOT.IP.LT.A(2,1)) GO TO 10
             CP = 0.
             LI = 2
             UI = 2
C            IF(SUPRES(J,K,N).EQ.1)  WRITE(6,1001) IP,A(2,1)
             GO TO 55
C
   10        DO 50 I=2,6
                IF(.NOT.A(I,1).EQ.9999.0) GO TO 20
C                  IF( SUPRES(J,K,N).EQ.1)  WRITE(6,1002) IP,A(I-1,1)
                   CP = 0.
                   LI = I-1
                   UI = I-1
                   GO TO 55
C
   20           IF(IP-A(I,1)) 30,40,50
C               IP < A(I,1)
   30              CP = (IP-A(I-1,1))/(A(I,1)-A(I-1,1))
                   LI = I-1
                   UI = I
                   GO TO 55
C               IP = A(I,1)
   40              CP = 0
                   LI = I
                   UI = I
                   GO TO 55
C               END IF
   50        CONTINUE
C     END IF
C
   55 IF(.NOT.IV.LT.A(1,2)) GO TO 60
C            IF(SUPRES(J,K,N).EQ.1)  WRITE(6,1003) IV,A(1,2)
             TABLE2=A(LI,2)+CP*(A(UI,2)-A(LI,2))
             RETURN
C
   60        DO 100 I=2,10
                IF(.NOT.A(1,I).EQ.9999.0) GO TO 70
C                  IF( SUPRES(J,K,N).EQ.1) WRITE(6,1004) IV,A(1,I-1)
                   TABLE2=A(LI,I-1)+CP*(A(UI,I-1)-A(LI,I-1))
                   RETURN
C
```

```
   70             IF(IV-A(1,I)) 80,90,100
C                 IV <  A(1,I)
   80                   CV = (IV-A(1,I-1))/(A(1,I)-A(1,I-1))
                        LFT= A(LI,I-1)+CP*(A(UI,I-1)-A(LI,I-1))
                        RGT= A(LI,I)+CP*(A(LI,I)-A(LI,I))
                        TABLE2= LFT+CV*(RGT-LFT)
                        RETURN
C                 IV =  A(1,I)
   90                   TABLE2=A(LI,I)+CP*(A(UI,I)-A(LI,I))
                        RETURN
C                 END IF
  100         CONTINUE
C      END IF
C
C      WRITE(6,1005)
       RETURN
C
C      FORMAT STATEMENTS FOR SUBROUTINE TABLE2**************************
C
 1001  FORMAT('0','SUBROUTINE TABLE2: INPUT PARAMETER BELOW DATA.'
     *        /'        INPUT PARAMETER              = ',F10.2,
     *        /'        USED LOWEST PARAMETER        = ',F10.2)
 1002  FORMAT('0','SUBROUTINE TABLE2: INPUT PARAMETER ABOVE DATA.'
     *        /'        INPUT PARAMETER              = ',F10.2,
     *        /'        USED HIGHEST PARAMETER       = ',F10.2)
 1003  FORMAT('0','SUBROUTINE TABLE2: INPUT INDEP. VAR. BELOW DATA.'
     *        /'        INPUT INDEP. VAR.            = ',F10.2,
     *        /'        USED LOWEST INDEP. VAR.      = ',F10.2)
 1004  FORMAT('0','SUBROUTINE TABLE2: INPUT INDEP. VAR. ABOVE DATA.'
     *        /'        INPUT INDEP. VAR.            = ',F10.2,
     *        /'        USED HIGHEST INDEP. VAR.     = ',F10.2)
 1005  FORMAT('0','SUBROUTINE TABLE2: ERROR. SUBROUTINE DID NOT END')
       END
C
C                                                              9-05-84
C **********************************************************************
       FUNCTION SUPRES(J,K,N)
C **********************************************************************
C      DETERMINES TO SUPPRESS WARNINGS FROM TABLE1 OR TABLE2 AFTER THEY
C      HAVE BEEN CALLED ABOUT 20 TIMES IN A ROW. (ABOUT 5 DT INTERVALS.)
C      *****************************************************************
       INTEGER J,K,N, SUPRES
C
       IF(K-J.EQ.1)GO TO 10
              N  = 0
              K  = 0
              J  = 0
              GO TO 15
```

```
   10 CONTINUE
         N  = N+1
         J  = K
   15 CONTINUE
C
      IF(N.EQ.20)WRITE(6,105)
  105 FORMAT('0','TABLE LOOKUP WARNINGS SUPPRESSED')
C
      IF(N.GE.20) SUPRES = 1
      IF(N.LT.20) SUPRES = 0
      RETURN
      END
C
C                                                                  9-07-84
C ****************************************************************************
      SUBROUTINE TGTNAV
C ****************************************************************************
C     RNG, SCVV
C    *************************************************************************
C     NAVIGATES THE TARGET AND COMPUTES RELATIVE RANGE, RANGE RATES.
C     INCORPORATES ECM AND GLINT MODELS TO GIVE APPARENT TARGET
C     POSITIONS. ALSO CALCULATES LINE OF SIGHT ANGLES AND RATES.
C     ************************************************************************
C
      IMPLICIT REAL(A-Z)
      INTEGER PH1,PH2,PH3,PH4,I,J,K,N,NPTS,CPA,NOUT,PCOUNT,NFAZE
C
C
C     ****************************************************
C     COMMON BLOCK /A/: MISCELLANEOUS CONSTANTS
C     ****************************************************
C
      COMMON /A/ TIME   ,FINTIM,DT    ,CPDT ,NOUT ,NPTS ,CPA   ,PCOUNT,
     *           G      ,T     ,RHO   ,PI   ,PII  ,MASS ,WT    ,S     ,
     *           IXX    ,IYY   ,IZZ   ,IXZ  ,IA   ,IB   ,IC    ,GS    ,
     *           ID     ,IE    ,IF    ,IG   ,IH   ,II   ,IJ    ,IK    ,
     *           CHORD2,CHORD  ,SPAN2 ,SPAN ,NFAZE
C
C
C     ****************************************************
C     COMMON BLOCK /D/: MISSILE FLIGHT DYNAMICS PARAMETERS
C     ****************************************************
C
      COMMON /D/ ALFA          ,BETA          ,VT           ,HMDOT        ,
     *           U             ,V             ,W            ,
     *           PHI           ,GAMMA         ,THETA        ,SY           ,
     *           CD            ,CY            ,CL           ,CR           ,
     *           CM            ,CN            ,P            ,Q            ,
```

```
     *             R               ,ALFADT        ,BETADT         ,PDOT          ,
     *             QDOT            ,RDOT          ,NZ             ,ALTUDE        ,
     *             XM              ,YM            ,XMDOT          ,YMDOT
C
C
C     ***********************************************
C     COMMON BLOCK /E/: INITIAL CONDITIONS
C     ***********************************************
C
      COMMON /E/ XM1            ,YM1           ,ALTUD1         ,U1            ,
     *           PITCH1         ,BANK1         ,HEDNG1         ,SIDES1        ,
     *           AOA1           ,PTCHR1        ,ROLLR1         ,YAWR1         ,
     *           XT1            ,YT1           ,HT1            ,TSPEED
C
C
C     ***********************************************
C     COMMON BLOCK /F/: GUIDANCE PARAMETERS
C     ***********************************************
C
      COMMON /F/ PH1            ,PH2           ,PH3            ,PH4           ,
     *           OFFSET         ,ALTATT        ,SGDZPU         ,MISDST        ,
     *           LAMDAZ         ,LAMDEL        ,KNFAZ          ,KNFEL         ,
     *           NZC            , PHIC         ,GAMMAC         ,PCLIM         ,
     *           PC             ,QC            ,RC             ,RANGE         ,
     *           SIGAZ          ,SIGEL         ,SIGDAF         ,SIGDEF        ,
     *           SYT            ,THETAT        ,XT             ,YT            ,
     *           HT             ,NYC           ,POPRNG
C
C
C     ***********************************************
C     COMMON BLOCK /H/: ECM/GLINT PARAMETERS
C     ***********************************************
C
      COMMON /H/ FREQ           ,SHIFTY        ,SHIFTH         ,BRNTHR        ,
     *           XECM           ,YECM          ,HECM           ,XGLNT         ,
     *           YGLNT          ,HGLNT         ,XTECM          ,YTECM         ,
     *           HTECM
C
C EXECUTABLE STATEMENTS:
C*************************************************************************
C
C *** TARGET MOTION
C
      XT = XT1
      YT = YT1+TSPEED*TIME
      HT = HT1
C
C     RELATIVE RANGE TO TARGET
```

```
C
      XR  = XT-XM
      YR  = YT-YM
      HR  = HT-ALTUDE
C
C *** RANGE & MISS DISTANCE
C
      RNGE    = SQRT(XR**2+YR**2+HR**2)
      IF(RNGE.GT.2000.)GO TO 25
           IF(RNGE.LT.RANGE)GO TO 25
                CPA   = 1
                MISDST     = RANGE
   25 CONTINUE
      RANGE      = RNGE
C
C
C *** GLINT MODEL (SUPPRESSED AT A RANGE OF 100 FT)
C ************* TESTPATCH TO SUPPRESS GLINT (KTEST = 1)
      KTEST = 1
      IF(KTEST.EQ.1) GO TO 50
C ************* ENDTEST
      CALL RNG(RAND)
C
      IF(PCGLNT.NE.1) GO TO 100
           IF(RANGE.LT.100.0) GO TO 50
                XGLNT = 20*RAND
                YGLNT = 50*RAND
                HGLNT = 20*RAND
                GO TO 100
   50      CONTINUE
                XGLNT = 0.0
                YGLNT = 0.0
                HGLNT = 0.0
  100 CONTINUE
C
C
C *** ECM BLINKING MODEL (SUPPRESSED AT BURN-THROUGH RANGE)
C
C   * SELECT THE PHASE APPLIED TO THE ECM SIGNAL
C
      GO TO(101,102,103,104),NFAZE
  101      PHASE = 0.0
           GO TO 105
  102      PHASE = PI*0.5
           GO TO 105
  103      PHASE = PI
           GO TO 105
  104      PHASE = PI*1.5
```

```
  105 CONTINLE
C
      POPRNG = PHASE*PII
      IF(RANGE.LT.BRNTHR) GO TO 350
            XECMW = SIN(2*PI*FREQ*TIME+PHASE)
            XECM  = SQWV(XECMW,SHIFTX)
C
            YECMW = SIN(2*PI*FREQ*TIME+PHASE)
            YECM  = SQWV(YECMW,SHIFTY)
C
            HECMW = SIN(2*PI*FREQ*TIME+PHASE)
            HECM  = SQWV(HECMW,SHIFTH)
            GC TO 400
  35C CONTINLE
            XECM  = 0.0
            YECM  = 0.0
            HECM  = 0.0
  400 CONTINLE
C
      XTECM  = XT+XECM+XGLNT
      YTECM  = YT+YECM+YGLNT
      HTECM  = HT+HECM+HGLNT
C
C
C *** RELATIVE RANGE AND RANGE RATE TO RADAR TARGET
C
      XRECM   = XTECM-XM
      YRECM   = YTECM-YM
      HRECM   = HTECM-ALTUDE
      RNGECM  = SQRT(XRECM**2+YRECM**2)
      RGECMT  = SQRT(XRECM**2+YRECM**2+HRECM**2)
C
      XDCTR   = -XMDOT
      YDCTR   = TSPEED-YMDOT
      HDCTR   = -HMDOT
      HORDTR  = SQRT(XDOTR**2+YDOTR**2)
C
C
C *** SEEKER LCS AND LCS RATE CALCULATIONS
C
      SYT     = ATAN2(YRECM,XRECM)
      TRAKAZ  = ATAN2(YMDCT,XMDOT)
      SIGAZ   = SYT-TRAKAZ
C
      VTANAZ  = -XDOTR*SIN(SYT)+YDOTR*COS(SYT)
      SIGDAZ  = VTANAZ/RNGECM
      SIGDAF  = REALPL(SIGDAF,KNFAZ,SIGDAZ,DT)
C
```

```
      THETAT = ATAN2(HRECM,RNGECM)
      HORDOT = SQRT(XMDOT**2+YMDOT**2)
      TRAKEL = ATAN2(HMDOT,HORDOT)
      SIGEL  = THETAT-TRAKEL
C
      VTANEL = HDOTR*COS(THETAT)+HORDTR*SIN(THETAT)
      SIGDEL = VTANEL/RGECMT
      SIGDEF = REALPL(SIGDEF,KNFEL,SIGDEL,DT)
C
C
      RETURN
      END
C
C                                                             8-01-84
C ************************************************************************
      SUBROUTINE RNG(RAND)
C ************************************************************************
C     GENERATES A RANDOM NUMBER BETWEEN -1.0 & 1.0
C     *********************************************************************
C
      IMPLICIT REAL(A-Z)
      DATA SEED/4.0/
C
      RAND = (SEED + 3.14159)**5.04
      RAND = (RAND - IFIX(RAND)-0.5)*2.0
      SEED = RAND
C
      RETURN
      END
C
C                                                             9-07-84
C ************************************************************************
      FUNCTION SQWV(WAVE,AMPL)
C ************************************************************************
C     GENERATES A SQUAREWAVE FROM A SINWAVE
C     *********************************************************************
C
      IMPLICIT REAL(A-Z)
C
      IF (WAVE.GT.0.0) SQWV=AMPL
      IF (WAVE.LT.0.0) SQWV=-AMPL
      IF (WAVE.EQ.0.0) SQWV= 0.0
C
      RETURN
      END
C
C                                                             9-07-84
C ************************************************************************
```

```
      SUBROUTINE PREPAR
C ************************************************************************
C     DESIGNATES UP TO 20 PARAMETERS TO BE STORED FOR OUTPUT AND
C     ASSIGNS THEM TO THE NEXT ROW OF THE PTS ARRAY. EACH PARAM. IS
C     STORED IN A COLUMN OF THE ARRAY FROM ROW 3 UNTIL THE END OF THE
C     ARRAY IS REACHED OR CPA OCCURS. ROWS 1 & 2 CONTAIN MINIMUM AND
C     MAXIMUM VALUES OF EACH VARIABLE RESPECTIVELY. COL. 1 CONTAINS
C     THE VALUES OF TIME FOR EACH POINT. NPTS IS COMMON TO BLOCK A
C     AND INDICATES THE NUMBER OF POINTS STORED.
C     ********************************************************************
C
      IMPLICIT REAL(A-Z)
      INTEGER PH1,PH2,PH3,PH4,I,J,K,N,NPTS,CPA,NOUT,PCOUNT,NFAZE
      DIMENSION KEEP(20)
C
      COMMON /A/ TIME  ,FINTIM,DT    ,CPDT  ,NCUT  ,NPTS  ,CPA   ,PCOUNT,
     *           G     ,T     ,RHO   ,PI    ,PII   ,MASS  ,WT    ,S     ,
     *           IXX   ,IYY   ,IZZ   ,IXZ   ,IA    ,IB    ,IC    ,QS    ,
     *           ID    ,IE    ,IF    ,IG    ,IH    ,II    ,IJ    ,IK    ,
     *           CHORD2,CHORD ,SPAN2 ,SPAN  ,NFAZE
C
C
      COMMON /C/ KPTCHR         ,KROLLR         ,KYAWRT         ,KBANK          ,
     *           KGAMMA         ,KALT           ,CGARML         ,CGARMN         ,
     *           RRTLIM         ,PLIM           ,KNY            ,KNZ            ,
     *           AILRON         ,STBLTR         ,RUDDER         ,
     *           BSERO          ,NZSERO         ,NYSERO
C
C
      COMMON /D/ ALFA           ,BETA           ,VT             ,HMDOT          ,
     *           U              ,V              ,W              ,
     *           PHI            ,GAMMA          ,THETA          ,SY             ,
     *           CD             ,CY             ,CL             ,CR             ,
     *           CM             ,CN             ,P              ,Q              ,
     *           R              ,ALFADT         ,BETADT         ,PDOT           ,
     *           QDOT           ,RDOT           ,NZ             ,ALTUDE         ,
     *           XM             ,YM             ,XMDOT          ,YMDOT
C
      COMMON /E/ XM1            ,YM1            ,ALTUD1         ,U1             ,
     *           PITCH1         ,BANK1          ,HEDNG1         ,SIDES1         ,
     *           AOA1           ,PTCHR1         ,ROLLR1         ,YAWR1          ,
     *           XT1            ,YT1            ,HT1            ,TSPEED
C
      COMMON /F/ PH1            ,PH2            ,PH3            ,PH4            ,
     *           OFFSET         ,ALTATT         ,SGDZPU         ,MISDST         ,
     *           LAMDAZ         ,LAMDEL         ,KNFAZ          ,KNFEL          ,
     *           NZC            , PHIC          ,GAMMAC         ,PCLIM          ,
     *           PC             ,QC             ,RC             ,RANGE          ,
```

```
     *              SIGAZ        ,SIGEL       ,SIGDAF      ,SIGDEF      ,
     *              SYT          ,THETAT      ,XT          ,YT          ,
     *              HT           ,NYC         ,POPRNG
C
      COMMON /G/ AOA          ,SIDESL      ,BANK        ,FLTPHC      ,
     *              BANKC        ,PITCH       ,ROLLRT      ,ROLRTC      ,
     *              PTCHRT       ,YAWRT       ,HEADNG      ,FLTPTH      ,
     *              HEADT        ,ELEVT       ,DSIGAZ      ,DSIGEL      ,
     *              DSGDAZ       ,DSGDEL      ,ERFBK       ,ERFRR       ,
     *              ERFAZ        ,ERFEL
C
      COMMON /H/ FREQ         ,SHIFTY      ,SHIFTH      ,BRNTHR      ,
     *              XECM         ,YECM        ,HECM        ,XGLNT       ,
     *              YGLNT        ,HGLNT       ,XTECM       ,YTECM       ,
     *              HTECM
C
C
      COMMON /I/ PTS(300,20),PLTN(6,7),XN(6,7),YN(6,7),TITLE(6),
     *              LEG(4,20)
C
C EXECUTABLE STMTS ***************************************************
C
C     RADIAN TO DEGREE CONVERSIONS FOR OUTPUT
C
      AOA    = ALFA*PII
      SIDESL = BETA*PII
      BANK   = PHI*PII
      FLTPHC = GAMMAC*PII
      BANKC  = PHIC*PII
      PITCH  = THETA*PII
      ROLLRT = P*PII
      ROLRTC = PCLIM*PII
      PTCHRT = Q*PII
      YAWRT  = R*PII
      HEADNG = SY*PII
      FLTPTH = GAMMA*PII
      HEADT  = SYT*PII
      ELEVT  = THETAT*PII
      DSIGAZ = SIGAZ*PII
      DSIGEL = SIGEL*PII
      DSGDAZ = SIGDAF*PII
      DSGDEL = SIGDEF*PII
C
C *** CREATE THE MISSION PHASE MARKER (MARK)
C
      MARK = 0.0
      IF(PH1.EQ.1)MARK = 1.0
      IF(PH2.EQ.1)MARK = 2.0
```

```
      IF(PH3.EQ.1)MARK =  3.0
      IF(PH4.EQ.1)MARK =  4.0
C
      NPTS = NPTS+1
      K    = NPTS+2
C
C *** COMPUTE THE ERROR FUNCTIONS
C
      IF(MARK.EQ.4) GO TC 50
             ERRBK      = 0.0
             ERRRR      = 0.0
             ERRAZ      = 0.0
             ERREL      = 0.0
             GC TC 100
   50 CONTINUE
             ERRBK      = ERRBK + ABS(BANKC-BANK)    *DT
             ERRRR      = ERRRR + ABS(RCLRTC-ROLLRT)*DT
             ERRAZ      = ERRAZ + ABS(DSGDAZ)        *DT
             ERREL      = ERREL + ABS(DSGDEL)        *DT
  10C CONTINUE
C
      ERFBK      = ERRBK/TIME
      ERFRR      = ERRRR/TIME
      ERFAZ      = ERRAZ/TIME
      ERFEL      = ERREL/TIME
C
C *** SELECT THE VARIABLES TC BE STORED
C
      KEEP(1)  = TIME
C
C     GRAPH 1
      KEEP(2)  = NZC
      KEEP(3)  = NZ
C
C     GRAPH 2
      KEEP(4)  = BANKC
      KEEP(5)  = BANK
C
C     GRAPH 3
      KEEP(6)  = ROLRTC
      KEEP(7)  = ROLLRT
C
C     GRAPH 4
      KEEP(8)  = YECM
      KEEP(9)  = YGLNT
C
C     GRAPH 5
      KEEP(1C) = AILRON
```

```
      KEEP(11) = STBLTR
      KEEP(12) = RUDDER
C
C     GRAPH 6
      KEEP(13) = ALTUDE
C
C     GRAPH 7
      KEEP(14) = XM
      KEEP(15) = YM
      KEEP(16) = XT
      KEEP(17) = YT
C
C     SPARES
      KEEP(18) = RANGE
      KEEP(19) = MARK
      KEEP(20) = NYC
C
C *** STORE MINIMUM AND MAXIMUM VALUES OF EACH VARIABLE
C
      DO 20 I=1,20
         IF (NPTS.GT.1) GO TO 10
            PTS(1,I)  = KEEP(I)
            PTS(2,I)  = KEEP(I)
   10    CONTINUE
         PTS(1,I)  = AMIN1(PTS(1,I),KEEP(I))
         PTS(2,I)  = AMAX1(PTS(2,I),KEEP(I))
   20 CONTINUE
C
C *** STORE VALUES OF EACH VARIABLE WITH THE TIME
C
      DO 30 I=1 ,20
         PTS(K,I)  = KEEP(I)
   30 CONTINUE
C
C *** CHECK FOR ARRAY OVERFLOW AND TERMINATE AT 255 POINTS
C
      IF(NPTS.GE.295) CPA = 3.0
C
C
      RETURN
      END
C
C                                                                   9-07-84
C ***********************************************************************
      SUBROUTINE OUTPUT(NPTS,CPA)
C ***********************************************************************
C     HEADER, PLOT1, PLOT2, PLOT21, PLOT3
C   *********************************************************************
```

```
C       RECEIVES THE DATA FROM THE PROGRAM IN THE PTS ARRAY. PRINTS THE
C       PRIME OUTPUT AND DATA RANGES TO THE SCREEN AND TABULAR OUTPUT TO
C       FILE 9 (TCMC DATA). THEN IT PROCESSES THE DATA FOR PLOTTING USING
C       DISSPLA. THE BASIC FORMAT OF THE SEVEN GRAPHS CALLED IN THIS S/R
C       IS FIXED BUT THE TITLES AND THE VARIABLES CAN BE EASILY CHANGED BY
C       CHANGING THE PARAMETERS IN THE DATA STATEMENTS IN THIS S/R. THE
C       TITLE GIVEN HERE WILL BE PRINTED FOR ALL PLOTS. @
C       ********************************************************************
        IMPLICIT REAL(A-Z)
        INTEGER   KFILE,NPTS,I,J,K,L,M,N,NN,CPA,
     *            NDV(5,7),DV(4),LEG(4,20),PLTN(6,7),
     *            XN(6,7),YN(6,7),TITLE(8,4),MESS1(2),MESS2(2)
C
        DIMENSION YP(10),XP(10)
C
C       ********************************************************************
C
        COMMON /F/ PH1         ,PH2        ,PH3        ,PH4        ,
     *             OFFSET      ,ALTATT     ,SGDZPU     ,MISDST     ,
     *             LAMDAZ      ,LAMDEL     ,KNFAZ      ,KNFEL      ,
     *             NZC         , PHIC      ,GAMMAC     ,PCLIM      ,
     *             PC          ,QC         ,RC         ,RANGE      ,
     *             SIGAZ       ,SIGEL      ,SIGDAF     ,SIGDEF     ,
     *             SYT         ,THETAT     ,XT         ,YT         ,
     *             HT          ,NYC        ,POPRNG
C
        COMMON /G/ AOA         ,SIDESL     ,BANK       ,FLTPHC     ,
     *             BANKC       ,PITCH      ,ROLLRT     ,ROLRTC     ,
     *             PTCHRT      ,YAWRT      ,HEADNG     ,FLTPTH     ,
     *             HEADT       ,ELEVT      ,DSIGAZ     ,DSIGEL     ,
     *             DSGDAZ      ,DSGDEL     ,ERFBK      ,ERFRR      ,
     *             ERFAZ       ,ERFEL
C
        COMMON /H/ FREQ        ,SHIFTY     ,SHIFTH     ,BRNTHR     ,
     *             XECM        ,YECM       ,HECM       ,XGLNT      ,
     *             YGLNT       ,HGLNT      ,XTECM      ,YTECM      ,
     *             HTECM
C
        COMMON /I/ PTS(300,20)
C
C
C  ************************************************************************
C  ************ INITIALIZE THE GRAPHICS CONTROL ARRAY ***************
C
C          EACH ROW IN THE DATA STATEMENT (COLUMN OF THE ARRAY)
C          CORRESPONDS TO A SINGLE GRAPH. THE FIRST ELEMENT IS
C          A FLAG (1 TO PLOT, 0 TO PASS OVER). THE NEXT 4 ELEMENTS
```

```
C          ARE THE NUMBERS (BETWEEN 1 AND 20) OF THE DEPENDENT
C          VARIABLES TO BE PLOTTED AGAINST TIME.
C
C
      DATA    NCV      / 0   ,2   ,3   ,20  ,0   ,
     *                   0   ,4   ,5   ,0   ,0   ,
     *                   0   ,6   ,7   ,0   ,0   ,
     *                   0   ,8   ,9   ,0   ,0   ,
     *                   0   ,10  ,11  ,12  ,0   ,
     *                   0   ,13  ,0   ,0   ,0   ,
     *                   0   ,0   ,0   ,0   ,0   /
C
C *** LOAD THE MESSAGES AND VARIABLES TO APPEAR IN THE UPPER
C     LEFT HAND CORNER OF EACH GRAPH.
C
      DATA    MESS1   /'FREQ  = '/
      DATA    MESS2   /'PHASE = '/
C
C EXECUTABLE STMTS:
C
      VAR1  = FREQ
      VAR2  = PUPRNG
C
C *****************************************************************
C *******  READ TITLE CAPTIONS FOR GRAPHS AND PRINTOUT *************
C                 FROM FILE NO.2: LABELS DATA
C
      IF(FLAG.EQ.1.0) GO TO 18
C
C *** READ IN OVERALL TITLE LINES (4 LINES OF 32 CHARACTERS)
C
      READ(2,5)((TITLE(J,I),J=1,8),I=1,4)
    5 FORMAT(20X,8A4)
C
C *** READ IN EACH GRAPH TITLE & ITS AXIS LABELS (24 CHARACTERS EACH)
C
      DO 10 J=1,7
          READ(2,12)(PLTN(I,J),I=1,6)
          READ(2,12)(XN(I,J),I=1,6)
          READ(2,12)(YN(I,J),I=1,6)
   10 CONTINUE
   12 FORMAT(20X,6A4)
C
C *** READ IN THE LEGEND LABEL FOR EACH OF THE 20 STORED VARIABLES
C     (16 CHARACTERS EACH)
C
      READ(2,15)((LEG(I,J),I=1,4),J=1,20)
   15 FORMAT(20X,4A4)
```

```
C
      FLAG = 1.0
   18 CONTINUE
C
C
C ******************************************************************************
C ***************** WRITE PRIMARY DATA OUTPUT *************************
C        TO FILE 6 (TERMINAL) AND THEN FILE 9 (TCMC DATA)
C
      DO 100 K=1,2
         IF(K.EQ.1)KFILE=6
         IF(K.EQ.2)KFILE=9
C
C ***    TITLES
C
         WRITE(KFILE,20)((TITLE(I,J),I=1,8),J=1,4)
   20    FORMAT('1',4(20X,8A4/)//)
C
C *** INDICATE HOW THE SIMULATION TERMINATED
C
         GO TO(30,40,50),CPA
C
   30       WRITE(KFILE,35)
   35       FORMAT(1X, 'SIMULATION TERMINATED DUE TO CPA')
            GO TO  60
C
   40       WRITE(KFILE, 45)
   45       FORMAT(1X, 'SIMULATION TERMINATED DUE TO FINTIME')
            GO TO  60
C
   50       WRITE(KFILE, 55)
   55       FORMAT(1X, 'SIMULATION TERMINATED DUE TO FULL ARRAY')
C
   60    CONTINUE
C
C ***    VALUE OF THE ITERATED PARAMETER
C
         WRITE(KFILE,65) FREQ
   65    FORMAT(1X,'*** BLINKER FREQUENCY=   ',F8.2)
C
         WRITE(KFILE,67) PCPRNG
   67    FORMAT(1X,'*** BLINKER PHASE    =   ',F6.0//)
C
C ***    LIST THE PRIMARY DATA OUTPUTS
C
         WRITE(KFILE,75) MISDST,ERFBK,ERFRR,ERFAZ,ERFEL
   75    FORMAT(1X,'      MISS     * ===================== ERROR FUNC
     *TIONS =====================*'/'    DISTANCE   *     BANK       *
```

```
     *   ROLLRATE   *     AZIMUTH     *    ELEVATION    *'//
     *   5(3X,F10.5,2X,'*')//////)
C
C ***        LIST THE VARIABLE RANGES
C
             WRITE(KFILE,80)
  80         FORMAT(18X,'******* RANGES FOR ALL SAVED VARIABLES *******'
     *          ///30X, '       MINIMUM            MAXIMUM    '//)
             WRITE(KFILE,90)(((LEG(I,J),I=1,4), PTS(1,J),PTS(2,J)) ,J=1,20)
  90         FORMAT(11X, 4A4, 4X, F12.6, 3X, F12.6)
C
 100 CONTINUE
C
C
C *****************************************************************
C ******************* TABULAR DATA OUTPUT **************************
C
      DO 200  I=1,4
             J=(I-1)*4+2
             K=J+3
             WRITE(9,20)((TITLE(L,M),L=1,8),M= 1,4)
             WRITE(9,65) FREQ
             WRITE(9,125) I
 125         FORMAT(50X, 'DATA SET NUMBER  ',I1,'  OF 4'//)
             WRITE(9,135)(LEG(L,1),L=1,4),((LEG(L,M),L=1,4),M=J,K)
 135         FORMAT(2X, 20A4///)
C
             NN=NPTS+2
             DO 150 N=3,NN
C                 START NEW PAGE EVERY 65 LINES
                  L = MOD(N,65)
                  IF(L.NE.0) GO TO 140
                       WRITE(9,20)((TITLE(L,M),L=1,8),M=1,4)
                       WRITE(9,65) FREQ
                       WRITE(9,125) I
                       WRITE(9,135)(LEG(L,1),L=1,4),
     *                             ((LEG(L,M),L=1,4),M=J,K)
 140              CONTINUE
                  WRITE(9,145) PTS(N,1),(PTS(N,L),L=J,K)
 145              FORMAT(1X,5('*',F12.6,3X))
 150         CONTINUE
 200 CONTINUE
C
C
C *****************************************************************
C ******* PRODUCE GRAPHIC OUTPUT USING DISSPLA SUBROUTINES **********
C
C
```

```
C
C     **************
C     GRAPH NC.S 1-6
C     **************
C
      DO 300 J = 1,6
C           IF((J.EQ.4).AND.(FREQ.EQ.0.0))GO TC 28C
            IF(NDV(1,J).EQ.0)GO TC 280
                  DC 250 I = 2,5
                        DV(I-1)    = NDV(I,J)
  25C             CONTINUE
C
                  CALL  PLOT1(MESS1,MESS2,VAR1,VAR2)
                  CALL  HEADER(J,TITLE,PLTN,XN,YN)
                  CALL  PLOT2(PTS,LEG,DV,1,NPTS)
C
  28C       CCNTINUE
  300 CONTINUE
C
C
C     ********
C     GRAPH NC.7 *** 3-DIMENSIONAL GEO PLCT
C     ********
C
      IF(NDV(1,7).EQ.0) GC TC 900
C
      CALL  PLCT1(MESS1,MESS2,VAR1,VAR2)
      CALL  PLCT3(NPTS,PTS,TITLE)
C
C ***********
C
 900  CONTINUE
C
      RETURN
      ENC
C
C                                                                    9-07-84
C ************************************************************************
      SUBROUTINE HEADER(KP,TITLE,PLTN,XN,YN)
C ************************************************************************
C     LOADS THE 1D ARRAYS USED TO PASS LABELS TO DISSPLA FROM THE
C     2D ARRAYS PACKED WITH THE TITLE OF EACH OF THE SEVEN GRAPHS AND
C     THE AXIS LABELS. CALLS THE DISSPLA HEADING AND AXIS LABEL
C     ********************************************************************
C
      INTEGER KF,PLTN(6,7),XN(6,7),YN(6,7),XNM(6),YNM(6),HD(6),
     *        I, TITLE(8,4)
C
```

```
      DO 50 J=1,3
         DC 30 I=1,8
            HC(I)       = TITLE(I,J)
   30    CCNTINUE
         CALL HEADIN(HC   ,32    ,   1.1   ,4)
   5C CONTINUE
      DO 60 I=1,6
         HC(I)    = PLTN(I,KP)
         XNM(I)    = XN(I,KP)
         YNM(I)    = YN(I,KP)
   6C CONTINUE
      CALL HEADIN(HD    ,24    ,   1.0    ,4)
C
      CALL XNAME( XNM   ,24)
      CALL YNAME( YNM   ,24)
C
      RETURN
      END
C ****************************************************************
C     FILE: FLCT1
C ****************************************************************
C     CONTAINS ALL S/R'S THAT INTERFACE WITH DISSPLA EXCEPT HEADER
C     ************************************************************
C
C                                                          9-10-84
C ****************************************************************
      SUBROUTINE PLOT1(MESS1,MESS2,VAR1,VAR2)
C ****************************************************************
C     INITIALIZES DISSPLA FOR A NEW PAGE AND GRAPH
C     ************************************************************
C
      IMPLICIT REAL(A-H,C-Z),INTEGER(I-N)
      DIMENSICN MESS1(2),MESS2(2)
C
      CALL NCCHEK
      CALL GRACE(0.)
      CALL BLOWUP(0.647)
      CALL PAGE(11.,8.5)
      CALL HWROT('AUTO')
      CALL HWSCAL('SCREEN')
C     CALL NCERDR
      CALL PHYSOR(1.,.75)
      CALL AREA2C(9.,6.5)
C     CALL SWISSM
C
C *** PUT THE MESSAGES INTO THE GRAPHS
C
      CALL MESSAG(MESS1,8,0.2,6.0)
```

```
      CALL REALNO(VAR1 ,2,'ABUT','ABUT')
      CALL MESSAG(MESS2,8,0.2,5.6)
      CALL REALNO(VAR2 ,0,'ABUT','ABUT')
      CALL BLREC(0.1,5.5,1.8,0.8,0.01)
C
      RETURN
      END
C
C                                                                   8-26-84
C ******************************************************************************
      SUBROUTINE PLOT2(PTS,LEG,DV,IV,NPTS)
C ******************************************************************************
C     LOADS THE LEGEND ARRAY WITH CURVE LABELS; GETS THE POINTS FOR
C     EACH CURVE FROM THE PTS ARRAY; PLOTS EACH CURVE. IV,DV ARE IN-
C     DEPENDENT, DEPENDENT VARIABLE INDEXES. THEY GIVE THE COLUMN IN
C     THE PTS ARRAY WHERE THEIR VALUES ARE FOUND. LEG IS THE PACKED
C     ARRAY CONTAINING LEGEND LABELS FOR EACH VARIABLE. DV IS A 4
C     ELEMENT ARRAY CONTAINING THE INDEXES FOR UP TO 4 DEP VAR'S.
C     **************************************************************************
C
      IMPLICIT  REAL(A-H,O-Z),INTEGER(I-N)
      INTEGER   DV(4),IPACK(100),LEG(4,20),LBL(5)
      DIMENSION PTS(300,20), XP(300), YP(300)
C
      DATA MONEY /'$    '/
C
C
C *** FIRST FIND OUT HOW MANY CURVES THERE ARE
C
      I=1
    5 IF (DV(I).EQ.0)GO TO 10
         MCRV = I
         IF (I.EQ.4)GO TO 10
         I    = I+1
         GO TO 5
   10 CONTINUE
C
C *** NEXT PACK THE LEGEND ARRAY AND RANGE THE Y-AXIS
C
      DO 30 I=1,MCRV
         K    = DV(I)
         IF(I.GT.1) GO TO 15
            YMIN = PTS(1,K)
            YMAX = PTS(2,K)
            GO TO 20
   15    CONTINUE
            YMIN = AMIN1(YMIN,PTS(1,K))
            YMAX = AMAX1(YMAX,PTS(2,K))
```

```
   20       CCNTINLE
C
            DC 25 J=1,4
                LBL(J)      = LEG(J,K)
   25       CCNTINUE
            LBL(5) = MONEY
            CALL LINES(LBL,IPACK,I)
   30   CONTINLE
C
C  *** RANGE THE INDEPENDENT VARIABLE(S)
C
        XMIN = PTS(1,IV)
        XMAX = PTS(2,IV)
C
C  *** NOW PLCT THE CURVES
C
        CALL GRAF(XMIN,'SCALE',XMAX,YMIN,'SCALE',YMAX)
        DO 90 I=1,MCRV
            DC 80 J=1,NPTS
                XP(J)       = PTS(J+2,IV)
                YP(J)       = PTS(J+2,DV(I))
   80       CCNTINUE
            CALL CURVE(XP,YP,NPTS,1)
   90   CONTINLE
C
C  PLCT THE GRID & LEGEND AND FINISH THE GRAPH
C
        CALL PLCT21(IPACK,MCRV)
C
        RETURN
        END

C
C                                                               7-25-84
C  *************************************************************************
        SUBROUTINE PLOT21(IPACK,MCRV)
C  *************************************************************************
C       PLCTS THE LEGEND & THE GRID AND ENDS THIS GRAPH
C       ********************************************************************
C
        IMPLICIT INTEGER(I-N)
        DIMENSICN IPACK(100)
C
        XW=XLEGND(IPACK,MCRV)
        YW=YLEGND(IPACK,MCRV)
        CALL LEGEND(IPACK,MCRV,0.5,0.5)
        CALL BLREC(0.4,0.4,XW+0.2,YW+0.2,.01)
        CALL DCT
```

```
      CALL GRID(1,1)
      CALL RESET('DOT')
      CALL ENDPL(0)
      RETURN
      END
C
C                                                          09-05-84
C ******************************************************************
      SUBROUTINE PLOT3(NPTS,PTS,TITLE)
C     ******************************************************************
C     CREATES A 3-D GEOGRAPHICAL PLOT OF MISSILE AND TARGET
C     TRACKS. BY CHANGING THE VIEWPOINT YOU CAN OBSERVE DIFFERENT
C     PORTIONS OF THE MISSION FROM VARIOUS PERSPECTIVES.
C     ******************************************************************
      IMPLICIT REAL(A-H,O-Z), INTEGER(I-N)
      INTEGER TITLE(8,4),HD(8)
      DIMENSION PTS(300,20),XP(300),YP(300),ZP(300),IPACK(100)
C
C     CALL BLOWUP(1.0)
C
C *** CREATE THE TITLES
C
      DO 40 J=1,3
         DO 30 I=1,8
            HD(I)      = TITLE(I,J)
 30      CONTINUE
         CALL HEADIN(HD  ,32   ,  1.1  ,4)
 40   CONTINUE
      CALL HEADIN('GEOGRAPHICAL TRACKS',19,1.0,4)
C
C *** DEFINE THE WORKBOX
C
      CALL VOLM3D(10,20,7.5)
C
C *** LABEL THE AXES
C
      CALL X3NAME('FEET EAST',9)
      CALL Y3NAME('FEET NORTH',10)
      CALL Z3NAME('ALTITUDE (FT)',13)
C
C *** DEFINE THE VIEWPOINT
C
      CALL VUANGL(130,40,26)
C
C *** SET UP THE AXIS SYSTEM
C
      CALL CROSS
      CALL GRAF3D(-1000.,1000.,4000.,   0.0,5000.,25000.,
```

```
     *                 0.0,100.0,300.0)
C
C *** DRAW THE MISSILE'S TRACK
C
      IX    = 15
      IY    = 14
      IZ    = 13
C
      DO 50  J=1,NPTS
                 XP(J)  =  PTS(J+2,IX)
                 YP(J)  =  PTS(J+2,IY)
                 ZP(J)  =  PTS(J+2,IZ)
   50 CONTINUE
      CALL CLFV3D(XP,YP,ZP,NPTS,2)
C
C *** NOW PLOT THE TARGET'S TRACK
C
      IX    = 17
      IY    = 16
      IZ    =  0
C
      DO 60  J=1,NPTS
                 XP(J)  =  PTS(J+2,IX)
                 YP(J)  =  PTS(J+2,IY)
                 ZP(J)  =  10.0
   60 CONTINUE
      CALL CLFV3D(XP,YP,ZP,NPTS,5)
C
      CALL ENCPL(0)
      RETURN
      END
*************************************************************************

                          FILE #2 CONTENTS
                 CONTAINS ALL TITLES AND LABELS USED

GLOBAL TITLE LINES:'    CRUISE MISSILE TESTS       '
                   '  SEA SKIMMER (BTT) - NO PUPUP '
                   '    HI-FREQ SCANS - 0.0-30.0   '
                   '           9-17-84             '
PLOT & AXIS LABELS:'   NORMAL LOAD FACTOR   '     *************
           X..... '          TIME          '        GRAPH 1
           Y..... '  CMC & ACTUAL NZC, NZY '     *************
                  '   BANK ANGLE CONTROL   '     *************
           X..... '          TIME          '        GRAPH 2
           Y..... '  COMMANDED & ACTUAL PHI'     *************
                  '    ROLL RATE CONTROL   '     *************
```

```
           X.....  '        TIME               '      GRAPH 3
           Y.....  ' COMD & ACTUAL RCLL RATE   '   *************
                   '   ECM & GLINT SIGNALS     '   *************
           X.....  '          TIME             '      GRAPH 4
           Y.....  '    ECM & GLINT Y-SHIFT    '   *************
                   '     FLIGHT CONTROLS       '   *************
           X.....  '          TIME             '      GRAPH 5
           Y.....  ' 3 PRIMARY FLT. CCNTRCLS   '   *************
                   '    ALTITUDE CONTROL       '   *************
           X.....  '          TIME             '      GRAPH 6
           Y.....  '     ACTUAL ALTITUDE       '   *************
                   '                           '   *************
           X.....  '                           '      BLANK
           Y.....  '                           '   *************
LEGENDS:   1.      'TIME.......(SEC)  '       ********************
           2.  G1. 'NZC..........(G)  '       PARAMETERS STORED BY
           3.      'NZ...........(G)  '             PREPARE
           4.  G2. 'BANKC......(DEG)  '       ********************
           5.      'BANK.......(DEG)  '
           6.  G3. 'R/RT CMD...(DPS)  '
           7.      'ROLL RATE..(DPS)  '
           8.  G4. 'ECM SHIFT...(FT)  '
           9.      'GLINT SHIFT(FT)   '
          10.  G5. 'STBLTR.....(DEG)  '
          11.      'AILRON.....(DEG)  '
          12.      'RUDDER.....(DEG)  '
          13.  G6. 'ALTITUDE....(FT)  '
          14.  XX. 'XM...(FT NORTH)   '
          15.      'YM....(FT EAST)   '
          16.      'XT...(FT NORTH)   '
          17.      'XM....(FT EAST)   '
          18.      'RANGE.......(FT)  '
          19.      ' PHASE MARKER     '
          20.      'NYC..........(G)  '
```

```
C
C
C
C                         APPENDIX E
C
C                  LISTING FOR SUBROUTINE MISSN1
C
C                                                          9-07-84
C *****************************************************************
      SUBROUTINE MISSN1
C *****************************************************************
C     SEA SKIMMER GUIDANCE SCHEME. ALLOWS VARIABLE POPUP IN CLOSE
C     WITH NC OFFSET TURN. AFTER POPUP, GUIDANCE IS STANDARD PRO-
C     PORTIONAL. POPUP USES ONLY ALTITUDE COMMAND VICE GAMMAC.
C
C     MAKES MISSION PHASE DECISIONS AND INVOKES THE DIFFERENT MODES
C     OF GUIDANCE AS REQUIRED. DELIVERS NZC AND PHIC TO THE AUTOPILOT
C     CONTROL LOOPS. NYC IS ASSUMED TO ALWAYS BE ZERO. NZC IS LIMITED
C     TO +4.0 AND -2.0 G'S.
C     *************************************************************
C
      IMPLICIT REAL(A-Z)
      INTEGER PH1,PH2,PH3,PH4,I,J,K,N,NPTS,CPA,NOLT,PCOUNT,NFAZE
C
C
C     ****************************************
C     COMMON BLOCK /A/: MISCELLANEOUS CONSTANTS
C     ****************************************
C
      COMMON /A/ TIME   ,FINTIM,DT    ,CPDT ,NOLT ,NPTS ,CPA   ,PCOUNT,
     *           G      ,T     ,RHO   ,PI   ,PII  ,MASS ,WT    ,S     ,
     *           IXX    ,IYY   ,IZZ   ,IXZ  ,IA   ,IB   ,IC    ,QS    ,
     *           ID     ,IE    ,IF    ,IG   ,IH   ,II   ,IJ    ,IK    ,
     *           CHORD2,CHORD ,SPAN2,SPAN ,NFAZE
C
C
C     ****************************************
C     COMMON BLOCK /C/: CONTROL SYSTEM PARAMETERS
C     ****************************************
C
      COMMON /C/ KPTCHR       ,KROLLR       ,KYAWRT       ,KBANK       ,
     *           KGAMMA       ,KALT         ,CGARML       ,CGARMN      ,
     *           RRTLIM       ,PLIM         ,KNY          ,KNZ         ,
     *           AILRON       ,STBLTR       ,RUDDER       ,
     *           BSERO        ,NZSERO       ,NYSERO
C
C     ****************************************
C     COMMON BLOCK /D/: MISSILE FLIGHT DYNAMICS PARAMETERS
```

```
C     ********************************************
C
      COMMON /D/ ALFA          ,BETA         ,VT          ,HMDOT       ,
     *           U             ,V            ,W           ,
     *           PHI           ,GAMMA        ,THETA       ,SY          ,
     *           CD            ,CY           ,CL          ,CR          ,
     *           CM            ,CN           ,P           ,Q           ,
     *           R             ,ALFADT       ,BETADT      ,PDOT        ,
     *           QDOT          ,RDOT         ,NZ          ,ALTUDE      ,
     *           XM            ,YM           ,XMDCT       ,YMDOT
C
C     ********************************************
C     COMMON BLOCK /F/: GUIDANCE PARAMETERS
C     ********************************************
C
      COMMON /F/ PH1           ,PH2          ,PH3         ,PH4         ,
     *           OFFSET        ,ALTATT       ,SGDZPU      ,MISDST      ,
     *           LAMDAZ        ,LAMDEL       ,KNFAZ       ,KNFEL       ,
     *           NZC           , PHIC        ,GAMMAC      ,PCLIM       ,
     *           PC            ,QC           ,RC          ,RANGE       ,
     *           SIGAZ         ,SIGEL        ,SIGDAF      ,SIGDEF      ,
     *           SYT           ,THETAT       ,XT          ,YT          ,
     *           HT            ,NYC          ,POPRNG
C
C     ********************************************
C     COMMON BLOCK /G/: OUTPUT PARAMETERS
C     ********************************************
C
      COMMON /G/ AOA           ,SIDESL       ,BANK        ,FLTPHC      ,
     *           BANKC         ,PITCH        ,ROLLRT      ,ROLRTC      ,
     *           PTCHRT        ,YAWRT        ,HEADNG      ,FLTPTH      ,
     *           HEADT         ,ELEVT        ,DSIGAZ      ,DSIGEL      ,
     *           DSGDAZ        ,DSGDEL       ,ERFBK       ,ERFRR       ,
     *           ERFAZ         ,ERFEL
C
C EXECUTABLE STMTS:
C*************************************************************************
C
C     SET POPUP RANGE AND ALTITUDE
C
      POPRNG  =  15000.
C
C     MISSION PHASE LOGIC AND GUIDANCE COMMANDS
C
    1 IF(PH4.EQ.1) GO TO 40
      IF(PH1.EQ.1) GO TO 30
C
C *** INGRESS FROM INITIAL CONDITION TO POPUP MANEUVER
```

```
C
      IF(RANGE.LT.POPRNG) GO TO 9
C
C         ALTITUDE HOLD
C
          ALTC   = 50.0
          ALTUDF = ALTUDE
          GAMMAC = KALT*(ALTC-ALTUDF)/VT
          GAMMAF = GAMMA
          AZC    = COS(GAMMAF)+KGAMMA*VT*(GAMMAC-GAMMAF)/G
C
C         PROPORTIONAL NAVIGATION IN AZIMUTH
C
          AYC    = LAMDAZ*VT*SIGDAF/G
          PHIC   = ATAN2(AYC,AZC)
          NZC    = AZC*COS(PHI)+AYC*SIN(PHI)
          GO TO 100
    9     PH1    = 1
C
C ***  PULLUP TO ATTACK ALTITUDE
C      PROPORTIONAL NAVIGATION IN AZIMUTH
C
   30 IF(ALTUDE.GE.ALTATT) GO TO 39
C
C         COMMAND ATTACK ALTITUDE
C
          ALTC   = ALTATT
          ALTUDF = ALTUDE
          GAMMAC = KALT*(ALTC-ALTUDF)/VT
          GAMMAF = GAMMA
          AZC    = COS(GAMMAF)+KGAMMA*VT*(GAMMAC-GAMMAF)/G
C
C         PROPORTIONAL NAVIGATION IN AZIMUTH
C
          AYC    = LAMDAZ*VT*SIGDAF/G
          NZC    = AZC*COS(PHI)+AYC*SIN(PHI)
          PHIC   = ATAN2(AYC,AZC)
          GO TO 100
   39     PH4    = 1
C
C ***  ATTACK - BANK-TO-TURN OR SKID-TO-TURN OR BOTH
C      PROPORTIONAL NAVIGATION IN AZIMUTH AND ELEVATION
C
   40     ALTC   = 0.0
          GAMMAC = 0.0
          GAMMAF = GAMMA
          AYC    = LAMDAZ*VT*SIGDAF/G
          AZC    = LAMDEL*VT*SIGDEF/G+COS(GAMMAF)
```

```
C
C          FOR FINAL ATTACK, ENABLE NEGATIVE G COMMAND AND LATERAL
C          G COMMAND (NYC), OR LEAVE NYC = 0.0.
C
           NZC     = AZC*COS(PHI)+AYC*SIN(PHI)
           NYC     = 0.0
C ************ PATCH TO ENABLE SKID TO TURN (KTEST = 1)
      KTEST = 0
      IF(KTEST.EQ.1) GO TO 95
C ************ END
C
C
C          TURN TO PLACE THE NEAREST NZ VECTOR (+ OR-) IN THE DESIRED
C          DIRECTION.
C
           PHI     = ANGLE(PHI)
           PHIG    = ANGLE(ATAN2(AYC,AZC))
           IF (ABS(PHIG-PHI).LE.PI/2.) GO TO 50
              PHIC =ANGLE(PHIG+PI)
              GO TO 60
  50       CONTINUE
              PHIC = PHIG
  60       CONTINUE
C
C          ENSURE THE MISSILE ROLLS IN THE SHORTEST DIRECTION TO PHIC.
C
           DELPHI = PHIC-PHI
           DPHIAB = ABS(DELPHI)
           IF(DPHIAB.LT.PI) GO TO 100
           IF(PHIC.GE.0.0) GO TO 90
           PHIC    = PHIC+2.0*PI
           GO TO 100
  90       PHIC    = PHIC-2.0*PI
           GO TO 100
C
C *** FOR SKID TO TURN ONLY, SET PHIC TO 0.
C
  95       PHIC    = 0.0
           NYC     = AYC*COS(PHI)-AZC*SIN(PHI)
C
 100  CONTINUE
C ***********************************************************************
C
C     NZ COMMAND LIMITED TO -2 & +4 G'S.
C
      NZC= LIMIT(-2.0, 4.0,NZC)
      NYC= LIMIT(-1.0,1.0,NYC)
C
      RETURN
```

```
      END
C
C                                                                   9-06-84
C  ************************************************************************
      FUNCTION ANGLE(THETA)
C  ************************************************************************
C     LIMITS ANGLES IN RADIANS TO THE RANGE +PI TO -PI.
C     ********************************************************************
C
      IMPLICIT REAL(A-Z)
C
      DATA PI /3.1415962/
C
   10 IF(THETA.LT.PI) GO TO 20
          THETA = THETA - 2*PI
          GO TO 10
   20 CONTINUE
C
   30 IF(THETA.GT.-PI) GO TO 40
          THETA = THETA + 2*PI
          GO TO 30
   40 CONTINUE
      ANGLE     = THETA
      RETURN
      END
```

```
C
C
C
C                           APPENDIX F
C
C                  LISTING FOR SUBROUTINE MISSN2
C
C
C
C                                                                  9-07-84
C  ****************************************************************************
      SUBROUTINE MISSN2
C  ****************************************************************************
C     BALLISTIC  GUIDANCE SCHEME. ALLOWS VARIABLE POPUP IN CLOSE
C     WITH NO OFFSET TURN. AFTER POPUP, MISSILE ROLLS TO 90 DEGREES
C     ANGLE OF BANK AND USES LATERAL AND VERTICAL PROPORTIONAL NAV.
C
C     MAKES MISSION PHASE DECISIONS AND INVOKES THE DIFFERENT MODES
C     OF GUIDANCE AS REQUIRED. DELIVERS NZC AND PHIC TO THE AUTOPILOT
C     CONTROL LOOPS. NYC IS ASSUMED TO ALWAYS BE ZERO. NZC IS LIMITED
C     TO +4.0 AND -2.0 G'S.
C     ************************************************************************
C
      IMPLICIT REAL(A-Z)
      INTEGER PH1,PH2,PH3,PH4,I,J,K,N,NPTS,CPA,NOLT,PCOUNT,NFAZE
C
      COMMON /A/ TIME   ,FINTIM,DT    ,CPDT  ,NCUT  ,NPTS  ,CPA   ,PCOUNT,
     *           G      ,T     ,RHO   ,PI    ,PII   ,MASS  ,WT    ,S     ,
     *           IXX    ,IYY   ,IZZ   ,IXZ   ,IA    ,IB    ,IC    ,GS    ,
     *           ID     ,IE    ,IF    ,IG    ,IH    ,II    ,IJ    ,IK    ,
     *           CHORD2,CHORD  ,SPAN2 ,SPAN  ,NFAZE
C
      COMMON /C/ KPTCHR        ,KROLLR        ,KYAWRT        ,KBANK         ,
     *           KGAMMA        ,KALT          ,CGARML        ,CGARMN        ,
     *           RRTLIM        ,PLIM          ,KNY           ,KNZ           ,
     *           AILRON        ,STBLTR        ,RUDDER        ,
     *           BSERO         ,NZSERO        ,NYSERO
C
      COMMON /D/ ALFA          ,BETA          ,VT            ,HMDOT         ,
     *           L             ,V             ,W             ,
     *           PHI           ,GAMMA         ,THETA         ,SY            ,
     *           CD            ,CY            ,CL            ,CR            ,
     *           CM            ,CN            ,P             ,Q             ,
     *           R             ,ALFADT        ,BETADT        ,PDOT          ,
     *           QDOT          ,RDOT          ,NZ            ,ALTUDE        ,
     *           XM            ,YM            ,XMDOT         ,YMDOT
C
      COMMON /F/ PH1           ,PH2           ,PH3           ,PH4           ,
     *           OFFSET        ,ALTATT        ,SGDZPU        ,MISDST        ,
```

```
     *              LAMDAZ        ,LAMDEL      ,KNFAZ       ,KNFEL       ,
     *              NZC           , PHIC       ,GAMMAC      ,PCLIM       ,
     *              PC            ,QC          ,RC          ,RANGE       ,
     *              SIGAZ         ,SIGEL       ,SIGDAF      ,SIGDEF      ,
     *              SYT           ,THETAT      ,XT          ,YT          ,
     *              HT            ,NYC         ,POPRNG
C
      COMMON /G/    AOA           ,SIDESL      ,BANK        ,FLTPHC      ,
     *              BANKC         ,PITCH       ,ROLLRT      ,ROLRTC      ,
     *              PTCHRT        ,YAWRT       ,HEADNG      ,FLTPTH      ,
     *              HEADT         ,ELEVT       ,DSIGAZ      ,DSIGEL      ,
     *              DSGDAZ        ,DSGDEL      ,ERFEK       ,ERFRR       ,
     *              ERFAZ         ,ERFEL
C
C EXECUTABLE SIMTS:
C***********************************************************************
C
C     SET POPUP RANGE AND A PARABOLIC ALTITUDE TRACK
C
      POPRNG  = 15000
      VH   =  SQRT(XMDOT**2+YMDOT**2)
      ALTATT   = HMDOT*RANGE/VH + (G/2.)*(RANGE/VT)**2 + 10.
C
C     MISSION PHASE LOGIC AND GUIDANCE COMMANDS
C
    1 IF(PH4.EQ.1) GO TO 40
      IF(PH1.EQ.1) GO TO 30
C
C *** INGRESS FROM INITIAL CONDITION TO POPUP MANEUVER
C
         IF(RANGE.LT.POPRNG) GO TO 9
C
C           ALTITUDE HOLD
C
            ALTC    = 50.0
            ALTUDF =  ALTUDE
            GAMMAC =  KALT*(ALTC-ALTUDF)/VT
            GAMMAF =  GAMMA
            AZC     = COS(GAMMAF)+KGAMMA*VT*(GAMMAC-GAMMAF)/G
C
C           PROPORTIONAL NAVIGATION IN AZIMUTH
C
            AYC     = LAMDAZ*VT*SIGDAF/G
            PHIC    = ATAN2(AYC,AZC)
            NZC     = AZC*COS(PHI)+AYC*SIN(PHI)
            GO TO 100
    9       PH1     = 1
C
```

```
C ***     PULLUP TC ATTACK ALTITUDE
C         PROPCRTICNAL NAVIGATION IN AZIMUTH
C
C ************* PATCH  TC RETAIN BTT GUIDANCE TO IMPACT (KTEST=1)
      KTEST = 1
      IF(KTEST.EQ.1) GO TO 32
C ************* ENDPATCH
   3C     IF(ALTUDE.GE.ALTATT) GO TO 39
C
   32     CONTINUE
C            CCMMAND BALLISTIC ATTACK ALTITUDE
C
             ALTC   =  ALTATT
             ALTUDF =  ALTUDE
             GAMMAC =  KALT*(ALTC-ALTUDF)/VT
             GAMMAF =  GAMMA
             AZC    =  COS(GAMMAF)+KGAMMA*VT*(GAMMAC-GAMMAF)/G
C
C            PRCPORTIONAL NAVIGATION IN AZIMUTH
C
             AYC    =  LAMDAZ*VT*SIGDAF/G
             NZC    =  AZC*COS(PHI)+AYC*SIN(PHI)
             PHIC   =  ATAN2(AYC,AZC)
             GC TO 100
   39        FF4    =  1
C
C ***     ATTACK
C         PRCPCRTIONAL NAVIGATION IN AZIMUTH AND ELEVATION
C
C            CCMMAND ATTACK ALTITUDE & ROLL TC 90 DEG BANK.
C
   4C        PHIC   =  PI/2.
             ALTC   =  ALTATT
             ALTUDF =  ALTUDE
             GAMMAC =  KALT*(ALTC-ALTUDF)/VT
             GAMMAF =  GAMMA
             AZC    =  KGAMMA*VT*(GAMMAC-GAMMAF)/G
C
C            PRCPCRTIONAL NAVIGATION IN AZIMUTH
C
             AYC    =  LAMDAZ*VT*SIGDAF/G
             NZC    =  AZC*COS(PHI)+AYC*SIN(PHI)
C            NYC    =  AYC*COS(PHI)-AZC*SIN(PHI)
             NYC    =  0.0
C
  10C CONTINUE
C ***************************************************************************
C
```

```
C       NZ COMMAND LIMITED TU -2 & +4 G'S; NYC TO +- 0.5 G.
C
        NZC= LIMIT(-2.0, 4.0,NZC)
        NYC= LIMIT(-0.5, 0.5,NYC)
C
        RETURN
        END
```

## LIST OF REFERENCES


1. Patterson, Kent B., Bank-To-Turn Cruise Missile Terminal Guidance and Control Law Comparison, MS Thesis, Navy Postgraduate School, Monterey, California, 1983.

2. IBM Company, Continuous System Modelling Program III (CSMP III) Program Reference Manual, Program Number 5734-XS9, December 1975.

3. Speclchart, F.H., and Green, W. L., A Guide to Using CSMP-The Continuous System Modeling Program, Prentice-Hall, 1976.

4. Hewett, M.D., Guidance and Control Systems Course (Class Notes), 1983.

5. Roskam, J., Airplane Flight Dynamics and Automatic Flight Controls, Roskam Aviation and Engineering Corp., 1979.

INITIAL DISTRIBUTION LIST

| | | No. Copies |
|---|---|---|
| 1. | Defense Technical Information Center<br>Cameron Station<br>Alexandria, Virginia 22314 | 2 |
| 2. | Library, Code 0142<br>Naval Postgraduate School<br>Monterey, California 93943 | 2 |
| 3. | Dr. Marle D. Hewett<br>H.R Textron, Inc.<br>2485 McCabe Way<br>Irvine, California 92714 | 2 |
| 4. | CDR Barton P. Anderson, USN<br>Naval Air Rework Facility<br>Naval Air Station<br>Pensacola, Florida 32508 | 2 |

210090

Thesis
A4446 Anderson
c.1 An investigation into the control limitations of a bank to turn missle in the terminal homing phase.